



Gorilla Wood Glue

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name	Gorilla Wood Glue
CAS No.	Not applicable.
EC No.	Not applicable.
Registration number(s)	Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Adhesives.
Uses Advised Against	Not known.

1.3 Details of the supplier of the safety data sheet

Manufacturer

Company Identification	Gorilla Glue Europe Ltd
Address of Manufacturer	26 Eaton Avenue Matrix Park Buckshaw Village Chorley Lancashire
Postal code	PR7 7NA
Telephone:	01257 241 319
E-mail	Eucustomercare@gorillaglu.com
Office hours	08:30 - 17:00

Supplier

Company Identification	Gorilla Glue Europe Ltd
Address of Supplier	26 Eaton Avenue Matrix Park Buckshaw Village Chorley Lancashire
Postal code	PR7 7NA
Telephone:	01257 241 319
E-mail	Eucustomercare@gorillaglu.com
Office hours	08:30 - 17:00

1.4 Emergency telephone number

Emergency Phone No.	+44 (0)843 507 1200
Contact	Stuart Shotton
National response centre	
Address	NHS Direct
Emergency Phone No.	+44 111

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture



Gorilla Wood Glue

GB CLP Regulation, UK SI 2019/720
and UK SI 2020/1567

Not classified as hazardous for supply.

2.2 Label elements

Product Name

According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567
Gorilla Wood Glue

Hazard Pictogram(s)

None.

Signal Word(s)

None.

Hazard Statement(s)

EUH210: Safety data sheet available on request.

EUH208: Contains: (Formaldehyde, 2-methylisothiazol-3(2H)-one) May produce an allergic reaction.

Precautionary Statement(s)

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P501: Dispose of contents in accordance with local, state or national legislation.

2.3 Other hazards

Contains 2-methylisothiazol-3(2H)-one, a biocidal product to preserve the product during storage. Please follow all usage instructions.

2.4 Additional Information

None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / Registration number(s)	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Acetic acid ethenyl ester, co-polymer with ethenol	25213-24-5	607-648-9	1-5	Eye Irrit. 2 H319	GHS07
2-(2-butoxyethoxy)ethanol	112-34-5	203-961-6	1-5	Eye Irrit. 2 H319	GHS07
Aluminum chloride, basic	1327-41-9	215-477-2	0.1-1	Met. Corr. 1 H290 Eye Dam. 1 H318	GHS05
Methanol	67-56-1	200-659-6	0.01-0.1	Flam. Liq. 2 H225 Acute Tox. 3 H301 Acute Tox. 3 H311 Acute Tox. 3 H331 STOT SE 1 H370	GHS02 GHS06 GHS08
methyl acetate	79-20-9	201-185-2	0.01-0.1	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 EUH066	GHS02 GHS07
ethyl acetate	141-78-6	205-500-4	0.01-0.1	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 EUH066	GHS02 GHS07



Gorilla Wood Glue

Hydrogen chloride	7647-01-0	231-595-7	0.01-0.1	Skin Corr. 1B H314 STOT SE 3 H335	GHS05 GHS07
2-butoxyethanol	111-76-2	203-905-0	0.01-0.1	Acute Tox. 4 H302 Skin Irrit. 2 H315 Eye Irrit. 2 H319 Acute Tox. 4 H332	GHS07
Vinyl acetate	108-05-4	203-545-4	0.01-0.09	Flam. Liq. 2 H225 Acute Tox. 4 H332 STOT SE 3 H335 Carc. 2 H351	GHS02 GHS08 GHS07
Formaldehyde	50-00-0	200-001-8	0.01-0.05	Acute Tox. 4 H302 Skin Corr. 1B H314 Skin Sens. 1A H317 Acute Tox. 2 H330 Muta. 2 H341 Carc. 1B H350 EUH071	GHS06 GHS05 GHS08 GHS07
2-methylisothiazol-3(2H)-one	2682-20-4	220-239-6	<0.0015	Acute Tox. 3 H301 Acute Tox. 3 H311 Skin Corr. 1B H314 Skin Sens. 1A H317 Eye Dam. 1 H318 Acute Tox. 2 H330 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 EUH071	GHS06 GHS05 GHS07 GHS09

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, obtain medical attention.
Skin Contact	Wash skin with water. If symptoms develop, obtain medical attention.
Eye Contact	Flush eyes with water for at least 15 minutes. If symptoms develop, obtain medical attention.
Ingestion	Wash out mouth with water. If symptoms persist, obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

None anticipated. Treat symptomatically.

4.3 Indication of any immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.



Gorilla Wood Glue

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Unsuitable extinguishing media None.

5.2 Special hazards arising from the substance or mixture

None anticipated. Heating may cause decomposition.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep fire exposed containers cool by spraying with water.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear suitable gloves if prolonged skin contact is likely. Wash hands and exposed skin after use.

6.2 Environmental precautions

Do not release large quantities into the surface water or into drains.

6.3 Methods and material for containment and cleaning up

Dilute with water. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal or recovery.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

General hygiene measures for the handling of chemicals are applicable. Wear protective equipment to comply with good occupational hygiene practice. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wash hands and exposed skin after use. Do not eat, drink or smoke at the work place.

7.2 Conditions for safe storage, including any incompatibilities

Store in a tightly closed container. Keep in a cool, dry place. Keep container closed when not in use.

Storage temperature

>5° C

Storage life

Stable under normal conditions.

Incompatible materials

None known.

7.3 Specific end use(s)

Adhesives.



Gorilla Wood Glue

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTCL (8 hr TWA ppm)	LTCL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
2-(2-Butoxyethoxy) ethanol	112-34-5	10	67.5	15	101.2	
Aluminium salts, soluble	1327-41-9		2			
Vinyl acetate	108-05-4	5	17.6	10	35.2	
Methanol	67-56-1	200	266	250	333	Sk
Methyl acetate	79-20-9	200	616	250	770	
Formaldehyde	50-00-0	2	2.5	2	2.5	Carc
Ethyl acetate	141-78-6	200	734	400	1468	
Hydrogen chloride (gas and aerosol mists)	7647-01-0	1	2	5	8	
2-Butoxyethanol	111-76-2	25	123	50	246	Sk, BMGV

Region	Source
United Kingdom	UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark	Notes
Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
Carc	Capable of causing cancer and/or heritable genetic damage.
BMGV	Biological monitoring guidance values are listed in Table 2.

Biological Exposure Indices						
Substances	CAS Number	Sampling	Tissues	Control parameters	Biological monitoring guidance value	Comments
2-Butoxyethanol	111-76-2	Post shift	urine	butoxyacetic acid	240 mmol butoxyacetic acid/mol creatinine	

8.2 Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation.

8.2.2. Personal protection equipment



Eye Protection

Wear protective eye glasses for protection against liquid splashes.



Skin protection

Not normally required. Wear suitable gloves if prolonged skin contact is likely. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

**Gorilla Wood Glue**

Respiratory protection Normally no personal respiratory protection is necessary.



Thermal hazards Not applicable.

8.2.3. Environmental Exposure Controls Do not release large quantities into the surface water or into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

Appearance	Liquid.
	Colour : Brown.
Odour	Characteristic.
Odour threshold	Not established.
pH	3
Melting point/freezing point	0° C
Initial boiling point and boiling range	100° C
Flash Point	Not known.
Evaporation rate	Not known.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not known.
Vapour pressure	23 hPa @ 20° C
Vapour density	Not known.
Density (g/ml)	1.08
Relative density	Not known.
Solubility(ies)	Solubility (Water) : Completely miscible with water. Solubility (Other) : Not known.
Partition coefficient: n-octanol/water	Not known.
Auto-ignition temperature	Not known.
Decomposition Temperature (° C)	Not known.
Viscosity	Dynamic viscosity : 5000 cP
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2 Other information

None.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

Stable under normal conditions.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.



Gorilla Wood Glue

10.4 Conditions to avoid

Do not freeze. Keep away from heat and light.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity - Ingestion	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 62604.34
Acute toxicity - Skin Contact	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 198150.59
Acute toxicity - Inhalation	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 1060.28
Skin corrosion/irritation	Calculation method : Not classified.
Serious eye damage/irritation	Calculation method : Not classified.
Skin sensitization data	Calculation method : Not classified. It is not a skin sensitiser. Contains: (Formaldehyde, 2-methylisothiazol-3(2H)-one) May produce an allergic reaction.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified. There is no evidence of mutagenic potential.
Carcinogenicity	Calculation method : Not classified. No evidence of carcinogenicity.
Reproductive toxicity	Calculation method : Not classified. No evidence of reproductive effects.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : Not classified.
STOT - repeated exposure	Calculation method : Not classified.
Aspiration hazard	Calculation method : Not classified.

11.2 Other information

Not known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates.
Toxicity - Fish	Low toxicity to fish.
Toxicity - Algae	Low toxicity to algae.
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.



Gorilla Wood Glue

12.2 Persistence and degradability

No information on this formulation.

12.3 Bioaccumulative potential

No information on this formulation.

12.4 Mobility in soil

Miscible with water. The product is predicted to have high mobility in soil.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of empty containers and wastes safely. Dispose at suitable refuse site.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

Not classified as hazardous for transport.

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not classified as a Marine Pollutant.

14.6 Special precautions for user

Not known

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not known

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom Regulations - Authorisations and/or Restrictions On Use

UK REACH Candidate List of Substances of Very High Concern for

Authorisation

UK REACH Authorisation List (Annex

XIV) list of substances subject to authorisation

Not listed

Not listed



Gorilla Wood Glue

UK REACH Restrictions List (Annex XVII) Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	2-(2-butoxyethoxy)ethanol (112-34-5) - Entry 3, 55, 75; Methanol (67-56-1) - Entry 3, 40, 69, 75; Formaldehyde (50-00-0) - Entry 3, 28, 72, 75, 77; Aluminum chloride, basic (1327-41-9) - Entry 3; Vinyl acetate (108-05-4), methyl acetate (79-20-9), ethyl acetate (141-78-6) - Entry 3, 40, 75; Hydrogen chloride (7647-01-0), 2-butoxyethanol (111-76-2) - Entry 3, 75; 2-methylisothiazol-3(2H)-one (2682-20-4) - Entry 75
UK REACH Rolling Action Plan (RAP)	Not listed
Persistent Organic Pollutants (Various Amendments) Regulations 2019 (SI 2019/1099)	Not listed
The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019/583)	Not listed
The Prior Informed Consent (PIC) Regulations concerning the export and import of hazardous chemicals SI2008/2108 as amended	Not listed
European Regulations - Authorisations and/or Restrictions On Use Community Rolling Action Plan (CoRAP)	Aluminum chloride, basic (1327-41-9), Vinyl acetate (108-05-4), Methanol (67-56-1), Formaldehyde (50-00-0)
Seveso Directive	None known.
Regulation (EU) No 528/2012 as retained in UK law and amended by the Biocidal Products (Amendment) (EU Exit) Regulations 2019	Contains a biocide: Contains 2-methylisothiazol-3(2H)-one (PT06 – Preservatives for products during storage).

15.2 Chemical Safety Assessment

United Kingdom	A REACH chemical safety assessment has not been carried out.
----------------	--

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16

LEGEND

Hazard Pictogram(s)	GHS02: GHS: Flame GHS05: GHS: Corrosion GHS06: GHS: Skull and crossbones GHS07: GHS: Exclamation mark GHS08: GHS: Health hazard GHS09: GHS: Environment
---------------------	--

**Gorilla Wood Glue**

Hazard classification

Flam. Liq. 2 : Flammable liquid, Category 2
Met. Corr. 1 : Substance or mixture corrosive to metals, Category 1
Skin Corr. 1B : Skin corrosion/irritation, Category 1B
Skin Irrit. 2 : Skin corrosion/irritation, Category 2
Skin Sens. 1A : Skin sensitization, Category 1A
Eye Dam. 1 : Serious eye damage/irritation, Category 1
Eye Irrit. 2 : Serious eye damage/irritation, Category 2
Acute Tox. 2 : Acute toxicity, Category 2
Acute Tox. 3 : Acute toxicity, Category 3
Acute Tox. 4 : Acute toxicity, Category 4
STOT SE 3 : Specific target organ toxicity — single exposure, Category 3
Muta. 2 : Germ cell mutagenicity, Category 2
Carc. 1B : Carcinogenicity, Category 1B
Carc. 2 : Carcinogenicity, Category 2
STOT SE 1 : Specific target organ toxicity — single exposure, Category 1
Aquatic Acute 1 : Hazardous to the aquatic environment, Acute, Category 1
Aquatic Chronic 1 : Hazardous to the aquatic environment, Chronic, Category 1

Hazard Statement(s)

H225: Highly flammable liquid and vapour.
H290: May be corrosive to metals.
H301: Toxic if swallowed.
H302: Harmful if swallowed.
H311: Toxic in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H330: Fatal if inhaled.
H331: Toxic if inhaled.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H341: Suspected of causing genetic defects.
H350: May cause cancer.
H351: Suspected of causing cancer.
H370: Causes damage to organs.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
EUH210: Safety data sheet available on request.

Precautionary Statement(s)

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P501: Dispose of contents in accordance with local, state or national legislation.



Gorilla Wood Glue

Acronyms

ATE : Acute Toxicity Estimate
CAS : Chemical Abstracts Service
DNEL : Derived No Effect Level
EC : European Community
EINECS : European Inventory of Existing Commercial Chemical Substances
LTEL : Long term exposure limit
PBT : Persistent, Bioaccumulative and Toxic
PNEC : Predicted No Effect Concentration
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL : Short term exposure limit
STOT : Specific Target Organ Toxicity
vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for data used to compile the SDS

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

Training Advice

Regular safety training as appropriate

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Gorilla Glue Europe Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Gorilla Glue Europe Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.