



CE Declaration of Performance

According to Annex III of Regulation (EU) No 305/2011

Gorilla Grab and Seal

117525

EN 15651-1 F-INT-EXT-CC

Sealant for façade elements - For interior and exterior applications (intended for use in cold climates)

EN 15651-3 XS 1

Sealant for sanitary joints

Contact Address of the Manufacturer:

**Gorilla Glue Europe Ltd.
26 Eaton Avenue
Matrix Park
Buckshaw Village
Lancashire
PR7 7NA**

Verification of consistency of performance of the construction product as set out in Annex V:

The notified body **Institute for Testing and Certification**, notified body number **1023**, performed the determination of the product type on the basis of type testing under **System 3** and issued:

Report No.: 755200628/2025

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.



Gorilla Grab and Seal – Declared Performance

EN 15651-1 F-INT-EXT-CC CLASS – 25HM

Pre-Conditioning: Method B (according to ISO 8340)
Substrate: Glass without primer
Aluminium
Mortar M1

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire (EN ISO 11925-2)	E	EN 15651-1: 2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss of volume (ISO 10563)	$\leq 10\%$	
Tensile properties at maintained extension after immersion in water (ISO 10590)	No Failure	
Durability (ISO 9047, ISO 8340)	Pass	



Gorilla Grab and Seal – Declared Performance

EN 15651-3
CLASS – XS 1

Pre-Conditioning: Method B (according to ISO 8340)
Substrate: Glass without primer
Aluminium
Mortar

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire (EN ISO 11925-2)	E	EN 15651-3: 2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss of volume (ISO 10563)	$\leq 20\%$	
Tensile properties at maintained extension after immersion in water (ISO 10590)	No Failure	
Microbiological Growth	0	
Durability (ISO 9047, ISO 8340)	Pass	

Charles Berry
Assistant Regulatory Manager
1st September 2025