

**Gorilla Waterproof Coat and Seal Spray Black**

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier**

Product Name	Gorilla Waterproof Coat and Seal Spray Black
Contains:	Methyl acetate, Reaction mass of ethylbenzene and m-xylene and p-xylene, Hydrocarbons, C9-10, <2% aromatics)
CAS No.	Not applicable.
EC No.	Not applicable.
REACH Registration No.	Not applicable.
Unique Formula Identifier (UFI)	MX00-C083-1006-YPWV

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Sealant spray.
Uses Advised Against	Not known.

1.3 Details of the supplier of the safety data sheet

Manufacturer	
Company Identification	Gorilla Glue Europe Ltd
Address of Manufacturer	26 Eaton Avenue Matrix Park Buckshaw Village Chorley Lancashire
Postal code	PR7 7NA
Telephone:	01257 241 319
E-mail	Eucustomer@gorillaglue.com
Office hours	08:30 - 17:00
Supplier	
Company Identification	Gorilla Glue Europe Ltd
Address of Supplier	26 Eaton Avenue Matrix Park Buckshaw Village Chorley Lancashire
Postal code	PR7 7NA
Telephone:	01257 241 319
E-mail	Eucustomer@gorillaglue.com
Office hours	08:30 - 17:00

1.4 Emergency telephone number

Emergency Phone No.	+44 (0)843 507 1200
Contact	Stuart Shotton
National response centre	
Address	NHS Direct
Emergency Phone No.	+44 111

**Gorilla Waterproof Coat and Seal Spray Black****SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture**

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 Aerosol 1 :Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2 :Causes serious eye irritation.
STOT SE 3 :May cause drowsiness or dizziness.

2.2 Label elements

Product Name According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567
Gorilla Waterproof Coat and Seal Spray Black
Contains: Methyl acetate, Reaction mass of ethylbenzene and m-xylene and p-xylene,
Hydrocarbons, C9-10, <2% aromatics

Hazard Pictogram(s)



GHS02



GHS07

Signal Word(s)

Danger

Hazard Statement(s)

H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
EUH066: Repeated exposure may cause skin dryness or cracking.
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50° C/
122° F.
P501: Dispose of contents in accordance with local, state or national legislation.

2.3 Other hazards

None known.

2.4 Additional Information

For full text of H/P Statements see section 16.

**Gorilla Waterproof Coat and Seal Spray Black****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Product as supplied: Aerosol

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / Registration number(s)	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Methyl acetate	79-20-9	201-185-2	20-30	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 EUH066	GHS02 GHS07
Petroleum gases, liquefied	68476-85-7	270-704-2	10-20	Flam. Gas 1A H220 Press. Gas (Liq.) H280	GHS02 GHS04
Reaction mass of ethylbenzene and m-xylene and p-xylene		905-562-9	1-10	Flam. Liq. 3 H226 Asp. Tox. 1 H304 Acute Tox. 4 H312 Skin Irrit. 2 H315 Eye Irrit. 2 H319 Acute Tox. 4 H332 STOT SE 3 H335 STOT RE 2 H373 Aquatic Chronic 3 H412	GHS02 GHS08 GHS07
Hydrocarbons, C9-10, <2% aromatics	1174921-73-3	807-660-6	1-10	Flam. Liq. 3 H226 Asp. Tox. 1 H304 STOT SE 3 H336 Aquatic Chronic 3 H412	GHS02 GHS08 GHS07
Kieselguhr, soda ash flux-calcined	68855-54-9	272-489-0	1-5	STOT RE 2 H373	GHS08
Talc ($\text{Mg}_3\text{H}_2(\text{SiO}_3)_4$)	14807-96-6	238-877-9	1-5	Not classified	None
Kaolin	1332-58-7	310-194-1	1-3	Not classified	None
Carbon black	1333-86-4	215-609-9	<1	Not classified	None
Magnesium carbonate	546-93-0	208-915-9	<0.3	Not classified	None
Cristobalite	14464-46-1	238-455-4	<0.3	STOT RE 2 H373	GHS08
Quartz (SiO_2)	14808-60-7	238-878-4	<0.1	Not classified	None

For full text of H/P Statements see section 16.

**Gorilla Waterproof Coat and Seal Spray Black****SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures**

Inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
Skin Contact	Wash skin with soap and water. If symptoms persist, obtain medical attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Unlikely route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

5.1 Extinguishing media

Suitable Extinguishing media	Extinguish with carbon dioxide, dry chemical, foam or waterspray.
Unsuitable extinguishing media	Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Heating may cause pressure rise with risk of bursting. May decompose in a fire, giving off toxic and irritant vapours.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate sources of ignition. Provide adequate ventilation. Avoid breathing spray. Wear appropriate personal protective equipment, avoid direct contact. Wash hands and exposed skin after use.

6.2 Environmental precautions

Do not release large quantities into the surface water or into drains.

6.3 Methods and material for containment and cleaning up

Collect mechanically and dispose of according to Section 13. Absorb remaining liquid in sand or inert absorbent and remove to safe place. Transfer to a container for disposal.

6.4 Reference to other sections

See Also Section 8, 13.

**Gorilla Waterproof Coat and Seal Spray Black****SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling**

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing spray. Avoid contact with eyes. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke at the work place. Wash hands and exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Storage temperature

Do not expose to temperatures exceeding 50° C/ 122° F.

Storage life

Stable under normal conditions.

Incompatible materials

None known.

7.3 Specific end use(s)

Sealant spray.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****8.1.1 Occupational Exposure Limits**

SUBSTANCE	CAS No.	LTCL (8 hr TWA ppm)	LTCL (8 hr TWA mg/m ³)	STCL (ppm)	STCL (mg/m ³)	Note
Methyl acetate	79-20-9	200	616	250	770	
Liquefied petroleum gas	68476-85-7	1000	1750	1250	2180	(f)
Talc, respirable dust	14807-96-6		1			
Kaolin, respirable dust	1332-58-7		2			
Carbon black	1333-86-4		3.5		7	
Magnesite inhalable dust	546-93-0		10			
Magnesite respirable dust	546-93-0		4			
Refractory ceramic fibres and special purpose fibres - total inhalable dust	14464-46-1		5			Carc
Refractory ceramic fibres and special purpose fibres - respirable fraction	14464-46-1					Carc, (I)
Silica, respirable crystalline (respirable fraction)	14464-46-1		0.1			(t)
Silica, respirable crystalline (respirable fraction)	14808-60-7		0.1			(t)

Region

Source

United Kingdom

UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark

Notes

**Gorilla Waterproof Coat and Seal Spray Black**

(f)	Carc (only applies if LPG contains more than 0.1% of buta-1,3-diene)
Carc	Capable of causing cancer and/or heritable genetic damage.
(i)	0.3 fibres/millilitre
(t)	Carc (where generated as a result of a work process)

8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Ensure adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment**Eye Protection**

Wear eye protection with side protection (EN ISO 16321-1).

**Skin protection**

Wear protective clothing and gloves: Impervious gloves (EN 374). Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

**Respiratory protection**

Wear suitable respiratory protection.

**Thermal hazards**

Not applicable.

8.2.3. Environmental Exposure Controls Do not release large quantities into the surface water or into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

Appearance	Aerosol
	Colour : Black.
Odour	Characteristic.
Odour threshold	Not established.
pH	Not known.
Melting point/freezing point	Not known.
Initial boiling point and boiling range	Not known.
Flash Point	-60° C
Evaporation rate	Not known.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not known.
Vapour pressure	Not known.
Vapour density	Not applicable.
Density (g/ml)	0.99
Relative density	Not applicable.
Solubility(ies)	Solubility (Water) : Insoluble.
	Solubility (Other) : Most organic solvents.

**Gorilla Waterproof Coat and Seal Spray Black**

Partition coefficient: n-octanol/water	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition Temperature (° C)	Not known.
Viscosity	Kinematic Viscosity : 353 mm ² /s
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2 Other information

Volatile Organic Compound Content (%): 57.8

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

Stable under normal conditions.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Keep away from heat, sources of ignition and direct sunlight.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects**

Acute toxicity - Ingestion	Calculation method : Not classified.
Acute toxicity - Skin Contact	Calculation method : Not classified.
	Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 12087.91
Acute toxicity - Inhalation	Calculation method : Not classified.
	Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 16.48
Skin corrosion/irritation	Calculation method : Not classified.
Serious eye damage/irritation	Calculation method : Causes serious eye irritation. methyl acetate : The maximum average score was 1.7 for the cornea, 1.0 for the iris, 3.0 for the conjunctivae and 2.0 for chemosis. There was a complete reversibility within 7 days for all 4 responses.
Skin sensitization data	Calculation method : Not classified. It is not a skin sensitiser.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified. There is no evidence of mutagenic potential.
Carcinogenicity	Calculation method : Not classified. No evidence of carcinogenicity.
Reproductive toxicity	Calculation method : Not classified. No evidence of reproductive effects.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : May cause drowsiness or dizziness.

**Gorilla Waterproof Coat and Seal Spray Black**

STOT - repeated exposure
Aspiration hazard

Methyl acetate was evaluated in an EU Risk assessment and has a harmonised classification for STOT SE 3 (H336).

Calculation method : Not classified.

Not classified

11.2 Other information

Not known.

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity**

Toxicity - Aquatic invertebrates Low toxicity to invertebrates.

Toxicity - Fish Low toxicity to fish.

Toxicity - Algae Low toxicity to algae.

Toxicity - Sediment Compartment Not classified.

Toxicity - Terrestrial Compartment Not classified.

12.2 Persistence and degradability

Part of the components are biodegradable.

12.3 Bioaccumulative potential

The product has low potential for bioaccumulation.

12.4 Mobility in soil

Insoluble in water. The product is predicted to have low mobility in soil.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty.

Non-emptied aerosol : Dispose of wastes in an approved waste disposal facility.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION**14.1 UN number**

UN No. 1950

14.2 UN proper shipping name

UN proper shipping name AEROSOLS

14.3 Transport hazard class(es)

**Gorilla Waterproof Coat and Seal Spray Black**

ADR/RID

ADR/RID Class	2
ADR Classification Code	5F
Special Provisions	190 327 344 625
Limited Quantities	1 L
Excepted Quantities	E0
Emergency Action Code	
Packing Instructions for Packages	P207 LP200
Special Packing Provisions for Packages	PP87 RR6 L2
Mixed Packing Instructions for Packages	MP9
Instructions for Portable Tanks	
Special Provisions for Portable Tanks	
Tank Code for Tanks	
Special Provisions for Tanks	
Vehicle for Tank Carriage	
ADR Transport Category	2
Tunnel Restriction Code	D
Special Provisions for Carriage - Packages	V14
Special Provisions for Carriage - Bulk	
Special Provisions for Carriage - Loading, Unloading and Handling	CV9 CV12
Special Provisions for Carriage - Operation	S2

ADR HIN

IMDG

IMDG Class	2
Special Provisions	190 327 344 625
Limited Quantities	1 L
Excepted Quantities	E0
Mixed Packing Instructions for Packages	P207 LP200
Special Packing Provisions for Packages	PP87 RR6 L2
Instructions for Portable Tanks	
Special Provisions for Portable Tanks	
IMDG EMS	F-D, S-U
Stowage and Handling	SW1 SW22
Segregation	SG69
Marine Pollutant	Not classified as a Marine Pollutant.

ICAO/IATA

ICAO/IATA Class	2.1
Excepted Quantities	E0
Passenger and Cargo Aircraft Limited Quantities Packing Instructions	Y203
Passenger and Cargo Aircraft Limited Quantities Max net Qty	30Kg G

**Gorilla Waterproof Coat and Seal Spray Black**

Passenger and Cargo Aircraft Packing Instructions	203
Passenger and Cargo Aircraft Max net Qty	75Kg
Cargo Aircraft Packing Instructions	203
Cargo Aircraft Max net Qty	150Kg
Special Provisions	A145, A167, A802
Emergency Response Guidebook (ERG) Code	10L
Labels	
Labels	2.1

**14.4 Packing group**

Packing group

14.5 Environmental hazards

Environmental hazards Not classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No information available

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

United Kingdom Regulations - Authorisations and/or Restrictions On Use

UK REACH Candidate List of Substances Not listed

of Very High Concern for Authorisation

UK REACH Authorisation List (Annex XIV) Not listed

list of substances subject to authorisation

UK REACH Restrictions List (Annex XVII) methyl acetate (79-20-9) - Entry 3, 40, 75, Petroleum gases, liquefied (68476-85-7),

Restrictions on the manufacture, placing Reaction mass of ethylbenzene and m-xylene and p-xylene (905-562-9),

on the market and use of certain Hydrocarbons, C9-10, <2% aromatics (1174921-73-3) - Entry 40

dangerous substances, mixtures and articles

UK REACH Rolling Action Plan (RAP) Not listed

Persistent Organic Pollutants (Various Amendments) Regulations 2019 (SI 2019/1099) Not listed

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019/583) Not listed

**Gorilla Waterproof Coat and Seal Spray Black**

The Prior Informed Consent (PIC)	Not listed
Regulations concerning the export and import of hazardous chemicals	
SI2008/2108 as amended	
European Regulations - Authorisations and/or Restrictions On Use	
Community Rolling Action Plan (CoRAP)	Reaction mass of ethylbenzene and m-xylene and p-xylene (905-562-9), Carbon black (1333-86-4)
Seveso Directive	Code P3a : Lower Tier Quantity 150 - Upper Tier Quantity 500
15.2 Chemical Safety Assessment	
United Kingdom	A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-2, 8, 11, 14-16

LEGEND

Hazard Pictogram(s)



GHS02
GHS04: GHS: Gas cylinder
GHS08: GHS: Health hazard



GHS07

Hazard classification

Flam. Gas 1A : Flammable gas Category 1A
Aerosol 1 : Aerosol, Category 1
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Press. Gas (Liq.) : Gases under pressure, Liquefied gas
Asp. Tox. 1 : Aspiration hazard, Category 1
Acute Tox. 4 : Acute toxicity, Category 4
Skin Irrit. 2 : Skin corrosion/irritation, Category 2
Eye Irrit. 2 : Serious eye damage/irritation, Category 2
STOT SE 3 : Specific target organ toxicity — single exposure, Category 3
STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2
Aquatic Chronic 3 : Hazardous to the aquatic environment, Chronic, Category 3

Hazard Statement(s)

H220: Extremely flammable gas.
H222: Extremely flammable aerosol.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H229: Pressurised container: May burst if heated.
H280: Contains gas under pressure; may explode if heated.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.

**Gorilla Waterproof Coat and Seal Spray Black**

H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H373: May cause damage to organs through prolonged or repeated exposure.
H412: Harmful to aquatic life with long lasting effects.
EUH066: Repeated exposure may cause skin dryness or cracking.

Precautionary Statement(s)

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P261: Avoid breathing spray.
P264: Wash hands and exposed skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312: Call a POISON CENTRE/doctor if you feel unwell.
P337+P313: If eye irritation persists: Get medical advice/attention.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P405: Store locked up.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50° C/ 122° F.
P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE : Acute Toxicity Estimate
CAS : Chemical Abstracts Service
DNEL : Derived No Effect Level
EC : European Community
EINECS : European Inventory of Existing Commercial Chemical Substances
IATA : International Air Transport Association
IBC : Intermediate Bulk Container
ICAO : International Civil Aviation Organization
IMDG : International Maritime Dangerous Goods
LTEL : Long term exposure limit
PBT : Persistent, Bioaccumulative and Toxic



SAFETY DATA SHEET

Date of Issue: 06-06-2023

Date of Revision: 22-08-2025

Gorilla Waterproof Coat and Seal Spray Black

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

UN : United Nations

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for data used to compile the SDS

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

Training Advice

Regular safety training as appropriate

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Gorilla Glue Europe Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Gorilla Glue Europe Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.