



## CE Declaration of Performance

According to Annex III of Regulation (EU) No 305/2011

**Gorilla Kitchen & Bath Silicone Sealant - Clear**

119598-KBC

---

### **EN 15651-1 F-INT-EXT-CC**

Sealant for façade elements - For interior and exterior applications (intended for use in cold climates)

### **EN 15651-2 G-CC**

Sealant used for sealing glazing applications (intended for use in cold climates)

### **EN 15651-3 S**

Sealant for sanitary joints

---

Contact Address of the Manufacturer:

**Gorilla Glue Europe Ltd.  
26 Eaton Avenue  
Matrix Park  
Buckshaw Village  
Lancashire  
PR7 7NA**

Verification of consistency of performance of the construction product as set out in Annex V:

The notified body **SKZ - TeConA GmbH**, notified body number **NB01213**, performed the determination of the product type on the basis of type testing under **System 3** and issued:  
**Report No.: Report No.: 236801-VI,-VII,-VIII**

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.



**Gorilla Kitchen and Bathroom Silicone Sealant – Clear  
- Declared Performance**

**EN 15651-1 F-INT-EXT-CC  
CLASS – 25LM**

Pre-Conditioning: Method A (according to ISO 8340)  
Substrate: Glass without primer  
Aluminium (anodized, with primer)

| Essential characteristics                                                       | Performance                   | Harmonised technical specification |
|---------------------------------------------------------------------------------|-------------------------------|------------------------------------|
| Reaction to fire (EN 13501)                                                     | E                             | EN 15651-1: 2012                   |
| Release of chemicals dangerous to the environment and health                    | See product safety data sheet |                                    |
| Water tightness and air tightness                                               |                               |                                    |
| Resistance to flow (ISO 7390)                                                   | ≤ 3 mm                        |                                    |
| Loss of volume (ISO 10563)                                                      | ≤ 10%                         |                                    |
| Tensile properties at maintained extension after immersion in water (ISO 10590) | No Failure                    |                                    |
| Secant tensile modulus at -30°C (ISO 8339)                                      | ≤ 0.9 MPa                     |                                    |
| Tensile properties at maintained extension at -30°C (ISO 8340)                  | No Failure                    |                                    |
| Durability (EN 15651)                                                           | Pass                          |                                    |



**Gorilla Kitchen and Bathroom Silicone Sealant – Clear  
- Declared Performance**

**EN 15651-2 G-CC  
CLASS - 25LM**

Pre-Conditioning: Method A (according to ISO 8340)  
Substrate: Glass without primer  
Aluminium (anodized, with primer)

| Essential characteristics                                                       | Performance                   | Harmonised technical specification |
|---------------------------------------------------------------------------------|-------------------------------|------------------------------------|
| Reaction to fire (EN 13501)                                                     | E                             | EN 15651-2: 2012                   |
| Release of chemicals dangerous to the environment and health                    | See product safety data sheet |                                    |
| Water tightness and air tightness                                               |                               |                                    |
| Loss of volume (ISO 10563)                                                      | ≤ 10%                         |                                    |
| Resistance to flow (ISO 7390)                                                   | ≤ 3 mm                        |                                    |
| Adhesion and cohesion properties after exposure to artificial light (ISO 11431) | No Failure                    |                                    |
| Elastic recovery (ISO 7389)                                                     | ≥ 60%                         |                                    |
| Secant tensile modulus at -30°C (ISO 8339)                                      | Pass                          |                                    |
| Tensile properties at maintained extension at -30°C (ISO 8340)                  | ≤ 0.9 MPa                     |                                    |
| Durability                                                                      | Pass                          |                                    |



**Gorilla Kitchen and Bathroom Silicone Sealant – Clear  
- Declared Performance**

**EN 15651-3: S  
CLASS – XS1**

Pre-Conditioning: Method A (according to ISO 8340)  
Substrate: Glass without primer  
Aluminium (anodized, with primer)

| Essential characteristics                                                       | Performance                   | Harmonised technical specification |
|---------------------------------------------------------------------------------|-------------------------------|------------------------------------|
| Reaction to fire (EN 13501)                                                     | E                             | EN 15651-3: 2012                   |
| Release of chemicals dangerous to the environment and health                    | See product safety data sheet |                                    |
| Water tightness and air tightness                                               |                               |                                    |
| Resistance to flow (ISO 7390)                                                   | ≤ 3 mm                        |                                    |
| Loss of volume (ISO 10563)                                                      | ≤ 20%                         |                                    |
| Tensile properties at maintained extension after immersion in water (ISO 10590) | No Failure                    |                                    |
| Evaluation of the action of microorganisms (ISO 846)                            | 1                             |                                    |
| Durability                                                                      | Pass                          |                                    |

Charles Berry  
Assistant Regulatory Manager  
21<sup>st</sup> May 2026