

AUX R32 - The Free Match Inverter Series - AFEB24HP230V1CC

Job Name _____ Location _____ Date _____
 Purchaser _____ Engineer _____
 For ☐ Reference ☐ Approval ☐
 Submitted to _____ Construction _____
 Unit Designation _____ Schedule # _____



- ❖ Square panel
- ❖ Fresh air intake
- ❖ Detachable air guide vane
- ❖ New anti-leakage water pan
- ❖ Health filter
- ❖ Built-in pump
- ❖ Compact body
- ❖ Digital display
- ❖ 360° air supply
- ❖ Wifi control (Optional)

Indoor Unit			AFEB24HP230V1CC
Capacity	Cooling	Btu/h	24000
	Heating	Btu/h	24000
Electric Data	Power Supply	V~Hz/Ph	208~230,60,1
	Input Current	A	0.6
Indoor Unit	Air Flow Rate (Hi/Mi/Lo)	CFM	823/764/676
	Sound Pressure Level	dB(A)	47
	Net Dimensions	inch	33.07×33.07×9.69
		mm	840×840×246
	Package Dimensions	inch	35.83×35.83×12.20
		mm	910×910×310
	Net Dimension (Panel)	inch	37.40×37.40×2.17
		mm	950×950×55
	Packing Dimension (Panel)	inch	39.37×39.37×3.94
		mm	1000×1000×100
Piping Diameter	Net/Gross(body)	lbs	52.9/61.7
	Net/Gross(Panel)	lbs	11.7/17.2
	Liquid Side	In.[mm]	1/4[6.35]
	Gas Side	In.[mm]	5/8[15.88]

Remarks:

- 1.All specifications are subject to change by the manufacturer without prior notice.
- 2.All units are being tested and comply to ISO5151.
- 3.Sound pressure levels are measured in anechoic chamber.
During actual operation, sound pressure level will be higher as a result of room specification condition.
- 4.Data from AUX lab,08/03/24, Data may change according to test surroundings, AUX reserves right of explanation on data.



AUX-S-110024



Specifications are subject to change without notice.

© 2024 Aux Cloud Commerce (USA) Inc. All rights reserved

Dimensions

Indoor Unit

AFE24HP230V1CC

