



● JACK'S POINT
OTAGO

● GREY FRIARS
TRAY PROFILE



New Zealand Steel does not recommend the use of touch-up paint on any of its COLORSTEEL® products.

Air drying touch-up paints have different weathering characteristics to the baked-on finish of COLORSTEEL® coating systems. Over time, these two paints will weather differently and look different.

Minor surface scratches are best left alone. They become less noticeable as the coating weathers and do not affect the corrosion inhibiting properties of the material. However, widespread damage caused by rough handling should be corrected by replacement of the affected material instead of doing spot touch-ups.

Colour matched fasteners and accessories can be purchased. These will eliminate loss of time and damage caused by touch-up painting. Self tapping precoloured screws allow rapid installation and reduce the incidence of minor surface damage.

The use of prepainted soft edging, notched flashings and ridging eliminates the need to touch-up these areas. Because lead ribbon flashings may degrade ZINCALUME® based COLORSTEEL® coatings, soft zinc or aluminium ribbon should be used for flashings.

On occasions where the customer wishes to paint some ancillary part of the building or an adjacent building to match a COLORSTEEL® coating, standard house paint appropriately tinted, can be purchased from retail outlets. Because house paints have different weathering characteristics to COLORSTEEL® systems they must not be applied to COLORSTEEL® material.



colorsteel.co.nz



NOTE: Buyers and users of New Zealand Steel Limited products and services must make their own assessment of the products for their own conditions. All queries regarding product specification, purpose or application should be directed to New Zealand Steel Limited, phone 0800 697 833. New Zealand Steel Limited reserves the right to modify products, techniques, equipment and statements to reflect improvements in the manufacture and application of its products. The information contained in this brochure is accurate as at June 2026 and supplied without prejudice to New Zealand Steel Limited's standard terms and conditions of sale. In the event of conflict between this information and the standard terms and conditions, the standard terms and conditions prevail. This brochure supersedes all previous brochure editions. COLORSTEEL®, MAXAM®, ALTIMATE®, DRIDEX®, Activate®, FlaxPod®, TidalDrift®, TuiTuft®, SandBar®, SandScape® and StonePeak® are registered trademarks of New Zealand Steel Limited. ZINCALUME® is a registered trademark of BlueScope Steel Limited. Copyright© New Zealand Steel Limited, June 2026.