

Plaser Trimless round symmetric



EN
Discretion and integration
define PLASTER Trimless.

These luminaires are
characterized by their
complete integration into
the ceiling and their unique
finishes.

ES
Discreción e integración
definen a PLASTER Trimless.

Estas luminarias se
caracterizan por su completa
integración en el techo y sus
acabados únicos.

FR
Discretion et intégration
définissent PLASTER
Trimless.

Ces luminaires se
caractérisent par leur
intégration complète dans
le plafond et leurs finitions
uniques.

IT
Discrezione e integrazione
definiscono PLASTER
Trimless.

Questi apparecchi sono
caratterizzati dalla loro
completa integrazione nel
soffitto e dalle loro finiture
uniche.


Culture x light

Ref.
00451-

Plaster Trimless round symetric

Technical information / Información técnica

Category / Categoría:	Architectural
Colour / Color:	White / Black / Copper / Gold / Graphite
Materials / Materiales:	Aluminium
Index Protection / Índice de protección:	IP20
Technology / Tecnología:	LED
Colour Temperature / Temperatura de color:	2700K / 3000K / 4000K
Luminaire Total Power / Potencia total:	7W / 12,5W / 19W
Real Luminous Flux / Flujo luminoso real:	*see luminous flux table
Efficacy / Eficacia:	*see luminous flux table
CRI:	>90
Lifetime/ Vida útil:	65.000h L80B10
Angle / Ángulo:	15° / 38° / 60°
MacAdam Steps:	2-SDCM
Driver:	Included
Class / Clase:	II
Dimming / Regulación:	On-Off / Edge Cut / Dali push / Bluetooth / Matter / Dali no-push
Flicker / Parpadeo:	Flicker free
Voltage / Voltaje:	230V
Frequency / Frecuencia:	50/60Hz
Bluetooth:	>20m
Installation system / Sistema de instalación:	Ceiling
Cut Out / Agujero de empotramiento:	Ø110mm
Warranty / Garantía (years/años):	5 years



00451-
Plaster trimless

Quality certificates
/ Certificados de calidad

The image may not accurately reflect the reference. Nexia reserves the right to modify any components of the product.
Specifications regarding flux, power, and color temperature are subject to change by the manufacturer.
/ La imagen puede no reflejar con precisión la referencia. Nexia se reserva el derecho de modificar cualquier componente del producto. Las especificaciones sobre flujo, potencia y temperatura de color están sujetas a cambios por parte del fabricante.



Ref.
00451-

Plaster Trimless round symetric

Model

00451-

	Colour	CRI/Temp.	Angle	Led	Dimming	Emergency
● 0	White	H 927	1 15°	0 904lm / 7W	- On-Off	- No Emergency
● 1	Black	E 930	3 38°	2 1400 lm / 12,5W	R Edge Cut	EM Kit 1h
● A	Copper	F 940	6 60°	3 1800 lm / 19W	D Dali	
● D	Gold				B Bluetooth	
● G	Graphite				M Matter	
					N Dali no-push	

Customization options available under request:
Special colors (minimum units)

Luminous flux table / Tabla de flujos luminosos

2700K						
15°		38°		60°		
LED	real flux lm	lm/W	real flux lm	lm/W	real flux lm	lm/W
0	613	82	496	66	537	72
2	1007	72	816	58	883	63
3	1338	67	1084	54	1174	59

3000K						
15°		38°		60°		
LED	real flux lm	lm/W	real flux lm	lm/W	real flux lm	lm/W
0	628	84	509	68	551	73
2	1014	72	822	59	890	64
3	1348	67	1092	55	1182	59

4000K						
15°		38°		60°		
LED	real flux lm	lm/W	real flux lm	lm/W	real flux lm	lm/W
0	651	87	528	70	571	76
2	1070	76	867	62	938	67
3	1420	71	1150	58	1245	62