

UNITECH EVO 368 · MANUAL



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

UNITECH EVO 368 · MANUAL

(3ph) 400V ± 10% · 50/60Hz		
MIG	MMA	TIG
12,1 KVA	10,3 KVA	9,4 KVA
45 V	70 V	12 V
30 ÷ 350A	20 ÷ 300 A	10 ÷ 350 A
350A @ 50% 320A @ 60% 250A @ 100%	300A @ 50% 280A @ 60% 250A @ 100%	350A @ 50% 320A @ 60% 250A @ 100%
H		
IP 23S		
Power source 250x610x440 mm		
Wire feeder 240x560x460 mm		
Lifter 250x600x230 mm		
Trolley 460x1000x800 mm		
69,8 / 64,4 kg		

STANDARD CONFIGURATION

Part number	Description	
99855019K	UNITECH EVO 368 + H4 MANUAL · Air · (Only MIG MANUAL mode)	
99850010	Power source	INCLUDED
99420080	Wire feeder H4 · Air	
99900286	Wheels KIT X4 / H4 / XP4	
99490031	Lifter KIT Trolley UNI · only Air	
44890396	Interconnection cable · 50 mm² · 5 mt · Air	
33805101	Drive roll · Ø 30 mm · 0,8 - 1,0 mm	
99900282	Trolley · 4 wheels UNI	