SPINTA 10W-40 STOU

Product Code: SP-AG-1040-STOU

Universal Multifunctional Lubricant for Agricultural Tractors

PRODUCT DESCRIPTION

SPINTA 10W-40 STOU is a Super Tractor Oil Universal formulated for combined use in agricultural petrol and diesel engines, transmissions, hydraulic systems, oil-immersed brakes and gears where the manufacturer requires a STOU lubricant. Its SAE 10W-40 viscosity provides strong high-temperature protection while supporting engine cleanliness, wear and deposit control and smooth operation of mechanical systems.

APPLICATIONS & BENEFITS

Universal Agricultural Use One multifunctional lubricant can cover engine, transmission, hydraulic and wet-brake applications where the listed specifications are required.

High-Temperature Protection SAE 10W-40 viscosity supports a strong lubricating film during demanding agricultural operation.

Hydraulic & Transmission Performance Stable viscosity supports hydraulic pumps, transmissions, gears and bearings across a wide range of operating conditions.

KEY PERFORMANCE BENEFITS

Wet-Brake Compatibility Friction characteristics support smooth operation of oil-immersed brakes and help limit vibration and noise.

Anti-Corrosion Protection Protects components exposed to humidity and agricultural operating environments.

Fleet Simplification Broad multifunctional performance can reduce the number of lubricants required for compatible agricultural machinery.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels; suitable-for-use claims as indicated:

- Engine: API CG-4/SF; ACEA E3
- Engine: MB 228.1; CCMC D4; MAN 271
- Gear & Transmission: ZF TE-ML 06 A/B/C; ZF TE-ML 07B
- Gear & Transmission: API GL-4; Allison C4; CAT TO-2
- STOU: Massey Ferguson M1139 / M1144 / M1145
- STOU: John Deere J27
- STOU: Ford M2C159 B/C
- STOU: FNH 82009201 / 82009202 / 82009203
- STOU: New Holland 030 C / 024 C

Recommendation: Always refer to the agricultural machinery manufacturer's operating and maintenance manual to confirm the required viscosity grade, performance level and application before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	10W-40 STOU
SAE Grade	-	10W-40
Density @ 15°C, kg/dm³	ASTM D 4052	0.865
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	95.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	14.0
Viscosity Index	ASTM D 2270	140
TBN	ASTM D 2896	10.0
Sulfated Ash, % wt	ASTM D 874	≤ 1.4
Flash Point, °C	ASTM D 92	240
Pour Point, °C	ASTM D 97	-30

Note: The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.

Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it