SPINTA 2T Fully Synthetic

Product Code: SP-MC-2T-FULL

Full Synthetic 2-Stroke Motorcycle Lubricant

PRODUCT DESCRIPTION

SPINTA 2T Fully Synthetic is a low-smoke, full synthetic lubricant developed for high-performance 2-stroke motorcycle and scooter engines. Its formulation supports clean combustion, exhaust-port cleanliness and protection against seizure and piston-ring sticking, including under severe urban and demanding operating conditions. It is suitable for both oil-injection and premix systems.

APPLICATIONS & BENEFITS

Reliable Performance Helps control combustion deposits while maintaining effective lubrication of moving engine components and responsive performance.

Advanced Protection Formulated to help protect cylinders and piston rings against scuffing, seizure and sticking under severe conditions.

Low Smoke Dedicated additive technology helps reduce exhaust smoke and combustion residues.

KEY PERFORMANCE BENEFITS

Mixing Properties Suitable for modern oil-injection systems and premix applications where the listed performance levels are required.

Engine & Exhaust Cleanliness Helps maintain clean exhaust ports and reduce carbon-deposit formation.

Severe-Duty Performance Full synthetic formulation supports protection and lubrication during intensive urban or demanding operation.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels:

- API TC
- JASO FC
- ISO-L-EGD
- Piaggio SI
- TISI

Recommendation: Suitable for 2-stroke motorcycle and scooter engines using oil-injection or premix systems. Not intended for outboard marine engines; always follow the engine manufacturer's lubricant and mixing-ratio requirements.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	2T FULLY SYNTHETIC
Density @ 15°C, kg/dm³	ASTM D 4052	0.880
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	35.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	6.5
Viscosity Index	ASTM D 2270	130
Flash Point, °C	ASTM D 92	225
Pour Point, °C	ASTM D 97	-30

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.

Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it