SPINTA 2T Standard

Product Code: SP-MC-2T-STAND

2-Stroke Engine Lubricant

PRODUCT DESCRIPTION

SPINTA 2T Standard is a high-quality lubricant for 2-stroke motorcycle and scooter engines, formulated to provide reliable engine protection, good cleanliness and combustion-residue control under normal operating conditions. Its additive system helps reduce smoke and deposit formation and is suitable for both oil-injection and premix systems.

APPLICATIONS & BENEFITS

Reliable Performance Helps limit combustion deposits and supports consistent engine performance in regular service.

Advanced Protection Formulated to reduce deposit formation and provide dependable protection for 2-stroke engine components.

Low Smoke Balanced additive technology helps reduce exhaust smoke and combustion residues.

KEY PERFORMANCE BENEFITS

Mixing Properties Suitable for both oil-injection systems and premix applications.

Engine Cleanliness Helps control deposits and maintain engine cleanliness during daily use.

Daily-Use Protection Designed for regular motorcycle and scooter operation requiring API TC, JASO FB or ISO-L-EGB performance.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels:

- API TC
- JASO FB
- ISO-L-EGB

Recommendation: Suitable for 2-stroke motorcycle and scooter engines using oil-injection or premix systems. Not intended for outboard marine engines; always follow the engine manufacturer's lubricant and mixing-ratio requirements.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	2T STANDARD
Color	Visual	Red
Density @ 15°C, kg/dm³	ASTM D 4052	0.865
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	90.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	11.5
Viscosity Index	ASTM D 2270	115
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-24

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.

Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it

Spinta Italia S.r.l.
Viale C. Battisti 15, 27100 Pavia (PV) – Italy
info@spinta-lub.it - www.spinta-lub.it