SPINTA 4T 5W-40

Product Code: SP-MC-4T-0540

100% Synthetic 4-Stroke Motorcycle Engine Lubricant

PRODUCT DESCRIPTION

SPINTA 4T 5W-40 is a 100% synthetic high-performance lubricant developed for latest-generation 4-stroke motorcycle and scooter engines requiring SAE 5W-40, API SM and JASO MB. Its formulation supports viscosity stability, engine cleanliness and reliable protection, contributing to smooth operation and reduced vibration and engine noise.

APPLICATIONS & BENEFITS

Reliable Performance Fully synthetic technology provides dependable engine protection and stable lubrication under varied operating conditions.

Advanced Protection Detergent and anti-wear additives help control sludge and deposits and protect critical engine components.

Viscosity Stability Helps maintain stable lubricant performance throughout the service interval.

KEY PERFORMANCE BENEFITS

JASO MB Applications Designed for scooters, maxi-scooters and other 4-stroke applications where JASO MB performance is required.

Driving Comfort Stable lubrication helps reduce vibration and engine noise for smoother operation.

Engine Cleanliness Helps maintain internal cleanliness and supports consistent engine response.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels:

- SAE 5W-40
- API SM
- JASO MB

Recommendation: Always refer to the motorcycle or scooter manufacturer's operating and maintenance manual to confirm the required SAE viscosity grade, API service category and JASO performance level before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	4T 5W-40
SAE Grade	-	5W-40
Density @ 15°C, kg/dm³	ASTM D 4052	0.860
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	90.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	14.0
Viscosity Index	ASTM D 2270	155
Flash Point, °C	ASTM D 92	240
Pour Point, °C	ASTM D 97	-39

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.

Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it

Spinta Italia S.r.l.
Viale C. Battisti 15, 27100 Pavia (PV) – Italy
info@spinta-lub.it - www.spinta-lub.it