SPINTA 4T 10W-50

Product Code: SP-MC-4T-1050

100% Synthetic 4-Stroke Motorcycle Engine Lubricant

PRODUCT DESCRIPTION

SPINTA 4T 10W-50 is a 100% synthetic high-performance motorcycle lubricant formulated for latest-generation 4-stroke engines requiring SAE 10W-50, API SM and JASO MA2. Its higher operating-temperature viscosity supports a strong lubricating film, engine protection and reliable performance under sport, touring and demanding riding conditions.

APPLICATIONS & BENEFITS

Reliable Performance Fully synthetic technology provides robust lubrication and engine protection under demanding operating conditions.

High-Temperature Protection SAE 10W-50 viscosity supports lubricant film strength at elevated operating temperatures.

Advanced Protection Detergent and anti-wear additives help control sludge, deposits and wear on critical components.

KEY PERFORMANCE BENEFITS

Wet-Clutch Compatibility JASO MA2 performance supports motorcycles using a common lubricant for engine, gearbox and wet clutch.

Gear-Shift Performance Stable lubrication supports smooth and reliable gear engagement.

Viscosity Stability Helps maintain consistent lubricant performance during severe and high-temperature service.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels:

- SAE 10W-50
- API SM
- JASO MA2

Recommendation: Always refer to the motorcycle manufacturer's operating and maintenance manual to confirm the required SAE viscosity grade, API service category and JASO performance level before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	4T 10W-50
SAE Grade	-	10W-50
Density @ 15°C, kg/dm³	ASTM D 4052	0.880
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	135.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	19.0
Viscosity Index	ASTM D 2270	160
Flash Point, °C	ASTM D 92	245
Pour Point, °C	ASTM D 97	-30

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.

Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it

Spinta Italia S.r.l.
Viale C. Battisti 15, 27100 Pavia (PV) – Italy
info@spinta-lub.it - www.spinta-lub.it