SPINTA 0W-30 C2

Product Code: SP-PC-0030-C2

100% Synthetic Engine Lubricant

PRODUCT DESCRIPTION

SPINTA 0W-30 C2 is a high-performance 100% synthetic engine lubricant developed for latest-generation petrol and diesel engines requiring SAE 0W-30 and ACEA C2 performance. It is particularly suited to Ford, Jaguar and Land Rover applications requiring the listed specifications, while supporting fuel economy, cold-start protection and compatibility with modern exhaust after-treatment systems.

APPLICATIONS & BENEFITS

Fuel Economy & Emission Control SAE 0W-30 low-viscosity performance helps reduce friction and supports improved fuel efficiency and lower CO2 emissions.

Synthetic Base Technology High-quality synthetic base oils provide low volatility and help control lubricant consumption.

KEY PERFORMANCE BENEFITS

Engine Protection Provides reliable protection under varied driving conditions while helping reduce deposit formation.

MID-SAPS Technology A dedicated Mid-SAPS additive system supports compatibility with modern exhaust gas after-treatment systems.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels; suitable-for-use claims as indicated:

- SAE 0W-30
- ACEA C2
- Ford WSS-M2C950-A
- Jaguar Land Rover JLR.03.5007
- Suitable for use: Fiat 9.55535-GS1
- Suitable for use: Fiat 9.55535-DS1

Recommendation: Always refer to the vehicle manufacturer's operating and maintenance manual to confirm the required SAE viscosity grade, performance level and service interval before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	0W-30 C2
SAE Grade	-	0W-30
Density @ 15°C, kg/dm³	ASTM D 4052	0.855
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	55.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	11.0
Viscosity Index	ASTM D 2270	170
Flash Point, °C	ASTM D 92	235
Pour Point, °C	ASTM D 97	-42

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.
Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it

Spinta Italia S.r.l.
Viale C. Battisti 15, 27100 Pavia (PV) – Italy
info@spinta-lub.it - www.spinta-lub.it