SPINTA 5W-30 C2

Product Code: SP-PC-0530-C2

100% Synthetic Engine Lubricant - FAP/DPF Technology

PRODUCT DESCRIPTION

SPINTA 5W-30 C2 is a 100% synthetic engine lubricant developed for modern petrol and diesel engines requiring SAE 5W-30 and ACEA C2 performance. Suitable for vehicles equipped with FAP/DPF exhaust after-treatment systems, it combines emission-system protection, fuel economy support and stable lubrication performance.

APPLICATIONS & BENEFITS

Emission-System Protection Low-SAPS technology helps protect FAP/DPF and TWC after-treatment systems and supports their service life.

Shear Stability Helps reduce viscosity variation throughout the lubricant service life.

Oxidation Stability Improved resistance to thermal-oxidative degradation helps maintain engine protection over time.

KEY PERFORMANCE BENEFITS

Synthetic Base Technology High-quality synthetic base oils provide low volatility and help control lubricant consumption.

Cold-Start Performance Rapid low-temperature circulation supports reliable lubrication during engine start-up.

Engine Refinement Stable lubrication contributes to smooth engine operation and reduced mechanical noise.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels; suitable-for-use claims as indicated:

- SAE 5W-30
- ACEA C2
- PSA B71 2290
- Suitable for use: Fiat 9.55535-S1
- Suitable for use: Iveco 18-1811 SP-SC1

Recommendation: Always refer to the vehicle manufacturer's operating and maintenance manual to confirm the required SAE viscosity grade, performance level and service interval before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	5W-30 C2
SAE Grade	-	5W-30
Density @ 15°C, kg/dm³	ASTM D 4052	0.855
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	70.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	11.0
Viscosity Index	ASTM D 2270	155
Flash Point, °C	ASTM D 92	235
Pour Point, °C	ASTM D 97	-39

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.
Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it

Spinta Italia S.r.l.
Viale C. Battisti 15, 27100 Pavia (PV) – Italy
info@spinta-lub.it - www.spinta-lub.it