SPINTA 10W-60

Product Code: SP-PC-1060

100% Synthetic High-Performance Engine Lubricant

PRODUCT DESCRIPTION

SPINTA 10W-60 is a 100% synthetic high-performance engine lubricant developed for demanding petrol, diesel and gas-powered engines requiring SAE 10W-60, API SN/CF and ACEA A3/B3 or A3/B4 performance. Its formulation is designed to provide robust lubrication, deposit control and wear protection under severe operating conditions and high thermal stress.

APPLICATIONS & BENEFITS

Active Cleaning Formula Helps control dirt, sludge and deposit formation to maintain internal engine cleanliness.

Synthetic Base Technology Synthetic base oils provide low volatility and support stable lubrication under demanding operating conditions.

Wear Protection A strong lubricant film helps protect moving components against wear under severe stress.

KEY PERFORMANCE BENEFITS

Oxidation Resistance Helps resist thermal-oxidative degradation and maintain lubricant performance at high temperature.

Multi-Fuel Versatility Suitable for petrol, diesel and gas engines where the listed performance levels are required.

High-Performance Protection High viscosity at operating temperature supports protection in high-output and competition-oriented engines.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels; suitable-for-use claims as indicated:

- SAE 10W-60
- API SN/CF
- ACEA A3/B3, A3/B4

Recommendation: Always refer to the vehicle manufacturer's operating and maintenance manual to confirm the required SAE viscosity grade, performance level and service interval before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	10W-60
SAE Grade	-	10W-60
Density @ 15°C, kg/dm³	ASTM D 4052	0.855
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	150.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	24.0
Viscosity Index	ASTM D 2270	160
Flash Point, °C	ASTM D 92	250
Pour Point, °C	ASTM D 97	-39

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.
Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it

Spinta Italia S.r.l.
Viale C. Battisti 15, 27100 Pavia (PV) – Italy
info@spinta-lub.it - www.spinta-lub.it