SPINTA 20W-50
Product Code: SP-PC-2050

SPINTA 20W-60
Product Code: SP-PC-2060

Mineral Multigrade Engine Lubricants for Older & High-Mileage Engines

PRODUCT DESCRIPTION

SPINTA 20W-50 and SPINTA 20W-60 are mineral multigrade engine lubricants developed for older-generation, classic and high-mileage engines. Their formulation provides reliable wear protection, helps control sludge and deposits, and supports reduced lubricant consumption. The higher-viscosity 20W-60 grade is intended for applications requiring stronger high-temperature viscosity protection.

APPLICATIONS & BENEFITS

Engine Cleanliness Detergent technology helps control lacquer, sludge and harmful deposit formation in older engines.
Wear Protection Additives form a protective lubricant film between moving mechanical components to help reduce wear.
High-Mileage Performance High viscosity helps reduce leakage and lubricant consumption in engines with wider mechanical clearances.

KEY PERFORMANCE BENEFITS

Multi-Fuel Versatility Suitable for petrol, diesel and gas engines where the listed API performance level is required.
20W-60 Additional Grade The higher-viscosity 20W-60 grade provides an option where 20W-50 viscosity may be insufficient under demanding conditions.
Older-Engine Protection Supports reliable lubrication for classic, vintage and high-mileage engines operating under normal or severe conditions.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels:

- SAE 20W-50
- SAE 20W-60
- API SL/CF

Recommendation: Always refer to the vehicle manufacturer's operating and maintenance manual to confirm the required SAE viscosity grade and performance level before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	20W-50	20W-60
SAE Grade	-	20W-50	20W-60
Color	Visual	Amber	Green
Density @ 15°C, kg/dm³	ASTM D 4052	0.880	0.885
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	150.0	190.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	19.0	24.0
Viscosity Index	ASTM D 2270	130	130
Flash Point, °C	ASTM D 92	245	250
Pour Point, °C	ASTM D 97	-30	-27

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.
Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it

Spinta Italia S.r.l.
Viale C. Battisti 15, 27100 Pavia (PV) – Italy
info@spinta-lub.it - www.spinta-lub.it