SPINTA ATF 2

Product Code: SP-TR-ATF2

Automatic Transmission Fluid

PRODUCT DESCRIPTION

SPINTA ATF 2 is an automatic transmission fluid suitable for passenger cars and heavy-duty vehicles, power steering systems and hydraulic applications where the listed performance levels are required. Its mineral base oils and dedicated additive system provide reliable lubrication, friction control, oxidation resistance and protection of transmission and hydraulic components.

APPLICATIONS & BENEFITS

Oxidation Stability Helps protect the transmission against thermal stress and limits sludge, lacquer and harmful deposit formation.
Component Protection Selected base oils and additives provide protection for bronze, copper and other transmission components.
Viscosity Stability Viscosity-index-improving additives help maintain stable fluid performance over time and temperature variations.

KEY PERFORMANCE BENEFITS

Seal Compatibility Compatible with a wide range of sealing elastomers, helping reduce leakage associated with seal deterioration.
Versatile Use Suitable for compatible automatic transmissions, power steering systems and hydraulic circuits.
Smooth Operation Reliable friction characteristics support consistent and smooth transmission and steering-system operation.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels:

- DEXRON IID
- MB 236.6
- Ford Mercon
- TASA
- ZF TE-ML 02F
- ZF TE-ML 03D
- ZF TE-ML 11A
- ZF TE-ML 14A, 04D
- ZF TE-ML 17C
- VOITH H55.6335

Recommendation: Always refer to the vehicle or equipment manufacturer's operating and maintenance manual to confirm the correct ATF or power-steering fluid specification before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	ATF 2
Color	Visual	Red
Density @ 15°C, kg/dm³	ASTM D 4052	0.855
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	35.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	6.5
Viscosity Index	ASTM D 2270	150
Flash Point, °C	ASTM D 92	200
Pour Point, °C	ASTM D 97	-39
Brookfield Viscosity @ -40°C, mPa·s	DIN 51389	50,000

Note: *The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.*

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.
Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it

Spinta Italia S.r.l.
Viale C. Battisti 15, 27100 Pavia (PV) – Italy
info@spinta-lub.it - www.spinta-lub.it