SPINTA ATF M9

Product Code: SP-TR-M9

100% Synthetic Automatic Transmission Fluid

PRODUCT DESCRIPTION

SPINTA ATF M9 is a high-performance 100% synthetic automatic transmission fluid developed for modern Mercedes-Benz automatic transmissions. It provides stable lubrication, friction control, wear protection and smooth shifting in compatible 5- and 7-speed transmissions, including NAG-V Sport applications where the listed Mercedes-Benz specifications are required.

APPLICATIONS & BENEFITS

Fuel Economy Low-friction performance helps reduce transmission losses and supports efficient operation.

All-Season Fluidity Excellent low-temperature fluidity and stable hot performance support reliable operation across a wide temperature range.

Wear Protection Balanced friction characteristics help protect compact, highly loaded transmission components.

KEY PERFORMANCE BENEFITS

Foam & Oxidation Control Helps control foaming and supports oxidation stability at elevated operating temperatures.

Seal Compatibility Compatible with transmission sealing elastomers, helping reduce leakage associated with seal deterioration.

Smooth Operation Stable friction performance helps reduce vibration and supports smooth transmission behaviour.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels; OEM/application claims as indicated:

- Mercedes-Benz MB 236.15
- Mercedes-Benz MB 236.14 (001 989 68 03 10)
- Mercedes-Benz MB 236.12 (001 989 45 03 10)
- Mercedes-Benz MB 236.10 (001 989 21 03 10)

Recommendation: This is a special transmission fluid. Always verify the exact Mercedes-Benz transmission specification in the vehicle manufacturer's operating and maintenance documentation before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	ATF M9
Color	Visual	Blue
Density @ 15°C, kg/dm³	ASTM D 4052	0.845
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	30.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	6.5
Viscosity Index	ASTM D 2270	180
Flash Point, °C	ASTM D 92	210
Pour Point, °C	ASTM D 97	-54

Note: The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.

Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it