SPINTA CVT

Product Code: SP-TR-CVT

100% Synthetic Continuously Variable Transmission Fluid

PRODUCT DESCRIPTION

SPINTA CVT is a 100% synthetic fluid developed for continuously variable transmissions. Its formulation provides stable friction characteristics, all-season fluidity, wear protection, oxidation stability and compatibility with a broad range of CVT systems, including selected hybrid applications where the listed OEM requirements apply.

APPLICATIONS & BENEFITS

Fuel Economy Low-friction performance supports efficient power transmission compared with conventional stepped gear systems.

All-Season Fluidity Excellent low-temperature fluidity and stable high-temperature performance support reliable CVT operation.

Wear & Foam Protection Helps control wear, corrosion and foam formation during the transmission work cycle.

KEY PERFORMANCE BENEFITS

Friction Stability Balanced friction characteristics support smooth and stable continuously variable operation.

Long-Life Performance Oxidation stability at high temperature helps support transmission durability.

e-Mobility Compatibility Compatible with the listed hybrid/eCVT applications where the corresponding OEM requirement applies.

SPECIFICATIONS & PERFORMANCE LEVELS

Meets or exceeds the following specifications and performance levels; OEM/application claims as indicated:

- Audi Multitronic; TL 521 16 (G 052 516); TL 521 80 (G 052 180)
- BMW Mini Cooper EZL 799A; 8322 0136376; 8322 0429154
- Chery CVT / WCF-1 / Shell SL 2100
- Citroën PSA Standard 9735EF
- Chrysler NS-2 / CVT+4
- Daihatsu Fluid TC; AMMIX CVTF DFE / CVT Fluid DC / CVT Fluid DFC
- Dodge NS-2 / CVT+4
- Fiat Tutela Car CVT N.G.
- Fujiyuuko i-CVTF FG
- General Motors DEX-CVT; 1940713 / 1940714; CVTF I-Green2; VT40; HP CVT
- Honda HMMF (without starting clutch); HCF2; Z-1 (CVT without starting clutch); CVT; Ultra HEVF-Type 1
- Hyundai SP III (CVT model); CVT-1
- Idemitsu CVTF-EX1
- Jeep NS-2 / CVT+4
- Kia SP III (CVT model); CVT-1
- Lexus Fluid TC / Fluid FE
- Mazda JWS 3320
- Mopar CVT+4
- MG Rover EM-CVT
- Mini Cooper EZL 799 / EZL 799A / ZF CVT V1
- Mitsubishi CVTF-J1 / CVTF-J4 / J4+ / ECO J4 / SP-III (CVT only)
- Nissan NS-1 / NS-2 / NS-2V / NS-3 / N-CVT
- Opel 7-speed CVT; 95529854
- Perodua D-CVT
- Peugeot PSA Standard 9735EF
- Punch CVTF-EX1
- Renault Elf Matic CVT / CVT CK/SK/FK
- Saturn DEX-CVT / CVTF I-Green2
- Shell Green 1V
- Subaru iCVT / iCVT FG / ECVT / Lineartronic CVT & CVT II / CVT 3 / High Torque CVT / CV-30 / High Torque CVTF-LV
- Suzuki CVTF TC / CVTF 3320 / CVTF 4401 / NS-2 / CVT Green 1 & 2 / CVT Green 1V
- Toyota CVTF TC / CVTF FE
- Volvo CVT 4959
- VW TL 521 16 (G 052 516); TL 521 80 (G 052 180)
- Zotye CVTs
- e-Mobility: Ford Escape Hybrid eCVT; Honda e:HEV/iMMD; Jatco CVT 8 Hybrid; Mazda SKYACTIVE-HYBRID; Nissan Altima Hybrid; Toyota THSII/Prius/THS 5th Gen./Noah/Voxy

Recommendation: CVT fluids are application-specific. Always verify the exact OEM fluid number and CVT requirement in the vehicle manufacturer's operating and maintenance documentation before use.

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Property	Test Method	CVT
Color	Visual	Amber
Density @ 15°C, kg/dm³	ASTM D 4052	0.850
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	35.0
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	7.0
Viscosity Index	ASTM D 2270	170
Flash Point, °C	ASTM D 92	210
Pour Point, °C	ASTM D 97	-45

Note: The values shown above are typical for normal production and may vary within normal manufacturing tolerances. They do not constitute a product specification or contractual limit.

STORAGE, HEALTH & ENVIRONMENT

STORAGE

Store under cover whenever possible. If outdoor storage cannot be avoided, containers should be protected from rain and water infiltration. Avoid temperatures above 60°C, direct sunlight and freezing conditions.

HEALTH & SAFETY

When properly used and handled in accordance with standard personal hygiene practices, the product is not expected to present adverse health effects under normal conditions of use. Refer to the corresponding SPINTA Safety Data Sheet (SDS) for detailed precautions and first-aid information.

ENVIRONMENT

Do not discharge new or used product into drains, sewage systems, soil or watercourses. Used product must be collected and delivered to an authorized collection or disposal facility in accordance with applicable regulations.

ADDITIONAL INFORMATION

Safety Data Sheet (SDS): The corresponding SPINTA Safety Data Sheet is available separately and should be consulted before handling or using the product.

Technical Service: SPINTA ITALIA S.r.l. | Viale C. Battisti 15, 27100 Pavia (PV) - Italy | info@spinta-lub.it | www.spinta-lub.it