

# Safety Data Sheet



## 1. Identification

**Product Name:** BLACK REPAIR PRIMER

**Product Information:** UAP9693C

**Revision Date:** 08/06/2015

**Supplier:** Red Spot Paint & Varnish Co., Inc.  
1107 E. Louisiana St.  
Evansville, IN 47711

**Supersedes Date:** New SDS

**Preparer:** EHS@redspot.com

**24 Hour Emergency:** 1-812-428-9100

**Outside U.S. and Canada:**

**CHEMTREC:** 1-800-424-9300

**CHEMTREC:** 703-527-3887


**Note:** CHEMTREC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

## 2. Hazards Identification

### GHS Classification

Flam. Liq. 2, Acute Tox. 4 Inhalation

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

4% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

Highly flammable liquid and vapour.

Harmful if inhaled.

### GHS LABEL PRECAUTIONARY STATEMENTS

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Call a POISON CENTER or doctor/physician if you feel unwell.

### GHS SDS PRECAUTIONARY STATEMENTS

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/.../ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

## 3. Composition/Information on Ingredients

| <u>Chemical Name</u>   | <u>CAS-No.</u> | <u>Wt. %</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|------------------------|----------------|--------------|--------------------|-----------------------|
| METHYL N-PROPYL KETONE | 107-87-9       | 25-50        | GHS06              | H302-331              |
| CARBON                 | 1333-86-4      | 2.5-10       | No Information     | No Information        |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



**FIRST AID - INHALATION:** If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

**FIRST AID - SKIN CONTACT:** In case of contact, wash skin immediately with soap and water. If rash, irritation or burns develop, consult a physician. Launder clothing before reuse.

**FIRST AID - EYE CONTACT:** If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

**FIRST AID - INGESTION:** Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Have the victim drink 8 to 10 ounces (240 - 300 ml) of water to dilute the material in the stomach. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Consult a physician immediately. Do not induce vomiting without medical advice.

## 5. Fire-fighting Measures

**Flash Point, °C:** 7 (45°F)

**Explosive Limits, %:** 1.1 - 8.0

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may burst if exposed to extreme heat or fire. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Toxic gases may form when product burns. Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. During processing, dust may form explosive mixture in air.

**SPECIAL FIREFIGHTING PROCEDURES:** The use of self-contained breathing apparatus is recommended for fire fighters. Water spray may be useful in minimizing vapors and cooling exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Prevent product from entering drains. Remove all sources of ignition (flames, hot surfaces and electrical, static, or frictional spark). Avoid breathing vapors. Ventilate area. Remove with inert absorbent and non-sparking tools. Dispose of material in accordance with all federal, state and local regulations. Only trained personnel wearing protective equipment should handle spill cleanup. Avoid personal contact.

## 7. Handling and Storage



**HANDLING:** Handle in accordance with good industrial hygiene and safety practice. Keep away from food and drink. Keep out of reach of children. Open container carefully as content may be under pressure. Flammable liquid. Avoid heat, sparks and open flames. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Use in well ventilated area. To reduce potential for static discharge, bond and ground containers when transferring material. Take precautionary measures against static discharges. All metal parts of the mixing and processing equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

**STORAGE:** Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store near acids.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u>   | <u>ACGIH</u><br><u>TLV-TWA</u> | <u>ACGIH</u><br><u>TLV STEL</u> | <u>OSHA</u><br><u>PEL-TWA</u> | <u>OSHA</u><br><u>PEL-CEILING</u> | <u>Unit</u> |
|------------------------|--------------------------------|---------------------------------|-------------------------------|-----------------------------------|-------------|
| METHYL N-PROPYL KETONE | 200                            | 250                             | 200                           | N.E.                              | ppm         |

CARBON

3.5

-

3.5

N.E.

mg/m3

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

## Personal Protection



**RESPIRATORY PROTECTION:** When concentrations exceed the exposure limits specified, use of a NIOSH approved full facepiece organic vapor and dust/mist cartridge respirator is recommended. Where the protection factor may be exceeded, use of a full facepiece supplied air respirator or Self Contained Breathing Apparatus (SCBA) may be necessary. Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



**SKIN PROTECTION:** Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.



**EYE PROTECTION:** Wear chemical goggles and faceshield (if not wearing a full facepiece respirator). Safety glasses with side-shields.



**OTHER PROTECTIVE EQUIPMENT:** Flame retardant antistatic protective clothing. Safety shower and eyewash station should be located in immediate work area.



**HYGIENIC PRACTICES:** It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible. Wash hands and face before breaks and immediately after handling the product. Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited.

## 9. Physical and Chemical Properties

|                             |                      |                              |              |
|-----------------------------|----------------------|------------------------------|--------------|
| <b>Freeze Point, °C:</b>    | No Information       | <b>Boiling Range, °C:</b>    | 101 (214 °F) |
| <b>Explosive Limits, %:</b> | 1.1 - 8.0            | <b>Solubility in Water:</b>  | 18.7         |
| <b>Flash Point, °C:</b>     | 7 (45°F)             | <b>Vapor Pressure, mmHg:</b> | 14.97        |
| <b>VOC Content, lb/gal:</b> | 4.884 (581.196 gr/L) | <b>Evaporation Rate:</b>     | 1.77         |
| <b>Volume Solids, %:</b>    | 27.4745              | <b>Density, g/cm3:</b>       | 0.979        |
|                             |                      | <b>Physical State:</b>       | Liquid       |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with skin and eyes. Do not breathe vapours or spray mist. Do not store above 120 °F (48.9 °C). Avoid dust formation in confined areas. Do not create a powder cloud by using a brush or compressed air.

**INCOMPATIBILITY:** Keep away from strong oxidizing agents, heat and open flames. Incompatible with strong acids and oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May generate toxic or irritating combustion products. May generate carbon monoxide gas. Fumes may contain CO and/or CO<sub>2</sub>

**HAZARDOUS POLYMERIZATION:** Will not occur

## 11. Toxicological Information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** This product contains carbon black which has been determined to be a known animal carcinogen and a possible human carcinogen.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** This product is a severe eye irritant. Direct contact with the liquid or exposure to its vapors or mists may cause burning, tearing, redness and swelling. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** May be harmful if swallowed. This product may cause irritation and possible corrosive action in the mouth, stomach tissue, and digestive tract. Aspiration hazard: this material can enter the lungs during swallowing or vomiting and cause lung inflammation and damage.

**EFFECT OF OVEREXPOSURE - INHALATION:** Prolonged, repeated or high exposures may cause central nervous system depression leading to headaches, nausea, drowsiness, dizziness, and possibly narcosis. In extreme cases, may cause loss of consciousness. Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Direct skin contact may cause irritation.

**CARCINOGENICITY:** No Information

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Contact

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> | <u>Chemical Name</u>   | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|------------------------|------------------|--------------------|-------------------|
| 107-87-9       | METHYL N-PROPYL KETONE | 1600 mg/kg Rat   | 6480 mg/kg Rat     | N.I.              |

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Do not contaminate ponds, waterways or ditches with chemical or used container.

## 13. Disposal Information



### Product

**DISPOSAL INFORMATION:** Dispose of material in accordance with applicable federal, state and local regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Prevent product from entering drains. Remove all sources of ignition (flames, hot surfaces and electrical, static, or frictional spark). Avoid breathing vapors. Ventilate area. Remove with inert absorbent and non-sparking tools. Dispose of material in accordance with all federal, state and local regulations. Only trained personnel wearing protective equipment should handle spill cleanup. Avoid personal contact.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

|                           |        |                   |     |
|---------------------------|--------|-------------------|-----|
| DOT Proper Shipping Name: | Paint  | Packing Group:    | II  |
| DOT Technical Name:       | N/A    | Resp. Guide Page: | 128 |
| DOT Hazard Class:         | 3      |                   |     |
| DOT UN/NA Number:         | UN1263 |                   |     |

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No SARA 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(B) components exist in this product.

### U.S. State Regulations:

#### NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

| <u>Chemical Name</u>     | <u>CAS-No.</u> |
|--------------------------|----------------|
| STYRENE ACRYLIC POLYMERS | PROPRIETARY    |
| HYDROUS KAOLIN CLAY      | 1332-58-7      |

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u>     | <u>CAS-No.</u> |
|--------------------------|----------------|
| STYRENE ACRYLIC POLYMERS | PROPRIETARY    |
| HYDROUS KAOLIN CLAY      | 1332-58-7      |

#### CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| CARBON               | 1333-86-4      |

#### CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

### International Regulations: As follows -

#### CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**WHMIS Class**

## 16. Other Information

### HMIS Ratings:

|         |   |               |   |             |   |                      |   |
|---------|---|---------------|---|-------------|---|----------------------|---|
| Health: | 2 | Flammability: | 3 | Reactivity: | 0 | Personal Protection: | G |
|---------|---|---------------|---|-------------|---|----------------------|---|

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302 Harmful if swallowed.  
H331 Toxic if inhaled.

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS06



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

### Disclaimer:

The information, as set forth for reference only, was obtained from outside sources that Red Spot Paint & Varnish Co., Inc., and its affiliates and subsidiaries, believe to be accurate and reliable as of the date of this document. Please be advised that there are no warranties, representations or conditions, expressed or implied, of any kind, including, but not limited to, the accuracy, reliability, completeness of the information, or the merchantability or fitness for a particular purpose, and Red Spot Paint & Varnish Co., Inc. or its officers, employees, affiliates or subsidiaries, shall not be held liable for any errors or omissions, or for any direct, indirect or consequential loss or damage caused by or howsoever arising from reliance on all or any part of the contents of this document. Revisions of this document may be made based on the latest information made available to Red Spot Paint & Varnish Co., Inc. The information presented herein relates only to the specific material(s) designated and may not be valid for such material(s) used in combination with any other material(s), in any process or for any other purpose, unless specified in the text. Accordingly, the purchaser and each user assume all risks and liability connected to their specific use of such material(s). Nothing contained herein is to be construed as permission, recommendation or inducement by Red Spot Paint & Varnish Co., Inc. or its officers, employees, affiliates or subsidiaries, to use any material(s), product or process so as to infringe or conflict with any patent. Further, it is the user's obligation to utilize this (these) material(s) in full compliance with all required health, safety and environmental regulations. The references to legislative, regulatory and codes of practice documents cannot be considered as exhaustive. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

END OF DATA SHEET

