

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet



According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)
Issue date: 3/23/2022 Revision date: 7/3/2025 Supersedes: 6/17/2025 Version: 12.0 ECR25-031

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : QUICK-STICKCA CA Compliant Adhesive Canister

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives
Restrictions on use : For industrial/occupational use only

1.4. Supplier's details

Ductmate Industries
210 5th Street, Charleroi PA, 15022
800-245-3188 | ductmate.com

1.5. Emergency phone number

Emergency number : CHEMWATCH EMERGENCY RESPONSE (24/7) +1 855- 237-5573 +61 3 9573 3188

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Chemical under pressure, Category 1	H282	Extremely flammable chemical under pressure: May explode if heated.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H282 - Extremely flammable chemical under pressure: May explode if heated
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P261 - Avoid breathing vapors.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

P280 - Wear eye protection, protective gloves.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical attention.
P370+P378 - In case of fire: Use ABC-powder, carbon dioxide (CO₂), alcohol resistant foam to extinguish.
P376 - Stop leak if safe to do so.
P381 - In case of leakage, eliminate all ignition sources.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P501 - Dispose of contents and/or container to an approved waste disposal plant.

2.3. Hazards associated with known or reasonably anticipated uses

None known

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Methyl acetate	CAS-No.: 79-20-9	30 – 60
Isopentane	CAS-No.: 78-78-4	5-10
Trade Secret (Unique Identifier: QG0001)*	CAS-No.: Trade Secret	1-5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Move the affected person to fresh air. Get medical attention if symptoms occur.
First-aid measures after skin contact : Gently wash with plenty of soap and water. Get medical advice if skin irritation persists.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes. High concentration of vapors may induce: headache, nausea, dizziness.
Skin	: May cause slight irritation to the skin.
Eyes	: redness, itching, tears. Causes serious eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: None known.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: If necessary seek medical advice. Treat symptomatically.
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray or alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. vapors may cause fire/explosion if source of ignition is present. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Pressurized container: may burst if heated.
Explosion hazard	: vapors may form explosive mixture with air.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂). Organic compounds.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Use self-contained breathing apparatus and chemically protective clothing. Use shielding to protect from bursting cans.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate all ignition sources. No open flames, no sparks, and no smoking. Ventilate spillage area.
------------------	---

For non-emergency personnel

Emergency procedures	: Avoid breathing vapors. Avoid contact with skin and eyes. Keep unnecessary and unprotected personnel away from the spillage.
----------------------	--

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

Environmental precautions	: Avoid release to the environment.
---------------------------	-------------------------------------

6.2. Methods and materials for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: If safe, move leaking containers outdoors or to a well-ventilated area. Absorb and/or contain spill with inert material, then place in suitable container.
Other information	: Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid breathing vapors, spray. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from heat and direct sunlight. Do not puncture or incinerate containers.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep cool. Protect from sunlight.
Incompatible materials	: Strong oxidizers.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Methyl acetate (79-20-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Methyl acetate
ACGIH® TLV® TWA	200 ppm
ACGIH® TLV® STEL	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Methyl acetate
OSHA PEL (TWA)	610 mg/m³
	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Isopentane (78-78-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Isopentane
ACGIH® TLV® TWA	1000 ppm
Remark (ACGIH)	TLV® Basis: Narcosis; resp tract irr
Regulatory reference	ACGIH 2025
Trade Secret (Unique Identifier: QG0001)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	9000 mg/m³
	5000 ppm

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Trade Secret (Unique Identifier: QG0001)	
ACGIH® TLV® STEL	54000 mg/m ³
	30000 ppm
Remark (ACGIH)	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA)	9000 mg/m ³
	5000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.
Eye protection:
Chemical goggles
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Low viscosity liquid.
Color	: White to off-white
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Fruity
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 28 C / 82 F
Flash point	: -51 C / -60 F
Flammability (solid, gas)	: Flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Solubility	: In water, material is partially soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: 1.4% (LEL) – 16% (UEL)
Explosive properties	: None.
Oxidizing properties	: None.
Particle characteristics	: Particle characteristics : Not applicable
VOC g/L	43.13 g/L

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Protect from sunlight.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat (Vapors)	> 49.2 mg/l/4h
Isopentane (78-78-4)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EU Method B.1 (Acute Toxicity (Oral))
LC50 Inhalation - Rat	> 25.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

Methyl acetate (79-20-9)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Isopentane (78-78-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Isopentane (78-78-4)

NOAEC (inhalation, rat, vapor, 90 days)	30 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: other: U.S. EPA/FIFRA Guidelines §82-4, Guideline: EPA OTS 798.2450 (90-Day Inhalation Toxicity), Guideline: other: U.S. EPA/TSCA Guidelines 40 CFR §798.6059, and §798.6059, 798.6200, 798.6400, Guideline: other: EU Guideline 87/302/EEC
---	---

Aspiration hazard	: Not classified
-------------------	------------------

Quin US 0623/1405/1420 CA Compliant Pressure Sensitive Adhesive Canister

Viscosity, kinematic	> 20.5 mm ² /s
----------------------	---------------------------

Symptoms/effects	: May cause drowsiness or dizziness.
Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes. High concentration of vapors may induce: headache, nausea, dizziness.
Skin	: May cause slight irritation to the skin.
Eyes	: redness, itching, tears. Causes serious eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: None known.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Methyl acetate (79-20-9)

LC50 - Fish [1]	250 – 350 mg/l Brachydanio rerio (zebra-fish)
EC50 - Crustacea [1]	1026.7 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	> 120 mg/l Desmodesmus subspicatus

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

12.2. Persistence and degradability

Quin US 0623/1405/1420 CA Compliant Pressure Sensitive Adhesive Canister

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

Methyl acetate (79-20-9)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Isopentane (78-78-4)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Trade Secret (Unique Identifier: QG0001)

Persistence and degradability	Biodegradation is not applicable to inorganic compounds.
-------------------------------	--

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Dispose of in accordance with applicable federal, state, and local regulations.
Waste treatment methods	: Dispose in a safe manner in accordance with local/national regulations. Do not puncture or incinerate, even when empty.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN3501	UN3501	3501	3501
14.2. Proper Shipping Name			
Chemical under pressure, flammable, n.o.s. (Methyl acetate ; pentane	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Methyl acetate ; pentane	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Methyl acetate ; pentane)	Chemical under pressure, flammable, n.o.s. (Methyl acetate ; pentane)
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

DOT	TDG	IMDG	IATA
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT	
UN-No. (DOT)	: UN3501
DOT Special Provisions (49 CFR 172.102)	: 362 - This entry applies to liquids, pastes or powders, pressurized with a propellant that meets the definition of a gas in §173.115. A chemical under pressure packaged in an aerosol dispenser must be transported under UN1950. The chemical under pressure must be classed based on the hazard characteristics of the components in the propellant; the liquid; or the solid. The following provisions also apply: a. If one of the components, which can be a pure substance or a mixture, is classed as flammable, the chemical under pressure must be classed as flammable in Division 2.1. Flammable components are flammable liquids and liquid mixtures, flammable solids and solid mixtures or flammable gases and gas mixtures meeting the following criteria: (1) A flammable liquid is a liquid having a flashpoint of not more than 93 °C (200 °F); (2) A flammable solid is a solid that meets the criteria in §173.124 of this subchapter; or (3) A flammable gas is a gas that meets the criteria in §173.115 of this subchapter. b. Gases of Division 2.3 and gases with a subsidiary risk of 5.1 must not be used as a propellant in a chemical under pressure. c. Where the liquid or solid components are classed as Division 6.1, Packing Group II or III, or Class 8, Packing Group II or III, the chemical under pressure must be assigned a subsidiary risk of Division 6.1 or Class 8 and the appropriate identification number must be assigned. Components classed as Division 6.1, Packing Group I, or Class 8, Packing Group I, must not be offered for transportation and transported under this description. d. A chemical under pressure with components meeting the properties of: Class 1 (explosives); Class 3 (liquid desensitized explosives); Division 4.1 (self-reactive substances and solid desensitized explosives); Division 4.2 (substances liable to spontaneous combustion); Division 4.3 (substances which, in contact with water, emit flammable gases or toxic gases); Division 5.1 (oxidizing substances); Division 5.2 (organic peroxides); Division 6.2 (Infectious substances); or, Class 7 (Radioactive material), must not be offered for transportation under this description. e. A description to which special provision 170 or TP7 is assigned in Column 7 of the §172.101 Hazardous Materials Table, and therefore requires air to be eliminated from the package vapor space by nitrogen or other means, must not be offered for transportation under this description. f. Chemicals under pressure containing components forbidden for transport on both passenger and cargo aircraft in Columns (9A) and (9B) of the §172.101 Hazardous Materials Table must not be transported by air. T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter. TP40 - The portable tank must not be transported when connected with spray application equipment.
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 335
DOT Packaging Bulk (49 CFR 173.xxx)	: 313, 315
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 75 kg
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

UN-No. (TDG)

: UN3501

TDG Special Provisions

: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks. 2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act", 130 - (1) This shipping name applies to chemicals under pressure, including liquids, pastes or powders that are pressurized with a propellant that meets the criteria set out in section 2.2.1.2 of the UN Recommendation for a compressed gas or a liquefied gas. (2) These dangerous goods must be assigned to (a) primary Class 2.1, Flammable Gases, if one of the components, which can be a pure substance or a mixture, is classified as a flammable component under subsection (3); and (b) subsidiary Class 6.1, Toxic Substances, or Class 8, Corrosives, if one of the liquid or solid components is included in Class 6.1, Toxic Substances, Packing Group II or III, or Class 8, Corrosives, Packing Group II or III. (3) A flammable component is (a) a liquid that has a flashpoint of 60°C or less; (b) a solid that meets the criterion set out in subparagraph 2.21(a)(i) of Part 2 (Classification); and (c) a gas that meets the criteria set out in paragraph 2.14(a) of Part 2 (Classification). (4) This shipping name must not be used to transport (a) gases included in both primary Class 2.3, Toxic Gases, and subsidiary Class 5.1, Oxidizing Substances; (b) substances included in Packing Group I of Class 6.1, Toxic Substances, or Class 8, Corrosives; (c) liquid desensitized explosives included in Class 3, Flammable Liquids; (d) self-reactive substances and solid desensitized explosives included in Class 4.1, Flammable Solids; or (e) dangerous good included in (i) Class 4.2, Substances Liable to Spontaneous Combustion; (ii) Class 4.3, Water-reactive Substances; (iii) Class 5.1, Oxidizing Substances; (iv) Class 5.2, Organic Peroxides; (v) Class 6.2, Infectious Substances; or (vi) Class 7, Radioactive Materials. (5) Dangerous goods to which special packing provision PP86 or TP7 is assigned in Column 9 and Column 11 of the Dangerous Goods List in Chapter 3.2 of the UN Recommendations, and that therefore require air to be eliminated from the vapour space, must not be transported under this shipping name, but must be transported under their respective shipping names as listed in the Dangerous Goods List of Chapter 3.2 of the UN Recommendations. A chemical under pressure contained in an aerosol container must be transported under UN1950, AEROSOLS. SOR/2014-306 UN3500 to UN3505 SOR/2014-306

Explosive Limit and Limited Quantity Index

: 0

Excepted quantities (TDG)

: E0

Passenger Carrying Vessel Index

: Forbidden

Passenger Carrying Road Vehicle or Passenger

: Forbidden

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number

: 115

IMDG

Special provision (IMDG)

: 274, 362

Limited quantities (IMDG)

: 0

Excepted quantities (IMDG)

: E0

Packing instructions (IMDG)

: P206

Packing provisions (IMDG)

: PP89

Tank instructions (IMDG)

: T50

Tank special provisions (IMDG)

: TP4, TP40

EmS-No. (Fire)

: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage)

: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG)

: D

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Stowage and handling (IMDG) : SW2
Properties and observations (IMDG) : Liquids, pastes or powders, pressurized with a propellant which meets the definition of a gas.

IATA

Special provision (IATA) : A1, A187
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Forbidden
PCA limited quantity max net quantity (IATA) : Forbidden
PCA packing instructions (IATA) : Forbidden
PCA max net quantity (IATA) : Forbidden
CAO packing instructions (IATA) : 218
CAO max net quantity (IATA) : 75kg
ERG code (IATA) : 10L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

Isopentane (78-78-4)

Listed on the Canadian DSL (Domestic Substances List)

Trade Secret (Unique Identifier: QG0001)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Methyl acetate (79-20-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Isopentane (78-78-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Ductmate QUICK-STICK CA Adhesive Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Component	State or local regulations
Methyl acetate(79-20-9)	U.S. - New Jersey - Right to Know Hazardous Substance List
Isopentane(78-78-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List
Trade Secret (Unique Identifier: QG0001)()	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Revision date : 7/3/2025

Issue date : 3/23/2022

Full text of hazard classes and H-statements	
H282	Extremely flammable chemical under pressure: May explode if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.