

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet



According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)  
Issue date: 2/22/2022 Revision date: 7/3/2025 Supersedes: 6/17/2025 Version: 4.0 ECR25-031

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : QUICK-STICK Can Adhesive Aerosol

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives  
Restrictions on use : For industrial/occupational use only

#### 1.4. Supplier's details

Ductmate Industries  
210 5<sup>th</sup> Street, Charleroi PA, 15022  
800-245-3188 | ductmate.com

#### 1.5. Emergency phone number

Emergency number : CHEMWATCH EMERGENCY RESPONSE (24/7) +1 855- 237-5573 +61 3 9573 3188

### SECTION 2 Hazard Identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

|                                                                        |           |                                                                          |
|------------------------------------------------------------------------|-----------|--------------------------------------------------------------------------|
| Serious eye damage/eye irritation, Category 2A                         | H319      | Causes serious eye irritation.                                           |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336      | May cause drowsiness or dizziness.                                       |
| Hazardous to the aquatic environment — Chronic Hazard, Category 3      | H412      | Harmful to aquatic life with long lasting effects.                       |
| Aerosol, Category 1                                                    | H222;H229 | Extremely flammable aerosol. Pressurized container; may burst if heated. |

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H222 - Extremely flammable aerosol  
H229 - Pressurized container; may burst if heated  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing vapors.  
P264 - Wash hands thoroughly after handling.

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

- P271 - Use only outdoors or in a well-ventilated area.
- P273 - Avoid release to the environment.
- P280 - Wear eye protection, protective gloves.
- P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
- P312 - Call a POISON CENTER, a doctor if you feel unwell.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 - If eye irritation persists: Get medical attention.
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
- P405 - Store locked up.
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
- P501 - Dispose of contents and/or container to an approved waste disposal plant.

### 2.3. Hazards associated with known or reasonably anticipated uses

None known

### 2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name           | Product identifier | %       |
|----------------|--------------------|---------|
| Methyl acetate | CAS-No.: 79-20-9   | 30 – 60 |
| Propane        | CAS-No.: 74-98-6   | 10-25   |
| Butane         | CAS-No.: 106-97-8  | 5 – 10  |
| isopentane     | CAS-No.: 78-78-4   | 5-10    |

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First aid measures

### 4.1. Description of necessary first-aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Move the affected person to fresh air. Get medical attention if symptoms occur.
- First-aid measures after skin contact : Gently wash with plenty of soap and water. Get medical advice if skin irritation persists.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms/effects, acute and delayed

- Symptoms/effects : May cause drowsiness or dizziness.
- Inhalation : May cause minor irritation to the respiratory tract and to other mucous membranes. High concentration of vapors may induce: headache, nausea, dizziness.
- Skin : May cause slight irritation to the skin.

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

|                  |                                                                         |
|------------------|-------------------------------------------------------------------------|
| Eyes             | : redness, itching, tears. Causes serious eye irritation.               |
| Ingestion        | : May cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Chronic symptoms | : None known.                                                           |

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

|                                   |                                                            |
|-----------------------------------|------------------------------------------------------------|
| Other medical advice or treatment | : If necessary seek medical advice. Treat symptomatically. |
|-----------------------------------|------------------------------------------------------------|

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

|                                |                                                                              |
|--------------------------------|------------------------------------------------------------------------------|
| Suitable extinguishing media   | : Use dry chemical, CO <sub>2</sub> , water spray or alcohol-resistant foam. |
| Unsuitable extinguishing media | : Do not use a solid water stream as it may scatter and spread fire.         |

### 5.2. Specific hazards arising from the chemical

|                                                  |                                                                                                                                                                                                                                                                         |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard                                      | : Extremely flammable aerosol. vapors may cause fire/explosion if source of ignition is present. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Pressurized container: may burst if heated. |
| Explosion hazard                                 | : vapors may form explosive mixture with air.                                                                                                                                                                                                                           |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. Carbon oxides (CO, CO <sub>2</sub> ). Organic compounds.                                                                                                                                                                                 |

### 5.3. Special protective equipment and precautions for fire-fighters

|                                |                                                                                                                                                                                                |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Firefighting instructions      | : On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray.                                                      |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Use self-contained breathing apparatus and chemically protective clothing. Use shielding to protect from bursting cans. |

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |                                                                                                       |
|------------------|-------------------------------------------------------------------------------------------------------|
| General measures | : Eliminate all ignition sources. No open flames, no sparks, and no smoking. Ventilate spillage area. |
|------------------|-------------------------------------------------------------------------------------------------------|

#### For non-emergency personnel

|                      |                                                                                                                                |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Emergency procedures | : Avoid breathing vapors. Avoid contact with skin and eyes. Keep unnecessary and unprotected personnel away from the spillage. |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------|

#### For emergency responders

|                      |                                                                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                           |                                     |
|---------------------------|-------------------------------------|
| Environmental precautions | : Avoid release to the environment. |
|---------------------------|-------------------------------------|

### 6.2. Methods and materials for containment and cleaning up

|                         |                                                                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| For containment         | : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.                                                                                |
| Methods for cleaning up | : Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Absorb and/or contain spill with inert material, then place in suitable container. |
| Other information       | : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).                                                                             |

For further information refer to section 8: "Exposure controls/personal protection"

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling
- : Use only outdoors or in a well-ventilated area. Avoid breathing vapors, spray. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from heat and direct sunlight. Protect from sunlight. Do not expose to temperatures exceeding 122 deg F. Do not puncture or incinerate containers.
- Hygiene measures
- : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including incompatibilities

- Storage conditions
- : Store locked up. Store in a well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep cool. Protect from sunlight. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Incompatible materials
- : Strong oxidizers.

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

| Methyl acetate (79-20-9)                   |                                                                                                 |
|--------------------------------------------|-------------------------------------------------------------------------------------------------|
| USA - ACGIH - Occupational Exposure Limits |                                                                                                 |
| Local name                                 | Methyl acetate                                                                                  |
| ACGIH® TLV® TWA                            | 200 ppm                                                                                         |
| ACGIH® TLV® STEL                           | 250 ppm                                                                                         |
| Remark (ACGIH)                             | TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina) |
| Regulatory reference                       | ACGIH 2024                                                                                      |
| USA - OSHA - Occupational Exposure Limits  |                                                                                                 |
| Local name                                 | Methyl acetate                                                                                  |
| OSHA PEL (TWA)                             | 610 mg/m³                                                                                       |
|                                            | 200 ppm                                                                                         |
| Regulatory reference (US-OSHA)             | OSHA Annotated Table Z-1                                                                        |
| isopentane, 2-methylbutane (78-78-4)       |                                                                                                 |
| USA - ACGIH - Occupational Exposure Limits |                                                                                                 |
| Local name                                 | Isopentane                                                                                      |
| ACGIH® TLV® TWA                            | 1000 ppm                                                                                        |
| Remark (ACGIH)                             | TLV® Basis: Narcosis; resp tract irr                                                            |
| Regulatory reference                       | ACGIH 2025                                                                                      |
| Propane (74-98-6)                          |                                                                                                 |
| USA - ACGIH - Occupational Exposure Limits |                                                                                                 |
| Local name                                 | Propane                                                                                         |
| Remark (ACGIH)                             | TLV® Basis: Asphyxia                                                                            |

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

|                                                   |                                    |
|---------------------------------------------------|------------------------------------|
| <b>Propane (74-98-6)</b>                          |                                    |
| Regulatory reference                              | ACGIH 2025                         |
| <b>USA - OSHA - Occupational Exposure Limits</b>  |                                    |
| Local name                                        | Propane                            |
| OSHA PEL (TWA)                                    | 1800 mg/m³                         |
|                                                   | 1000 ppm                           |
| Regulatory reference (US-OSHA)                    | OSHA Annotated Table Z-1           |
| <b>Butane (106-97-8)</b>                          |                                    |
| <b>USA - ACGIH - Occupational Exposure Limits</b> |                                    |
| Local name                                        | Butane                             |
| ACGIH® TLV® STEL                                  | 2370 mg/m³ (EX - Explosion hazard) |
|                                                   | 1000 ppm (EX - Explosion hazard)   |
| Remark (ACGIH)                                    | TLV® Basis: CNS impair             |
| Regulatory reference                              | ACGIH 2025                         |

### 8.2. Appropriate engineering controls

|                                  |                                                                                                                              |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Appropriate engineering controls | : Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits. |
| Environmental exposure controls  | : Avoid release to the environment.                                                                                          |

### 8.3. Individual protection measures, such as personal protective equipment

|                                                                                                                                                                                                                                                                                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Hand protection:</b>                                                                                                                                                                                                                                                                 |
| In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.                                                                                                                                                                                    |
| <b>Eye protection:</b>                                                                                                                                                                                                                                                                  |
| Chemical goggles                                                                                                                                                                                                                                                                        |
| <b>Skin and body protection:</b>                                                                                                                                                                                                                                                        |
| Wear suitable protective clothing                                                                                                                                                                                                                                                       |
| <b>Respiratory protection:</b>                                                                                                                                                                                                                                                          |
| In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice. |

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

|                |                                                                                                       |
|----------------|-------------------------------------------------------------------------------------------------------|
| Physical state | : Liquid                                                                                              |
| Appearance     | : Low viscosity liquid.                                                                               |
| Color          | : White to off-white                                                                                  |
| Odor           | : There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. |
|                | Mixture contains one or more component(s) which have the following odor:<br>Fruity                    |
| Odor threshold | : No data available                                                                                   |
| pH             | : No data available                                                                                   |

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

|                                                 |                                             |
|-------------------------------------------------|---------------------------------------------|
| Melting point                                   | : Not applicable                            |
| Freezing point                                  | : No data available                         |
| Boiling point                                   | : 0 C / 32 F                                |
| Flash point                                     | : -104 C / 156 F                            |
| Flammability (solid, gas)                       | : Flammable                                 |
| Vapor pressure                                  | : No data available                         |
| Relative vapor density at 20°C                  | : No data available                         |
| Relative density                                | : No data available                         |
| Solubility                                      | : In water, material is partially soluble.  |
| Partition coefficient n-octanol/water (Log Pow) | : No data available                         |
| Auto-ignition temperature                       | : No data available                         |
| Decomposition temperature                       | : No data available                         |
| Viscosity, kinematic                            | : No data available                         |
| Explosion limits                                | : 1.4% (LEL) – 16% (UEL)                    |
| Explosive properties                            | : None.                                     |
| Oxidizing properties                            | : None.                                     |
| Particle characteristics                        | : Particle characteristics : Not applicable |
| VOC % by weight                                 | 32.5%                                       |

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

### 10.5. Incompatible materials

Oxidizing agent.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

#### Methyl acetate (79-20-9)

|               |            |
|---------------|------------|
| LD50 oral rat | 6482 mg/kg |
|---------------|------------|

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

|                                                                                  |                                                                                                                                                                                                                                                                                                                                                               |
|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Methyl acetate (79-20-9)</b>                                                  |                                                                                                                                                                                                                                                                                                                                                               |
| LD50 dermal rat                                                                  | > 2000 mg/kg                                                                                                                                                                                                                                                                                                                                                  |
| LC50 Inhalation - Rat (Vapors)                                                   | > 49.2 mg/l/4h                                                                                                                                                                                                                                                                                                                                                |
| <b>isopentane, 2-methylbutane (78-78-4)</b>                                      |                                                                                                                                                                                                                                                                                                                                                               |
| LD50 oral rat                                                                    | > 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EU Method B.1 (Acute Toxicity (Oral))                                                                                                                                                                                                                   |
| LC50 Inhalation - Rat                                                            | > 25.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)                                                                                                                                                                                                                                                                        |
| <b>Propane (74-98-6)</b>                                                         |                                                                                                                                                                                                                                                                                                                                                               |
| LC50 Inhalation - Rat [ppm]                                                      | > 20000 ppm/4h                                                                                                                                                                                                                                                                                                                                                |
| <b>Butane (106-97-8)</b>                                                         |                                                                                                                                                                                                                                                                                                                                                               |
| LC50 Inhalation - Rat [ppm]                                                      | > 20000 ppm/4h                                                                                                                                                                                                                                                                                                                                                |
| Skin corrosion/irritation                                                        | : Not classified                                                                                                                                                                                                                                                                                                                                              |
| Serious eye damage/irritation                                                    | : Causes serious eye irritation.                                                                                                                                                                                                                                                                                                                              |
| Respiratory or skin sensitization                                                | : Not classified                                                                                                                                                                                                                                                                                                                                              |
| Germ cell mutagenicity                                                           | : Not classified                                                                                                                                                                                                                                                                                                                                              |
| Carcinogenicity                                                                  | : Not classified                                                                                                                                                                                                                                                                                                                                              |
| Reproductive toxicity                                                            | : Not classified                                                                                                                                                                                                                                                                                                                                              |
| STOT-single exposure                                                             | : May cause drowsiness or dizziness.                                                                                                                                                                                                                                                                                                                          |
| <b>Methyl acetate (79-20-9)</b>                                                  |                                                                                                                                                                                                                                                                                                                                                               |
| STOT-single exposure                                                             | May cause drowsiness or dizziness.                                                                                                                                                                                                                                                                                                                            |
| <b>isopentane, 2-methylbutane (78-78-4)</b>                                      |                                                                                                                                                                                                                                                                                                                                                               |
| STOT-single exposure                                                             | May cause drowsiness or dizziness.                                                                                                                                                                                                                                                                                                                            |
| STOT-repeated exposure                                                           | : Not classified                                                                                                                                                                                                                                                                                                                                              |
| <b>isopentane, 2-methylbutane (78-78-4)</b>                                      |                                                                                                                                                                                                                                                                                                                                                               |
| NOAEC (inhalation, rat, vapor, 90 days)                                          | 30 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: other: U.S. EPA/FIFRA Guidelines §82-4, Guideline: EPA OTS 798.2450 (90-Day Inhalation Toxicity), Guideline: other: U.S. EPA/TSCA Guidelines 40 CFR §798.6059, and §798.6059, 798.6200, 798.6400, Guideline: other: EU Guideline 87/302/EEC |
| Aspiration hazard                                                                | : Not classified                                                                                                                                                                                                                                                                                                                                              |
| <b>Quin A001-378 / A091-378 CA Compliant Pressure Sensitive Adhesive Aerosol</b> |                                                                                                                                                                                                                                                                                                                                                               |
| Viscosity, kinematic                                                             | > 20.5 mm²/s                                                                                                                                                                                                                                                                                                                                                  |
| Symptoms/effects                                                                 | : May cause drowsiness or dizziness.                                                                                                                                                                                                                                                                                                                          |
| Inhalation                                                                       | : May cause minor irritation to the respiratory tract and to other mucous membranes. High concentration of vapors may induce: headache, nausea, dizziness.                                                                                                                                                                                                    |
| Skin                                                                             | : May cause slight irritation to the skin.                                                                                                                                                                                                                                                                                                                    |
| Eyes                                                                             | : redness, itching, tears. Causes serious eye irritation.                                                                                                                                                                                                                                                                                                     |
| Ingestion                                                                        | : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.                                                                                                                                                                                                                                                                                       |
| Chronic symptoms                                                                 | : None known.                                                                                                                                                                                                                                                                                                                                                 |

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

### SECTION 12 Ecological information

#### 12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

| Methyl acetate (79-20-9) |                                               |
|--------------------------|-----------------------------------------------|
| LC50 - Fish [1]          | 250 – 350 mg/l Brachydanio rerio (zebra-fish) |
| EC50 - Crustacea [1]     | 1026.7 mg/l Daphnia magna (Water flea)        |
| EC50 72h - Algae [1]     | > 120 mg/l Desmodesmus subspicatus            |

#### 12.2. Persistence and degradability

| Quin A001-378 / A091-378 CA Compliant Pressure Sensitive Adhesive Aerosol |                                      |
|---------------------------------------------------------------------------|--------------------------------------|
| Persistence and degradability                                             | No additional information available. |
| Methyl acetate (79-20-9)                                                  |                                      |
| Persistence and degradability                                             | Rapidly degradable                   |
| isopentane, 2-methylbutane (78-78-4)                                      |                                      |
| Persistence and degradability                                             | Readily biodegradable.               |
| Propane (74-98-6)                                                         |                                      |
| Persistence and degradability                                             | Not applicable.                      |
| Butane (106-97-8)                                                         |                                      |
| Persistence and degradability                                             | Not applicable.                      |

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Ozone : Not classified  
Fluorinated greenhouse gases : No

### SECTION 13 Disposal considerations

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.  
Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations. Do not puncture or incinerate, even when empty.

### SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA



# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

| DOT                                                                               | TDG                                                                               | IMDG                                                                               | IATA                                                                                |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 14.1. UN number                                                                   |                                                                                   |                                                                                    |                                                                                     |
| UN1950                                                                            | UN1950                                                                            | 1950                                                                               | 1950                                                                                |
| 14.2. Proper Shipping Name                                                        |                                                                                   |                                                                                    |                                                                                     |
| Aerosols                                                                          | AEROSOLS                                                                          | AEROSOLS                                                                           | Aerosols, flammable                                                                 |
| 14.3. Transport hazard class(es)                                                  |                                                                                   |                                                                                    |                                                                                     |
| 2.1                                                                               | 2.1                                                                               | 2.1                                                                                | 2.1                                                                                 |
|  |  |  |  |
| 14.4. Packing group                                                               |                                                                                   |                                                                                    |                                                                                     |
| Not applicable                                                                    | Not applicable                                                                    | Not applicable                                                                     | Not applicable                                                                      |
| 14.5. Environmental hazards                                                       |                                                                                   |                                                                                    |                                                                                     |
| Dangerous for the environment: No                                                 | Dangerous for the environment: No                                                 | Dangerous for the environment: No<br>Marine pollutant: No                          | Dangerous for the environment: No                                                   |
| No supplementary information available                                            |                                                                                   |                                                                                    |                                                                                     |

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

|                                                                  |                                                                                                                                                                                   |
|------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOT</b>                                                       |                                                                                                                                                                                   |
| UN-No. (DOT)                                                     | : UN1950                                                                                                                                                                          |
| DOT Special Provisions (49 CFR 172.102)                          | : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.                                                                                        |
| DOT Packaging Exceptions (49 CFR 173.xxx)                        | : 306                                                                                                                                                                             |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 75 kg                                                                                                                                                                           |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)     | : 150 kg                                                                                                                                                                          |
| DOT Vessel Stowage Location                                      | : A - The material may be stowed “on deck” or “under deck” on a cargo vessel and on a passenger vessel.                                                                           |
| DOT Vessel Stowage Other                                         | : 25 - Protected from sources of heat,87 - Stow “separated from” Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials |
| <b>TDG</b>                                                       |                                                                                                                                                                                   |
| UN-No. (TDG)                                                     | : UN1950                                                                                                                                                                          |

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

**TDG Special Provisions** : 80 - Despite section 1.17 of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with section 5.11 of Part 5, Means of Containment, except that the requirement in subsection 5.11(6) for aerosol containers to be tightly packed in a wood, fibreboard or plastic box does not apply to a user or purchaser who transports no more than six aerosol containers. Note that subsection 5.11(6) includes two requirements, one for a valve protection cap and one for containment, and that the exemption for aerosol containers in special provision 80 applies only to the containment requirement in that subsection; the requirement for a valve protection cap continues to apply. For a similar rule respecting aerosol containers, see subparagraph 1.15(1)(a)(i) of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2, (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a ship on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray. SOR/2014-306 UN1950, UN2037 SOR/2014-306

Explosive Limit and Limited Quantity Index : 1 L  
Excepted quantities (TDG) : E0  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L  
Emergency Response Guide (ERG) Number : 126

### IMDG

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Limited quantities (IMDG) : SP277  
Excepted quantities (IMDG) : E0  
Packing instructions (IMDG) : P207, LP200  
Packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

### IATA

Special provision (IATA) : A145, A167, A802  
PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
ERG code (IATA) : 10L

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

### 15.2. International regulations

#### CANADA

##### Methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

##### isopentane, 2-methylbutane (78-78-4)

Listed on the Canadian DSL (Domestic Substances List)

##### Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

##### Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

##### Methyl acetate (79-20-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### isopentane, 2-methylbutane (78-78-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

| Component                           | State or local regulations                                                                                                             |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Methyl acetate(79-20-9)             | U.S. - New Jersey - Right to Know Hazardous Substance List                                                                             |
| isopentane, 2-methylbutane(78-78-4) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List |
| Propane(74-98-6)                    | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List |
| Butane(106-97-8)                    | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List |

## SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Revision date : 7/3/2025

Issue date : 2/22/2022

# Ductmate QUICK-STICK CAN Adhesive Aerosol

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

| Full text of hazard classes and H-statements |                                                   |
|----------------------------------------------|---------------------------------------------------|
| H222                                         | Extremely flammable aerosol                       |
| H229                                         | Pressurized container; may burst if heated        |
| H319                                         | Causes serious eye irritation                     |
| H336                                         | May cause drowsiness or dizziness                 |
| H412                                         | Harmful to aquatic life with long lasting effects |

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.