

EVERsealTM Spray



UNION MADE IN THE USA



Sprayable Water-Based Duct Sealant

Cost-effective spray solutions for sealing metal ductwork

- Perfect for shop/fabrication use
- Time and labor savings over traditional application methods
- Sprays easily with common airless sprayer
- Indoor/Outdoor Grade
- For applications up to 15" WG
- Excellent UV, Flexibility, and Mold Resistant Properties
- UL 181 B-M Listed and UL 723 Classified
- LEED® Compliant, meets all applicable SCAQMD standards
- Manufactured by SMART Local 12



EVERseal™ Spray

Sprayable Water-Based Duct Sealant

DESCRIPTION

EVERseal spray is cost effective spray solution for sealing all metal ductwork - plus other key attributes listed.

SPECIAL CHARACTERISTICS

- Perfect for shop/fabrication use
- Time and labor savings over traditional application methods
- Sprays easily with common airless sprayer
- Indoor/Outdoor Grade
- For Applications up to 15" WG
- Excellent UV, Flexibility, and Mold Resistant Properties
- UL 181 B-M Listed and UL 723 Classified
- LEED® Compliant, meets all applicable SCAQMD standards
- Manufactured by SMART Local 12

DIRECTIONS FOR USE

Description: EVERseal Spray from Ductmate is a water-based, UL Listed 181B-M spray grade duct sealant, designed for sealing joints and seams of sheet metal air ducts, and UL listed flexible duct.

Directions For Use: Do not thin. For best results store at room temperature at least 24 hours before applying. Surfaces should be clean, dry and free of any dirt, oil, grease, water or other foreign matter. Do not apply when rain or freezing temperatures will occur within 36 hours.

Spray Equipment Instructions: Follow spray equipment manufacturer's instructions when using spray equipment. For best results, use commercial-grade airless paint-sprayer utilizing 121 Spray Tip with 2" fan pattern and minimum 0.021" orifice.

Clean Up: Use warm, soapy water to clean up sealant while it is still wet.

When Used In Conjunction With Sheet Metal: Apply by brush, hand, trowel or spray. EVERseal Spray should be applied to duct connections according to all applicable SMACNA standards. Apply to the inside of female fittings and outside of male fittings. Assemble the joint.

Brush sealant over the assembled joint. Thoroughly cover joint and screws with a 2" to 3" wide band. Assembly should cure for 24-72 hours before pressure testing the system. Since field temperature/humidity conditions may vary, longer set times may be required for specific installations. Apply at a rate of 50 sq. ft. per gallon (1/32" thick).

When Used in Conjunction With UL 181 Listed Flexible Air Ducts: Apply by brush a 1/16" (25 sq.ft. per gallon) coating and allow to dry a minimum of 24-72 hours. Since field temperature/humidity conditions may vary, longer set times may be required for specific installations. Use with mechanical fasteners per Air Duct installation instructions.

When Used In Conjunction With Duct Cover: Allow the sealant to cure fully before encapsulating duct ends with PROguard, or any duct cover products. You may set the duct upright on a palate and encapsulate just the top, allowing air to flow through the bottom until the sealant has cured.

LIMITED PRODUCT WARRANTY

Ductmate warrants that EVERseal® Spray, when properly installed and maintained, will be free from defects in material and workmanship, and will comply with all written specifications made by Ductmate at the time of sale. Ductmate's warranty shall run for a period of one year from the date of manufacture.

Warranty Limitation

The warranty stated above is in lieu of all other warranties, express or implied, including but not limited to the implied warranties of MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Although Ductmate may have suggested the product, or provided written or oral advice to the Purchaser, it is the Purchaser's responsibility to test and determine the suitability of EVERseal® Spray for the intended use and purpose, and Purchaser and/or its customer assumes all risk and liability whatsoever regarding such suitability.

Limitation of Liability

In the event of a breach of the above warranty, Ductmate's sole obligation, and Purchaser's sole and exclusive remedy, shall be, at Ductmate's option, repair or replacement of any defective products, or refund of an applicable portion of the purchase price. Ductmate shall have no liability for costs of removal or reinstallation of the product. The Purchaser agrees that no other remedy, including but not limited to loss of profits, loss sales, injury to person or property, or any other special, incidental or consequential damages, shall be available to the Purchaser for any claim arising out of this Agreement, regardless of whether such claim is made in contract or in tort, including strict liability in tort. In no event will Ductmate be obligated to pay damages to the Purchaser in any amount exceeding the purchase price that the Purchaser paid to Ductmate for the allegedly defective product.

TECHNICAL INFORMATION

CHEMICAL TYPE:	Synthetic Latex
COLOR:	Gray
ODOR:	Mild (wet) None (dry)
VOC CONTENT: EPA Method 24	Pass - Very Low
TVOC EMISSIONS: CDPH Standard Method v1.2	Private Office - Pass School Classroom - Pass
DENSITY:	11.5 +/- 0.5 lbs per gallon
SOLID CONTENTS:	66% +/- 3%
VISCOSITY:	75,000 +/- 22,000 cP
SHORE A HARDNESS:	>50
APPLICATION TEMPERATURE:	35°F to 110°F
SERVICE TEMPERATURE:	-25°F to 220°F
STORAGE TEMPERATURE:	35°F to 110°F
DRY TO TOUCH:	1 hour (approximate)
CURE TIME:	24 to 72 hours <i>Depending on humidity, application, and temperature</i>
FLEXIBILITY: ASTM D522 (1/8" Mandrel Bend)	Pass
MOLD RESISTANCE: UL 181B Mold & Humidity Test	Pass
FREEZE THAW STABILITY:	Pass
ADHESION STRENGTH: UL 181B Peel Adhesion	Pass - Exceeds Standards
COVERAGE:	25 sq. ft./gal. at 1/16" 50 sq. ft./gal. at 1/32"
SHELF LIFE:	1 year (unopened container)
PACKAGING:	5 gallon pail 54 gallon drum
SPRAYER SETTINGS:	Spray Tip - 121 • 2" Spray Pattern • 0.021" Orifice Optimum Pressure Range • 1250 - 1500 p.s.i.



CAULKINGS AND SEALANTS
R15020

WARNING: DO NOT FREEZE or apply at freezing conditions, If frozen completely thaw prior to use
KEEP OUT OF REACH OF CHILDREN Consult SDS (Safety Data Sheet) Before Using



Charleroi, PA
210 Fifth Street
Charleroi, PA 15022
724-258-0500

Lodi, CA
810 S. Cluff Avenue
Lodi, CA 95240-9141
209-333-4680

*Additional Manufacturing and Warehousing in
Monongahela, PA and Wagoner, OK*

1-800-245-3188 • www.ductmate.com

© Copyright Ductmate Industries. All rights reserved.



Ductmate Is A Proud Member Of The Following Organizations:



Distributed By: