



COLOR

CHAMPAGNE

SKU

18601PP

THICKNESS

3/4"

WIDTH

4-3/4"

LENGTH

23-5/8"

ENVIRONMENT

No harmful VOC, Prop 65 certified,
LEED credits

All dimensions are nominal!

PRODUCT DETAILS

WOOD SPECIES:

French White Oak

GRADE:

Classic

CONSTRUCTION:

9-ply hardwood

WEAR LAYER:

3 mm sawn cut, live sawn

GLUE:

Carb II, TSCA Title 6 EPA certified

STYLE:

Wire brushed, bevel 4-sides, T&G

Fumed and lime-washed colors

PERFORMANCE & INSTALLATION

FINISH:

UV-cured Urethane, brush matte, 7 - 10% gloss

Static Friction Coefficient (ASTM D 2047): slip resistance < 0.5

WARRANTY:

25 Years Surface (3-Year Light Commercial), Lifetime Structural

COVERAGE:

7.75 sq ft / carton

INSTALLATION:

Glue, float or nail with glue assist

SUBFLOOR:

Wood, concrete or radiant floor systems

RADIANT HEAT:

Yes, glue down or floating installation > 83° F

CERTIFIED MANUFACTURING

- 100% PEFC (PanEuro Forest Council) material
100% chain of custody from forest to jobsite
- Lacey Act compliant
- No halogenated hydrocarbons, herbicides, heavy metals
- No added Urea Formaldehyde, NAF

GREEN BUILD STATEMENT:

Valaire Hardwood Flooring may contribute to attaining points within the Environmental Quality section of the LEED rating system. The determining factor for indoor quality is the quantity of noxious emanations from volatile compounds in adhesives and finishes.

TEST RESULTS:

Emissions Test:

CA - DPH specification 01350 (Prop 65): Pass

Delamination Test:

ANSI/HPVA Bond Line 3 Cycle Test: 100% Pass

Critical Radial Flux:

avg 0.37 w/cm2 ASTM E 648, Class 2 NFPA Life Safety Code 101

NWFA Janka (Hardness):

1200 lbs

Surface Burning:

ASTM E84 Class C

Smoke Density:

Avg.DMC 281-389 Non Flaming ASTM E 662