TECHNICAL SPECIFICATION

PlantMax X3

Technical data

Main	
Type	Two-row tree planter
Weight (typical)	4,500 kg (narrow configuration, no scarifier/subsoiler or carrier included)
Cab	ROPS/FOPS compliant safety cab. 12 mm polycarbonate windows
Climate	Heating, ventilation, air conditioning
Electronic system	24V
Controller system	CAN-based mobile controller system.
Hydraulics	Load sensing pressure compensated. Req. flow/pressure 120L/min 130 ba
Planter	
Performance	3,000 seedlings/h (max technical)
Planter width (C-C)	Narrow: 2250, 2480, 2710 Wide: 2940, 3170, 3440 (mm)
Width adjustment	+/-8° (approx. +/- 220 mm (110 mm/side))
Planting depth	3 different tips (S, M, L); 8 planting hardness levels
Compacting	2 different spades; 8 compactor hardness levels
Seedling spacing	Adjustable, automatic adjustment for missed planting attempts
General	
Fuel tank	Extra 235 litres fuel tank for carrier
Water tank	320 litres
Seedling storage	3 floor storage, >8000 seedlings (depending on size and container)

PLANTMA FORESTRY AB

Storgatan 31
771 30 Ludvika, Sweden

M info@plantmaforestry.com
T +46 240 146 00

www.plantmaforestry.com