Hard Metal Processing,
Convincing through homogeneity and process reliability.

For the hard metal production of feedstocks in granulate or full-strand form.

The Type **K III A** Discharge Kneader stands for maximum process reliability, high efficiency, and reproducible product quality.

Your Advantages at a Glance

Customer-Specific Plant Design
- Batch sizes from 10 to 1000 liters
- Exact reproducibility from batch to batch through recipe management
- Energy-efficient design for lower operating costs
- Individual product mixing thanks to independent drives
- Granule production through granulator integration
- ATEX-compliant construction

Homogeneous Mixtures
- Bubble-free product discharge without air inclusions through vacuum technology in the product chamber and pre-vacuum chamber

Temperature Control Throughout the Entire Process
- All product-contact components, including kneading blades and discharge screw, are temperature-controlled
- Optimal temp. control of the mixing trough up to granulation stage

Reduced Setup, Process, and Downtime
- Ergonomic and user-friendly design
- Fast and easy cleaning thanks to accessibility of the mixing trough and simple disassembly of the mixing tools

High Equipment Availability & Extended Service Life
- Wear protection for maximum durability of product-contact components and mixing tools

*LINDEN-EXTRUSION-KNEADER TYPE K III 100 A

HIGHEST QUALITY | FIRST-CLASS AFTER-SALES SERVICE | MAXIMUM PROCESS STABILITY

Tel.-Nr.: **+49 2264 45910**

E-Mail: **info@linden-kneter.de**

Web: **www.linden-kneter.de**