

Approved Body No. 1121

Certificate of Constancy of Performance

1121-CPR-UK-AG8064

In compliance with Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the Construction Product:

33.01 Series Mortice Sashlock **See Annex A**

Intended use: For use on fire/smoke compartmentation doors

Essential characteristics	Performance	Designated standard
Mechanical test evidence: WIL 310709 & WIL 311797 Fire test evidence: WF 310030 & WF 197132 iss.11		
Self-closing 5.4.2 Closing force 5.1.2 Re-latching force of latch bolt	Grade 8 = 200Kg door mass with 15N maximum closing force. >2.5N	EN 12209:2003 / AC:2005
Durability of self-closing 5.3.1 Durability of latch action	Grade H = 200,000 cycles with 10N side load on latch bolt.	
Ability to maintain the door in the closed position and not contribute to its spread of fire	Grade 1: suitable for use on fire/smoke resistant door assemblies	
Dangerous substances	Pass: the materials in the lock do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

Approved Body No. 1121

Certificate of Constancy of Performance

1121-CPR-UK-AG8064

Placed on the market under the name of

**Merlin Architectural Ltd
Rossmore House
Rossmore Road East
Ellesmere Port
Cheshire
CH65 3DA
United Kingdom**

and produced in the manufacturing plant

J/390

This is coded format, and the information is held by the Approved Body

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 12209:2003 / AC:2005

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **29/06/2023** and will remain valid as long as neither the designated standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Approved Product Certification Body.

UKCA certificate valid to: **17/10/2025**



0087

A handwritten signature in black ink, appearing to read 'Paul Duggan'.

Paul Duggan
Certification Manager

**Warringtonfire Testing and Certification Limited
Suite 302, The Genesis Centre, Birchwood, Warrington, WA3 7BH, UK**

Approved Body No. 1121

Certificate of Constancy of Performance

1121-CPR-UK-AG8064

Annex A

Model No.	Product	Backset	Distance
33.01.31 Series 33.01.32 Series	64/76mm UK Euro Sashlock Square or Radiused Forend	44mm 57mm	57mm