


RUSTIC DRYBACK LVT HERRINGBONE

Specifications

Total thickness	2.5 mm
Wear layer	0.55 mm
Dimensions	730 x 146 mm
Installation Method	Glue-down
Surface area per box	3,8369 m ²
Weight per box	17,37 kg
Pieces per box	36 pieces
Colors	010, 011, 012, 013, 014, 015, 016, 017



EN ISO 10874 Commercial



EN ISO 10874 Domestic



EN ISO 24344



ISO 24343-1



EN 13501-1




DIN 51130



Underfloor Heating
<28°C



ISO4918




Laying instructions on
enviroflooring.eu
or scan the QR code



RUSTIC DRYBACK LVT HERRINGBONE

Testreports

Item	Test Method	Requirement	Test Results
Overall Thickness	ISO 24346	-0.10~0.13mm	Min:2.45 Max:2.60 Avg:2.54
Straightness	ISO 24342	≤0.25mm	Min:0.04 Max:0.13 Avg:0.08
Squareness	ISO 24342	≤0.25mm	Min:0.03 Max:0.12 Avg:0.07
Thickness of Wear Layer	EN428	0.55mm (±0.02mm)	0.56
Gloss at 60° Angle	ASTM D1455	1.5-3°	Min:1.8 Max:3.0 Avg:2.6
Curling (80°C /6H)	ISO 23999	≤2mm	Min:0.23 Max:0.98 Avg:0.63
Dimensions Stability (80°C /6H)	ISO 23999	≤0.25%	CD:0.05% MD:0.09%
Peel resistance	EN 431	≥50N/5cm	Min:73.7 Max:100.6 Avg:80.2
Micro-scratch Resistance	EN160 94	≤2 grade	1 grade
Residual Indentation	ISO 24343-1	≤0.10mm	0.07



Laying instructions on
enviroflooring.eu
or scan the QR code

