29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Pliogrip™ 8804T
ADHESIVE
™ Trademark, Ashland or its subsidiaries, registered in various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : ADHESIVE

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America (USA) +1-614-790-3333 EHSProductSafety@ashland.com	**Emergency telephone number** 1-800-ASHLAND (1-800-274-5263) **Regulatory Information Number** 1-800-325-3751 **Product Information** +1-614-790-3333

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
In case of inadequate ventilation wear respiratory protection.
Response:
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation or rash occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
Storage:
Store locked up.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
TALC	14807-96-6	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	24.365
BUTANEDIOL-1,4	110-63-4	Acute Tox. 4; H302 STOT SE 3; H336	9.10
PIPERAZINE	110-85-0	Flam. Sol. 1; H228 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1B; H334 Skin Sens. 1B; H317 Repr. 2; H361	1.00

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Move to fresh air.
Call a physician or poison control centre immediately.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.

In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye.
If swallowed	:	Obtain medical attention. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) Cough bronchitis Headache Shortness of breath confusion seizures Convulsions Difficulty in breathing Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of damaging fertility or the unborn child.
Notes to physician	:	No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Hydrocarbons Nitrogen oxides (NOx) Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).
Hydrogen chloride gas

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Combination of nitrites or oxides of nitrogen with secondary or tertiary amines can form nitrosamines which are potential carcinogens.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Store in a cool, dry, ventilated area.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
TALC	14807-96-6	TWA	20 Million particles per cubic foot Dust	OSHA Z-3
		TWA	2 mg/m3 respirable dust fraction	OSHA P0
		TWA	2 mg/m3 Respirable	NIOSH REL
		PEL	2 mg/m3 Respirable dust	CAL PEL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA	2 mg/m3 Respirable fraction	ACGIH
PIPERAZINE	110-85-0	TWA	0.03 ppm Inhalable fraction and vapor (piperazine)	ACGIH

Hazardous components without workplace control parameters

Components	CAS-No.
BUTANEDIOL-1,4	110-63-4

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter within the capabilities of the respirator/filter combination.
Where concentrations are above recommended limits or are unknown, or a cartridge type respirator is not adequate, wear a positive-pressure supplied-air respirator.

Hand protection
- Material : butyl-rubber
- Break through time : 480 min
- Glove thickness : > 0.5 mm
- Remarks : The exact break through time can be obtained from the protective glove producer and this has to be observed. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	liquid
Colour	:	tan
Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 93.4 °C
Evaporation rate	:	No data available

Flammability (solid, gas)	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	1.235 g/cm3 (25 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Thermal decomposition	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Product will not undergo hazardous polymerization.
Conditions to avoid	:	Exposure to moisture
Incompatible materials	:	Acids Aldehydes alkalis chlorinated hydrocarbons Copper Copper alloys fluorides Phosphorus compounds

	Strong oxidizing agents
Hazardous decomposition products	Carbon monoxide Carbon dioxide (CO2) Hydrocarbons Acetone carbon dioxide and carbon monoxide Hydrogen chloride gas Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity
Not classified based on available information.
Components:
TALC**:**
Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 423

BUTANEDIOL-1,4**:**
Acute oral toxicity : LD50 (Rat): 1,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.1 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Target Organs: Nervous system
Symptoms: Drowsiness

LC50 (Rat): > 15 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Target Organs: Nervous system
Symptoms: Loss of balance

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

PIPERAZINE**:**

Acute oral toxicity	:	LD50 (Rat): ca. 2,600 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC0 (Rat, male and female): 1.61 mg/l Exposure time: 8 h Test atmosphere: vapour

Skin corrosion/irritation
Causes skin irritation.
Product:
Remarks: May cause skin irritation and/or dermatitis.

Components:
TALC**:**
Species: reconstructed human epidermis (RhE)
Result: No skin irritation

BUTANEDIOL-1,4**:**
Result: No skin irritation

PIPERAZINE**:**
Result: Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation
Causes serious eye irritation.
Product:
Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:
TALC**:**
Species: Rabbit
Result: Slight, transient irritation
Method: OECD Test Guideline 405

BUTANEDIOL-1,4**:**
Result: No eye irritation

PIPERAZINE**:**
Result: Corrosive

Respiratory or skin sensitisation
Skin sensitisation: May cause an allergic skin reaction.
Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Components:
TALC**:**

Test Type: Maximisation Test
Species: Guinea pig
Assessment: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 406
Result: Did not cause sensitisation on laboratory animals.

BUTANEDIOL-1,4**:**
Test Type: Maximisation Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Result: Did not cause sensitisation on laboratory animals.

PIPERAZINE**:**
Assessment: The product is a respiratory sensitiser, sub-category 1B.

Assessment: The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity
Not classified based on available information.
Components:
TALC**:**

Genotoxicity in vitro	:	Test Type: In vitro gene mutation study in bacteria Test species: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative
	:	Test Type: In vitro gene mutation study in bacteria Test species: Saccharomyces cerevisiae Metabolic activation: with and without metabolic activation Result: negative
Genotoxicity in vivo	:	Test Type: dominant lethal test Test species: Rat (male) Cell type: Bone marrow Result: negative

BUTANEDIOL-1,4**:**

Genotoxicity in vitro	:	Test Type: Ames test Result: negative
	:	Test Type: Chromosome aberration test in vitro Result: negative

Carcinogenicity
Not classified based on available information.

Reproductive toxicity
Suspected of damaging fertility or the unborn child.
Components:
PIPERAZINE**:**
Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure
Not classified based on available information.
Components:
BUTANEDIOL-1,4**:**
Exposure routes: inhalation (dust/mist/fume)
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure
Not classified based on available information.
Repeated dose toxicity
Components:
BUTANEDIOL-1,4**:**
Species: Rat
NOAEL: 225 mg/kg
Application Route: Ingestion
Exposure time: 90-day

Aspiration toxicity
Not classified based on available information.
Further information
Product:
Remarks: No data available

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	:	Not classified based on available information.
Long-term (chronic) aquatic hazard	:	Not classified based on available information.

Components:

BUTANEDIOL-1,4**:**

Toxicity to fish	:	LC0 (Pimephales promelas (fathead minnow)): 30,000 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna Straus): 813 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae	:	EC10 (Desmodesmus subspicatus (green algae)): 76 mg/l Exposure time: 72 h Test Type: Cell multiplication inhibition test EC50 (Desmodesmus subspicatus (green algae)): > 500 mg/l Exposure time: 72 h Test Type: Cell multiplication inhibition test

PIPERAZINE**:**

Toxicity to fish	:	LC50 (Poecilia reticulata (guppy)): > 1,800 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 21 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 12.5 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

Persistence and degradability

TALC**:**

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

BUTANEDIOL-1,4**:**
Biodegradability : Biodegradation: 100 %
Exposure time: 14 d
Remarks: Readily biodegradable

Photodegradation :
PIPERAZINE**:**
Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

No data available

Bioaccumulative potential

BUTANEDIOL-1,4**:**
Bioaccumulation : Bioconcentration factor (BCF): 3.16
Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-octanol/water : log Pow: -0.88 (25 °C)

No data available

Mobility in soil

BUTANEDIOL-1,4**:**
Distribution among environmental compartments : Koc: 8.4

No data available

Other adverse effects

Product:
Additional ecological information : No data available

BUTANEDIOL-1,4**:**
Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with

		chemical or used container. Send to a licensed waste management company. Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant		no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
FURAN	110-00-9	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
FURAN	110-00-9	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation
Reproductive toxicity

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

WARNING: This product can expose you to chemicals including Talc (Mg3H2(SiO3)4), Quartz (SiO2), furan, propylene oxide; 1,2-epoxypropane methyloxirane, acetaldehyde; ethanal, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL	:	This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.
AICS	:	Not in compliance with the inventory
ENCS	:	Not in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	Not in compliance with the inventory
IECSC	:	Not in compliance with the inventory
TCSI	:	Not in compliance with the inventory
TSCA	:	On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 10/12/2018

NFPA:	HMIS III:

SAFETY DATA SHEET


Revision Date: 10/12/2018

Print Date: 9/9/2019

SDS Number: 000000247536

Pliogrip™ 8804T ADHESIVE
™ Trademark, Ashland or its subsidiaries, registered in various countries
846899

Version: 1.7



HEALTH	
FLAMMABILITY	
PHYSICAL HAZARD	

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

Full text of H-Statements

H228	Flammable solid.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative