NALCO
An Ecolab Company

SAFETY DATA SHEET

NALCO® 1720

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	NALCO® 1720
Other means of identification	:	Not applicable.
Recommended use	:	OXYGEN SCAVENGER
Restrictions on use	:	Refer to available product literature or ask your local Sales Representative for restrictions on use and dose limits.
Company	:	Nalco Company 1601 W. Diehl Road Naperville, Illinois 60563-1198 USA TEL: (630)305-1000
Emergency telephone number	:	(800) 424-9300 (24 Hours) CHEMTREC
Issuing date	:	11/11/2015


Section: 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral)	:	Category 4
Serious eye damage	:	Category 1

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Harmful if swallowed.
Causes serious eye damage.

Precautionary Statements : **Prevention:**
Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection/face protection.
Response:
IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
Storage:
Protect product from freezing.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration: (%)
Sodium Bisulfite	7631-90-5	10 - 30
Potassium Bisulfite	7773-03-7	1 - 5

Section: 4. FIRST AID MEASURES

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off with soap and plenty of water. Get medical attention if symptoms occur.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Protection of first-aiders : In event of emergency assess the danger before taking action. Do not put yourself at risk of injury. If in doubt, contact emergency responders. Use personal protective equipment as required.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Section: 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Decomposition products may include the following materials: metal oxides

Special protective equipment for firefighters : Use personal protective equipment.

Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Environmental precautions	:	Do not allow contact with soil, surface or ground water.
Methods and materials for containment and cleaning up	:	Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Flush away traces with water.

Section: 7. HANDLING AND STORAGE

Advice on safe handling	:	Do not ingest. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Use only with adequate ventilation.
Conditions for safe storage	:	Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers. Amine and sulphite products should not be stored within close proximity or resulting vapors may form visible airborne particles. Protect product from freezing.
Suitable material	:	The following compatibility data is suggested based on similar product data and/or industry experience: Polypropylene, Buna-N, EPDM, Polyethylene, Polyurethane, PVC, Neoprene, Chlorosulfonated polyethylene rubber, Fluoroelastomer The following compatibility data is suggested based on similar product data and/or industry experience: Compatibility with Plastic Materials can vary; we therefore recommend that compatibility is tested prior to use.
Unsuitable material	:	The following compatibility data is suggested based on similar product data and/or industry experience: Brass, Mild steel, Stainless Steel 304, Stainless Steel 316L, 100% phenolic resin liner, Epoxy phenolic resinThe following compatibility data is suggested based on similar product data and/or industry experience:

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Sodium Bisulfite	7631-90-5	TWA	5 mg/m3	ACGIH
		TWA	5 mg/m3	NIOSH REL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Personal protective equipment

Eye protection	:	Safety goggles Face-shield
Hand protection	:	Wear protective gloves. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin protection	:	Wear suitable protective clothing.
Respiratory protection	:	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid
Colour	:	clear
Odour	:	Pungent
Flash point	:	does not flash
pH	:	3.5 - 4.1, 100 % Method: ASTM E 70
Odour Threshold	:	no data available
Melting point/freezing point	:	FREEZING POINT: -11 °C, ASTM D-1177
Initial boiling point and boiling range	:	96 °C (760 mm Hg) Method: ASTM D 86
Evaporation rate	:	no data available
Flammability (solid, gas)	:	no data available
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	no data available
Relative vapour density	:	no data available
Relative density	:	1.22 - 1.28 (15.6 °C)
Density	:	10.1 - 10.7 lb/gal
Water solubility	:	completely soluble
Solubility in other solvents	:	no data available

Partition coefficient: n-octanol/water	:	no data available
Auto-ignition temperature	:	no data available
Thermal decomposition temperature	:	no data available
Viscosity, dynamic	:	5 mPa.s (15 °C) Method: ASTM D 2983
Viscosity, kinematic	:	no data available
Molecular weight	:	no data available
VOC	:	no data available

Section: 10. STABILITY AND REACTIVITY

Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.
Conditions to avoid	:	Freezing temperatures.
Incompatible materials	:	Contact with strong acids (e.g. sulfuric, phosphoric, nitric, hydrochloric, chromic, sulfonic) may generate heat, splattering or boiling and toxic vapors. Contains Sulfite. SO2 may react with vapors from neutralizing amines and may produce a visible cloud of amine salt particles.
Hazardous decomposition products	:	Decomposition products may include the following materials: metal oxides Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	:	Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes	:	Causes serious eye damage.
Skin	:	Health injuries are not known or expected under normal use.
Ingestion	:	Harmful if swallowed.
Inhalation	:	Health injuries are not known or expected under normal use.
Chronic Exposure	:	Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact	:	Redness, Pain, Corrosion

Skin contact	:	No symptoms known or expected.
Ingestion	:	No information available.
Inhalation	:	No symptoms known or expected.

Toxicity

Product

Acute oral toxicity	:	Acute toxicity estimate 1,782 mg/kg
Acute inhalation toxicity	:	no data available
Acute dermal toxicity	:	rabbit: > 3,000 mg/kg Test substance: Similar Product
Skin corrosion/irritation	:	Result: 1.0 Method: Draize Test Test substance:Similar Product
Serious eye damage/eye irritation	:	Result: 9.4 Method: Draize Test Test substance: Similar Product
Respiratory or skin sensitization	:	Result: Contains an ingredient that can cause asthmatic-like reactions in sulfite-sensitive individuals.
Carcinogenicity	:	no data available
Reproductive effects	:	no data available
Germ cell mutagenicity	:	no data available
Teratogenicity	:	no data available
STOT - single exposure	:	no data available
STOT - repeated exposure	:	no data available
Aspiration toxicity	:	no data available

Section: 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects	:	This product has no known ecotoxicological effects.

Product

Toxicity to fish	:	LC50 Pimephales promelas (fathead minnow): 382 mg/l

Exposure time: 96 hrs
Test substance: Product

LC50 Inland Silverside: > 5,000 mg/l
Exposure time: 96 hrs
Test substance: Product

NOEC Pimephales promelas (fathead minnow): 250 mg/l
Exposure time: 96 hrs
Test substance: Product

NOEC Inland Silverside: 5,000 mg/l
Exposure time: 96 hrs
Test substance: Product

Toxicity to daphnia and other aquatic invertebrates : LC50 Daphnia magna (Water flea): 728 mg/l
Exposure time: 48 hrs
Test substance: Product

LC50 Mysid Shrimp (Mysidopsis bahia): > 5,000 mg/l
Exposure time: 96 hrs
Test substance: Product

NOEC Daphnia magna (Water flea): 250 mg/l
Exposure time: 48 hrs
Test substance: Product

NOEC Mysid Shrimp (Mysidopsis bahia): 5,000 mg/l
Exposure time: 96 hrs
Test substance: Product

EC50 Ceriodaphnia dubia: 491 mg/l
Exposure time: 48 hrs
Test substance: Product

LC50 Ceriodaphnia dubia: 508 mg/l
Exposure time: 48 hrs
Test substance: Product

NOEC Ceriodaphnia dubia: 313 mg/l
Exposure time: 48 hrs
Test substance: Product

Persistence and degradability

Greater than 95% of this product consists of inorganic substances for which a biodegradation value is not applicable.

Mobility

The environmental fate was estimated using a level III fugacity model embedded in the EPI (estimation program interface) Suite TM, provided by the US EPA. The model assumes a steady state condition between the total input and output. The level III model does not require equilibrium between the defined media. The information provided is intended to give the user a general estimate of the environmental fate of this product under the defined conditions of the models.

If released into the environment this material is expected to distribute to the air, water and soil/sediment in the approximate respective percentages;

Air	:	<5%
Water	:	30 - 50%
Soil	:	50 - 70%

The portion in water is expected to be soluble or dispersible.

Bioaccumulative potential

The product will not bioaccumulate.

Other information

no data available

Section: 13. DISPOSAL CONSIDERATIONS

If this product becomes a waste, it is not a hazardous waste as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, since it does not have the characteristics of Subpart C, nor is it listed under Subpart D.

Disposal methods	:	Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
Disposal considerations	:	Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (DOT)

The presence of an RQ component (Reportable Quantity for U.S. DOT) in this product causes it to be regulated with an additional description of RQ for road, or as Environmentally hazardous for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name(s)	:	SODIUM BISULFITE
UN/ID No.	:	UN 3082
Transport hazard class(es)	:	9
Packing group	:	III
Reportable Quantity (per package)	:	18,347 lbs
RQ Component	:	SODIUM BISULFITE

Air transport (IATA)

The presence of an RQ component (Reportable Quantity for U.S. DOT) in this product causes it to be regulated with an additional description of RQ for road, or as Environmentally hazardous for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name(s)	:	SODIUM BISULFITE
UN/ID No.	:	UN 3082
Transport hazard class(es)	:	9
Packing group	:	III
Reportable Quantity (per package)	:	18,347 lbs
RQ Component	:	SODIUM BISULFITE

Sea transport (IMDG/IMO)

Proper shipping name	:	PRODUCT IS NOT REGULATED DURING TRANSPORTATION

Section: 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium Bisulfite	7631-90-5	5000	18347

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Acute Health Hazard
SARA 302	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

INTERNATIONAL CHEMICAL CONTROL LAWS :

TOXIC SUBSTANCES CONTROL ACT (TSCA)
The substances in this preparation are included on or exempted from the TSCA 8(b) Inventory (40 CFR 710)

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA)
The substance(s) in this preparation are included in or exempted from the Domestic Substance List (DSL).

AUSTRALIA
All substances in this product comply with the National Industrial Chemicals Notification & Assessment Scheme (NICNAS).

CHINA
All substances in this product comply with the Provisions on the Environmental Administration of New Chemical Substances and are listed on or exempt from the Inventory of Existing Chemical Substances China (IECSC).

JAPAN
All substances in this product comply with the Law Regulating the Manufacture and Importation Of Chemical Substances and are listed on the Existing and New Chemical Substances list (ENCS).


KOREA
All substances in this product comply with the Toxic Chemical Control Law (TCCL) and are listed on the Existing Chemicals List (ECL)

NEW ZEALAND
All substances in this product comply with the Hazardous Substances and New Organisms (HSNO) Act 1996,and are listed on or are exempt from the New Zealand Inventory of Chemicals.

PHILIPPINES
All substances in this product comply with the Republic Act 6969 (RA 6969) and are listed on the Philippines Inventory of Chemicals & Chemical Substances (PICCS).

Section: 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date	:	11/11/2015
Version Number	:	1.5
Prepared By	:	Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

For additional copies of an SDS visit www.nalco.com and request access.