SAFETY DATA SHEET

Issuing Date 29-Jun-2016 **Revision Date** 29-Jun-2016 **Revision Number** 5

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THECOMPANY/UNDERTAKING

Product identifier

Product Name **42348 Super Tech Engine Starting Fluid 11 OZ.**

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Engine Starting Fluid

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Technical Chemical Co.

Supplier Address 3327 Pipeline Road
Box 139
Cleburne
TX
76033
US

Supplier Phone Number Phone:817-645-6088 Fax:817-645-6088

Supplier Email mhutchinson@technicalchemical.com

Emergency telephone number

Company Emergency Phone Number 800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A

Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements

Emergency Overview

Signal word **Danger**

Hazard Statements
Causes skin irritation
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child
May cause respiratory irritation. May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Appearance Clear, colorless to yellow **Physical state** Aerosol Liquid spray **Odor** Ether

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Pressurized container: Do not pierce or burn, even after use
Do not spray on an open flame or other ignition source

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)

Skin
IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Inhalation
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
Protect from sunlight

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

43.5 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if swallowed
Toxic to aquatic life with long lasting effects
INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical name	CAS No	Weight-%	Trade Secret
Petroleum gases, liquified, sweetened	68476-86-8	10 - 30	*
Ethyl ether	60-29-7	10 - 30	*
Heptane	142-82-5	7 - 13	*
Carbon Dioxide	124-38-9	3 - 7	*
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	0.1 - 1	*
Toluene	108-88-3	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

Ingestion	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects	Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists. Dry chemical, CO2, alcohol-resistant foam or water spray.

Unsuitable extinguishing media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

Uniform Fire Code	Irritant: Liquid Aerosols: Level III

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact Yes. **Sensitivity to Static Discharge** Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Stop leak if you can do it without risk.
Other Information	Ventilate the area.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. **Methods and material for containment and cleaning up**

Methods for containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

Methods for cleaning up Do not direct water at spill or source of leak.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with eyes.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Protect from moisture. Keep out of the reach of children. Store away from other materials. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl ether 60-29-7	STEL: 500 ppm TWA: 400 ppm	TWA: 400 ppm TWA: 1200 mg/m^3 (vacated) TWA: 400 ppm (vacated) TWA: 1200 mg/m^3 (vacated) STEL: 500 ppm (vacated) STEL: 1500 mg/m^3	IDLH: 1900 ppm
Heptane	STEL: 500 ppm	TWA: 500 ppm	IDLH: 750 ppm
142-82-5	TWA: 400 ppm	TWA: 2000 mg/m^3 (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m^3 (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m^3	Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m^3 15 min TWA: 85 ppm TWA: 350 mg/m^3
Carbon Dioxide 124-38-9	STEL = 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m^3 (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m^3 (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m^3	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m^3 STEL: 30000 ppm STEL: 54000 mg/m^3
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m^3 (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m^3 Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m^3 STEL: 150 ppm STEL: 560 mg/m^3

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures	Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Skin and body protection	Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Aerosol, Liquid spray		
Appearance	Clear, colorless to yellow	**Odor**	Ether
Color	No information available	**Odor Threshold**	No information available

Property	**Values**	**Remarks Method**
pH	UNKNOWN	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known

Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	.710	None known
Water Solubility	Partially soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Excessive heat.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information .

Inhalation

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.

Eye contact

Specific test data for the substance or mixture is not available. May cause redness, itching, and pain. May cause irritation.

Skin contact

Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Repeated exposure may cause skin dryness or cracking.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. (based on components).

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl ether 60-29-7	= 1215 mg/kg (Rat)	> 20 mL/kg (Rabbit)	-
Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m^3 (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms

Erythema (skin redness). May cause redness and tearing of the eyes. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Mutagenic Effects

Contains a known or suspected mutagen.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethyl ether 60-29-7		Group 3		
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5	A2	Group 1	Known	X
Toluene 108-88-3		Group 3		

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP (National Toxicology Program)
Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity

Contains a known or suspected reproductive toxin. Product is or contains a chemical which is a known or suspected reproductive hazard.

STOT - single exposure	Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product.
STOT - repeated exposure	No information available.
Chronic Toxicity	Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Aspiration may cause pulmonary edema and pneumonitis. Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects. May cause adverse liver effects.
Target Organ Effects	Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Reproductive System. Central Nervous System (CNS). Central Vascular System (CVS). Liver. Kidney.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
3,432.00 mg/kg
ATEmix (dermal)
15,409.00 mg/kg (ATE)
ATEmix (inhalation-dust/mist)
529.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity
Toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethyl ether 60-29-7		96h LC50: = 2560 mg/L (Pimephales promelas) 96h LC50: > 10000 mg/L (Lepomis macrochirus)	EC50 = 5600 mg/L 15 min	24h EC50: = 165 mg/L
Heptane 142-82-5		96h LC50: = 375.0 mg/L (Cichlid fish)		24h EC50: > 10 mg/L
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5		96h LC50: > 5000 mg/L (Oncorhynchus mykiss)		48h EC50: > 1000 mg/L

Toluene 108-88-3	96h EC50: > 433 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 12.5 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 15.22 - 19.05 mg/L (Pimephales promelas) 96h LC50: 5.89 - 7.81 mg/L (Oncorhynchus mykiss) 96h LC50: 14.1 - 17.16 mg/L (Oncorhynchus mykiss) 96h LC50: = 5.8 mg/L (Oncorhynchus mykiss) 96h LC50: = 12.6 mg/L (Pimephales promelas) 96h LC50: 11.0 - 15.0 mg/L (Lepomis macrochirus) 96h LC50: = 54 mg/L (Oryzias latipes) 96h LC50: = 28.2 mg/L (Poecilia reticulata) 96h LC50: 50.87 - 70.34 mg/L (Poecilia reticulata)	EC50 = 19.7 mg/L 30 min	48h EC50: 5.46 - 9.83 mg/L 48h EC50: = 11.5 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Log Pow
Petroleum gases, liquified, sweetened 68476-86-8	<=2.8
Ethyl ether 60-29-7	0.82
Heptane 142-82-5	4.66
Toluene 108-88-3	2.7

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes

Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Ethyl ether 60-29-7	Ignitable Reactive
Heptane 142-82-5	Toxic Ignitable
Toluene 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY

Hazard Class ORM-D

Description CONSUMER COMMODITY, ORM-D

Emergency Response Guide Number 126

TDG

UN-No. UN1950

Proper Shipping Name AEROSOLS

Hazard Class 2.1

Description UN1950, AEROSOLS, 2.1

MEX

UN-No. UN1950

Proper Shipping Name AEROSOLS

Hazard Class 2.1

Description UN1950, AEROSOLS, 2.1

ICAO

UN-No. UN1950

Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Description	UN1950, AEROSOLS, 2.1

IATA

UN-No.	UN1950
Proper Shipping Name	AEROSOLS, FLAMMABLE
Hazard Class	2.1
ERG Code	10L
Description	UN1950, AEROSOLS, FLAMMABLE, 2.1

IMDG/IMO

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
EmS-No.	F-D S-U
Description	UN1950, AEROSOLS, 2.1

RID

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Classification code	5F
Description	UN1950, AEROSOLS, 2.1

ADR

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Classification code	5F
Tunnel restriction code	(D)
Description	UN1950, AEROSOLS, 2.1

ADN

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Classification code	5F

Special Provisions	190, 327, 344, 625
Description	UN1950, AEROSOLS, 2.1
Hazard Labels	2.1
Limited Quantity	1 L
Ventilation	VE01, VE04

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

IECSC

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethyl ether 60-29-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Toluene - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Ethyl ether 60-29-7	X	X	X	X	
Heptane 142-82-5	X	X	X		
Carbon Dioxide 124-38-9	X	X	X		-
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5					X
Toluene 108-88-3	X	X	X	X	X

International Regulations

Mexico National occupational exposure limits

Chemical name	Carcinogen Status	Exposure Limits
Ethyl ether		Mexico: TWA 400 ppm Mexico: TWA 1200 mg/m^3 Mexico: STEL 500 ppm Mexico: STEL 1500 mg/m^3
Heptane		Mexico: TWA 400 ppm Mexico: TWA 1600 mg/m^3 Mexico: STEL 500 ppm Mexico: STEL 2000 mg/m^3
Carbon Dioxide	-	Mexico: TWA= 5000 ppm Mexico: TWA= 9000 mg/m^3 Mexico: STEL= 15000 ppm Mexico: STEL= 27000 mg/m^3
Toluene		Mexico: TWA 50 ppm Mexico: TWA 188 mg/m^3

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Not determined

16. OTHER INFORMATION

NFPA	**Health Hazards** 2	**Flammability** 4	**Instability** 0	**Physical and Chemical Hazards** -
HMIS	**Health Hazards** 2 *	**Flammability** 4	**Physical Hazard** 0	**Personal Protection** X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By
Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 29-Jun-2016
Revision Date 29-Jun-2016
Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet