SAFETY DATA SHEET

according to the Globally Harmonized System and US regulation

Distributed by:
SUPERIOR
1402 N. Capitol Ave., Ste. 100
Indianapolis, IN 46202
(317) 781-4400
www.superioroil.com

TRIGONOX C

Version 1 Revision Date 03/31/2020 Print Date 01/19/2021 US / Z8

1. IDENTIFICATION

Product name	:	TRIGONOX C
Product Use Description	:	Specific use(s): Polymerization initiator
Company	:	Nouryon Functional Chemicals LLC 131 S Dearborn St, Suite 1000 Chicago IL 60603-5566 US
Telephone	:	+18008287929
Fax	:	+13125447188
E-mail address	:	polymer.amer@nouryon.com
Emergency telephone	:	24 hours:+31 57 06 79211, CHEMTREC-USA:1-800-424-9300, CANUTEC-CANADA:1-613-996-6666, 化学事故应急咨询电话：国家化学事故应急响应中心 +86 532 8388 9090

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	colorless
Odor	Faint.

GHS Classification

Organic peroxides, Type C
Acute toxicity, Category 4, Inhalation
Skin irritation, Category 2
Skin sensitization, Category 1
Short-term (acute) aquatic hazard, Category 1
Long-term (chronic) aquatic hazard, Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H242 Heating may cause a fire.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.

H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P220 Keep/Store away from clothing/ combustible materials.
P234 Keep only in original container.
P235 Keep cool.
P261 Avoid breathing mist, vapours or spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P391 Collect spillage.
Storage:
P410 Protect from sunlight.
P420 Store away from other materials.
Disposal:
P501 Dispose of contents/container in accordance with local regulation.

Carcinogenicity:

IARC : No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA : No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP : No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Common Name : Organic peroxide
Pure substance/mixture : Substance

Hazardous ingredients

Chemical name	CAS-No.	Classification	Concentration [% W/W]
tert-Butyl peroxybenzoate	614-45-9	Org. Perox. C; H242 Acute Tox. 4; H332 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 M-Factor (Acute): 1	99 - 100

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.

Inhalation : If breathed in, move person into fresh air.
Consult a physician after significant exposure.

Skin contact : Take off contaminated clothing and shoes immediately.
Rinse immediately with plenty of water.
If skin irritation persists, call a physician.

Eye contact : Rinse with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

Ingestion : Clean mouth with water and drink afterwards plenty of water.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

Notes to physician

Symptoms : The symptoms and effects are as expected from the hazards as shown in section 2. No specific product related symptoms are known.

Risks : Causes skin irritation.
May cause an allergic skin reaction.
Harmful if inhaled.

Treatment : Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting / Specific hazards arising from the chemical	:	CAUTION: reignition may occur. Supports combustion. Do not use a solid water stream as it may scatter and spread fire. Water spray may be ineffective unless used by experienced firefighters. Do not allow run-off from fire fighting to enter drains or water courses. Hazardous decomposition products formed under fire conditions.
Combustion products	:	Fire will produce smoke containing hazardous combustion products (see section 10).
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

See also Section 9. Physical and chemical properties: Safety data

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Wear respiratory protection. Ensure adequate ventilation. Remove all sources of ignition. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Emergency measures on accidental release	:	Evacuate personnel to safe areas. Only qualified personnel equipped with suitable protective equipment may intervene. Prevent unauthorized persons entering the zone.
Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up / Methods for containment	:	Soak up with inert absorbent material and dispose of as hazardous waste. Keep wetted with water. Confinement must be avoided. Never return spills in original containers for re-use.

Reference to other sections	:	For disposal considerations see section 13. For personal protection see section 8.

7. HANDLING AND STORAGE

Handling

Advice on safe handling	:	For personal protection see section 8. Avoid formation of aerosol. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against fire and explosion	:	Use explosion protected equipment. Keep away from sources of ignition - No smoking. No sparking tools should be used. Keep away from reducing agents (e.g. amines), acids, alkalies and heavy metal compounds (e.g. accelerators, driers, metal soaps). Do not cut or weld on or near this container even when empty. Keep away from combustible material.
Temperature class	:	It is recommended to use electrical equipment of temperature group T3. However, autoignition can never be excluded.

Storage

Requirements for storage areas and containers	:	No smoking. Keep in a well-ventilated place. Electrical installations / working materials must comply with the technological safety standards. Keep only in original container. Store away from other materials.
Minimum storage temperature:	:	Avoid temperatures below: 10 °C (50 °F)
Maximum storage temperature:	:	25 °C (77 °F)
Other data	:	If product freezes or separates, contact the manufacturer. Maximum storage temperature is for quality only.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Decomposition products	CAS-No.	Value	Control parameters	Update	Basis	Form of exposure
Benzene	71-43-2	TWA	0.5 ppm	2007-01-01	ACGIH	
	Further information	:	leukemia: Leukemia BEI: Substances for which there is a Biological Exposure Index or Indices (see BEI® section) A1: Confirmed human carcinogen Skin: Danger of cutaneous absorption			
		STEL	2.5 ppm	2007-01-01	ACGIH	
	Further information	:	leukemia: Leukemia BEI: Substances for which there is a Biological Exposure Index or Indices (see BEI® section) A1: Confirmed human carcinogen Skin: Danger of cutaneous absorption			
		TWA	0.1 ppm	2013-10-08	NIOSH REL	
	Further information	:	Ca: Potential Occupational Carcinogen See Appendix A			
		ST	1 ppm	2013-10-08	NIOSH REL	
	Further information	:	Ca: Potential Occupational Carcinogen See Appendix A			
		TWA	10 ppm	2012-07-01	OSHA Z-2	
	Further information	:	Z37.40-1969 (a): This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard at 1910.1028.			
		CEIL	25 ppm	2012-07-01	OSHA Z-2	
	Further information	:	Z37.40-1969 (a): This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard at 1910.1028.			
		Peak	50 ppm	2012-07-01	OSHA Z-2	
	Further information	:	Z37.40-1969 (a): This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard at 1910.1028.			
	Further information	:	See 1910.1028. See Table Z-2 for the limits applicable in the operations or sectors excluded in 1910.1028 d: The final benzene standard in 1910.1028 applies to all occupational exposures to benzene except some subsegments of industry where exposures are consistently under the action level (i.e., distribution and sale of fuels, sealed containers and pipelines, coke production, oil and gas drilling and production, natural gas processing, and the percentage exclusion for liquid mixtures); for the excepted subsegments, the benzene limits in Table Z-2 apply.			
	Further information	:	Substance listed; for more information see OSHA document 1910.1028 See Table Z-2 for the limits applicable in the operations or sectors excluded in 1910.1028d. (d) The final benzene standard in 1910.1028 applies to all occupational exposures to benzene except in some circumstances the distribution and sale of fuels, sealed containers and pipelines, coke production, oil and gas drilling and production, natural gas processing, and the percentage exclusion for liquid mixtures; for the excepted subsegments, the benzene limits in Table Z-2 apply. See 1910.1028 for specific circumstances.			
		PEL	1 ppm	2012-04-03	OSHA CARC	
	Further information	:	1910.1028 This section applies to all occupational exposures to benzene. Chemical Abstracts Service Registry No. 71-43-2, except as provided in paragraphs (a)(2) and (a)(3) of this section. Paragraph (a)(2): This section does not			

			apply to: (i) The storage, transportation, distribution, dispensing, sale or use of gasoline, motor fuels, or other fuels containing benzene subsequent to its final discharge from bulk w holesale storage facilities, except that operations w here gasoline or motor fuels are dispensed for more than 4 hours per day in an indoor location are covered by this section. (ii) Loading and unloading operations at bulk w holesale storage facilities w hich use vapor control systems for all loading and unloading operations, except for the provisions of 29 CFR 1910.1200 as incorporated into this section and the emergency provisions of paragraphs (g) and (i)(4) of this section. (iii) The storage, transportation, distribution or sale of benzene or liquid mixtures containing more than 0.1 percent benzene in intact containers or in transportation pipelines w hile sealed in such a manner as to contain benzene vapors or liquid, except for the provisions of 29 CFR 1910.1200 as incorporated into this section and the emergency provisions of paragraphs (g) and (i)(4) of this section. (iv) Containers and pipelines carrying mixtures w ith less than 0.1 percent benzene and natural gas processing plants processing gas w ith less than 0.1 percent benzene. (v) Work operations w here the only exposure to benzene is from liquid mixtures containing 0.5 percent or less of benzene by volume, or the vapors released from such liquids until September 12, 1988; w ork operations w here the only exposure to benzene is from liquid mixtures containing 0.3 percent or less of benzene by volume or the vapors released from such liquids from September 12, 1988, to September 12, 1989; and w ork operations w here the only exposure to benzene is from liquid mixtures containing 0.1 percent or less of benzene by volume or the vapors released from such liquids after September 12, 1989; except that tire building machine operators using solvents w ith more than 0.1 percent benzene are covered by paragraph (i) of this section. (vi) Oil and gas drilling, production and servicing operations. (vii) Coke oven batteries. Paragraph (a)(3): The cleaning and repair of barges and tankers w hich have contained benzene are excluded from paragraph (f) methods of compliance, paragraph (e)(1) exposure monitoring-general, and paragraph (e)(6) accuracy of monitoring. Engineering and w ork practice controls shall be used to keep exposures below 10 ppm unless it is proven to be not feasible. Benzene (C6H6) (CAS Registry No. 71-43-2) means liquefied or gaseous benzene. It includes benzene contained in liquid mixtures and the benzene vapors released by these liquids. It does not include trace amounts of unreacted benzene contained in solid materials OSHA specifically regulated carcinogen
		STEL	5 ppm	2012-04-03	OSHA CARC	
	Further information	:	1910.1028 This section applies to all occupational exposures to benzene. Chemical Abstracts Service Registry No. 71-43-2, except as provided in paragraphs (a)(2) and (a)(3) of this section. Paragraph (a)(2): This section does not apply to: (i) The storage, transportation, distribution, dispensing, sale or use of gasoline, motor fuels, or other fuels containing benzene subsequent to its final discharge from bulk w holesale storage facilities, except that operations w here gasoline or motor fuels are dispensed for more than 4 hours per day in an indoor location are covered by this section. (ii) Loading and unloading operations at bulk w holesale storage facilities w hich use vapor control systems for all loading and unloading operations, except for the provisions of 29 CFR 1910.1200 as incorporated into this section and the emergency provisions of paragraphs (g) and (i)(4) of this section. (iii) The storage, transportation, distribution or sale of benzene or liquid mixtures containing more than 0.1 percent benzene in intact containers or in transportation pipelines w hile sealed in such a manner as to contain benzene vapors or liquid, except for the provisions of 29 CFR 1910.1200 as incorporated into this section and the emergency provisions of paragraphs (g) and (i)(4) of this section. (iv) Containers and pipelines carrying mixtures w ith less than 0.1 percent benzene and natural gas processing plants processing gas w ith less than 0.1 percent benzene. (v) Work operations w here the only exposure to benzene is from liquid mixtures containing 0.5 percent or less of benzene by volume, or the vapors released from such liquids until September 12, 1988; w ork operations w here the only exposure to benzene is from liquid mixtures containing 0.3 percent or less of benzene by volume or the vapors released from such liquids from September 12, 1988, to September 12, 1989; and w ork operations w here the only exposure to benzene is from liquid mixtures containing 0.1 percent or less of benzene by volume or the vapors released from such liquids after September 12, 1989; except that tire building machine operators using solvents w ith more than 0.1 percent benzene are covered by paragraph (i) of this section. (vi) Oil and gas drilling, production and servicing operations. (vii) Coke oven batteries. Paragraph (a)(3): The

			cleaning and repair of barges and tankers w hich have contained benzene are excluded from paragraph (f) methods of compliance, paragraph (e)(1) exposure monitoring-general, and paragraph (e)(6) accuracy of monitoring. Engineering and w ork practice controls shall be used to keep exposures below 10 ppm unless it is proven to be not feasible. Benzene (C6H6) (CAS Registry No. 71-43-2) means liquefied or gaseous benzene. It includes benzene contained in liquid mixtures and the benzene vapors released by these liquids. It does not include trace amounts of unreacted benzene contained in solid materials OSHA specifically regulated carcinogen			
		PEL	1 ppm	2014-11-26	CAL PEL	
	Further information	:	S: Skin see Section 5218			
		STEL	5 ppm	2014-11-26	CAL PEL	
	Further information	:	S: Skin see Section 5218			
tert-Butanol	75-65-0, 75-65-0	TWA	100 ppm	2007-01-01	ACGIH	
	Further information	:	CNS impair: Central Nervous System impairment A4: Not classifiable as a human carcinogen			
		TWA	100 ppm 300 mg/m3	2013-10-08	NIOSH REL	
		ST	150 ppm 450 mg/m3	2013-10-08	NIOSH REL	
		TWA	100 ppm 300 mg/m3	1997-08-04	OSHA Z-1	
	Further information	:	(b): The value in mg/m3 is approximate.			
		TWA	100 ppm 300 mg/m3	1989-01-19	OSHA P0	
		STEL	150 ppm 450 mg/m3	1989-01-19	OSHA P0	
		PEL	100 ppm 300 mg/m3	2014-11-26	CAL PEL	
		STEL	150 ppm 450 mg/m3	2014-11-26	CAL PEL	
Acetone	67-64-1, 67-64-1	TWA	250 ppm	2015-04-10	ACGIH	
	Further information	:	CNS impair: Central Nervous System impairment URT irr: Upper Respiratory Tract irritation eye irr: Eye irritation *: 2018 Adoption BEI: Substances for which there is a Biological Exposure Index or Indices (see BEI® section) A4: Not classifiable as a human carcinogen			
		STEL	500 ppm	2015-04-10	ACGIH	
	Further information	:	CNS impair: Central Nervous System impairment URT irr: Upper Respiratory Tract irritation eye irr: Eye irritation *: 2018 Adoption BEI: Substances for which there is a Biological Exposure Index or Indices (see BEI® section) A4: Not classifiable as a human carcinogen			
		TWA	250 ppm 590 mg/m3	2013-10-08	NIOSH REL	
		TWA	1,000 ppm 2,400 mg/m3	1997-08-04	OSHA Z-1	
	Further information	:	(b): The value in mg/m3 is approximate.			
		TWA	750 ppm 1,800 mg/m3	1989-01-19	OSHA P0	
		STEL	1,000 ppm 2,400 mg/m3	1989-01-19	OSHA P0	
	Further information	:	h: The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors.			
		STEL	750 ppm 1,780 mg/m3	2014-11-26	CAL PEL	

		C	3,000 ppm	2014-11-26	CAL PEL	
		PEL	500 ppm 1,200 mg/m3	2014-11-26	CAL PEL	
Carbon dioxide	124-38-9	TWA	5,000 ppm	2007-01-01	ACGIH	
	Further information	:	asphyxia: Asphyxia			
		STEL	30,000 ppm	2007-01-01	ACGIH	
	Further information	:	asphyxia: Asphyxia			
		TWA	5,000 ppm 9,000 mg/m3	2013-10-08	NIOSH REL	
	Further information	:	Normal constituent of air (about 300 ppm).			
		ST	30,000 ppm 54,000 mg/m3	2013-10-08	NIOSH REL	
	Further information	:	Normal constituent of air (about 300 ppm).			
		TWA	5,000 ppm 9,000 mg/m3	1997-08-04	OSHA Z-1	
	Further information	:	(b): The value in mg/m3 is approximate.			
		TWA	10,000 ppm 18,000 mg/m3	1989-01-19	OSHA P0	
	Further information	:	e: Exposures under 10,000 ppm to be cited as de minimus.			
		STEL	30,000 ppm 54,000 mg/m3	1989-01-19	OSHA P0	
		PEL	5,000 ppm 9,000 mg/m3	2014-11-26	CAL PEL	
		STEL	30,000 ppm 54,000 mg/m3	2014-11-26	CAL PEL	

Appropriate engineering controls
Explosion proof ventilation recommended.
Effective exhaust ventilation system

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles

Hand protection : Glove material: Nitrile rubber
Break through time: 480 min
Glove thickness: > 0.4 mm

: Glove material: Nitrile rubber
Break through time: 30 min
Glove thickness: > 0.11 mm

: The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.

Skin and body protection : Protective suit

Respiratory protection : In the case of vapor or aerosol formation use a respirator with an approved filter.
Filter A

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Wash contaminated clothing before re-use.

Environmental exposure controls

General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	:	liquid
Color	:	colorless
Odor	:	Faint.
Odor Threshold	:	No data available

Safety data

pH	:	neutral
Melting point	:	9 - 11 °C
Boiling point/boiling range	:	Decomposes below the boiling point.
Flash point	:	Above the SADT value
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Decomposition products may be flammable.
Lower explosion limit	:	No data available
Upper explosion limit	:	No data available
Vapor pressure	:	0.4 hPa at 50 °C
Relative vapor density	:	No data available
Relative density	:	1.04 at 20 °C
Bulk density	:	Not applicable
Water solubility	:	at 20 °C immiscible
Solubility in other solvents	:	Soluble in most organic solvents.
Partition coefficient: n-octanol/water	:	log Pow: 3 at 25 °C

Autoignition temperature	:	Test method not applicable
Decomposition temperature	:	SADT - (Self accelerating decomposition temperature) is the lowest temperature at which self accelerating decomposition may occur with a substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at and above the SADT. Contact with incompatible substances can cause decomposition below the SADT.
Self-Accelerating decomposition temperature (SADT)	:	60 °C
Viscosity, dynamic	:	6 mPa.s at 20 °C
Viscosity, kinematic	:	5.77 mm2/s at 20 °C
Explosive properties	:	Not explosive
Oxidizing properties	:	Not classified as oxidizing.
Active Oxygen Content	:	8 %
Organic peroxides	:	98 %

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

10. STABILITY AND REACTIVITY

Conditions to avoid	:	Confinement must be avoided. Heat, flames and sparks.
Materials to avoid	:	Contact with the following incompatible materials will result in hazardous decomposition: Acids and bases Iron Copper Reducing agents Heavy metals Rust Do not mix with peroxide accelerators, unless under controlled processing. Use only stainless steel 316, PP, polyethylene or glass-lined equipment. For queries regarding the suitability of other materials please contact the supplier.
Hazardous decomposition products	:	Benzene tert-Butanol Acetone Carbon dioxide Methane Benzoic acid

Thermal decomposition	:	SADT - (Self accelerating decomposition temperature) is the lowest temperature at which self accelerating decomposition may occur with a substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at and above the SADT. Contact with incompatible substances can cause decomposition below the SADT.
Reactivity	:	Stable under normal conditions.
Chemical stability	:	Stable under recommended storage conditions.
Hazardous reactions	:	No dangerous reaction known under conditions of normal use.
Self-Accelerating decomposition temperature (SADT)	:	60 °C (140 °F)

11. TOXICOLOGICAL INFORMATION

PRODUCT INFORMATION:

Hazard Summary

Acute toxicity	:	Harmful if inhaled.
Skin corrosion/irritation	:	Causes skin irritation.
Serious eye damage/eye irritation	:	Not classified based on available information.
Respiratory or skin sensitization	:	Respiratory sensitization: Not classified based on available information. Skin sensitization: May cause an allergic skin reaction.
Germ cell mutagenicity	:	Not classified based on available information.
Carcinogenicity	:	Not classified based on available information.
Reproductive toxicity	:	Not classified based on available information.
STOT-single exposure	:	Not classified based on available information.
STOT-repeated exposure	:	Not classified based on available information.
Aspiration hazard	:	Not classified based on available information.

Potential Health Effects

Inhalation	:	Inhalation of aerosols may cause irritation to mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Harmful if inhaled.
Skin	:	Causes skin irritation. May cause an allergic skin reaction.

Eyes	:	May cause eye irritation.
Ingestion	:	May cause irritation of the mucous membranes.
Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	The symptoms and effects are as expected from the hazards as shown in section 2. No specific product related symptoms are known.

Toxicology Assessment

Further information	:	No further data available.

Carcinogenicity:

IARC	:	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	:	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	:	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

TOXICOLOGY DATA FOR THE INGREDIENTS:

Test result

Component: tert-Butyl peroxybenzoate

Acute inhalation toxicity	:	LC50 : > 1.01 mg/l Exposure time: 4 h Test atmosphere: aerosol Assessment: The component/mixture is moderately toxic after short term inhalation.
Skin irritation	:	Species: Rabbit Result: Skin irritation
Eye irritation	:	Species: Rabbit Result: No eye irritation
Repeated dose toxicity	:	Species: Rat NOAEL: 30 mg/kg Application Route: Oral Exposure time: 90 d

Germ cell mutagenicity

Genotoxicity in vitro	:	In vitro gene mutation study in mammalian cells Result: positive Ames test Result: positive Method: OECD Test Guideline 471

Chromosome aberration test in vitro
Result: positive

Genotoxicity in vivo : In vivo micronucleus test
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity : No data available

Reproductive toxicity/Fertility : Species: Rat, male and female
Application Route: Oral
Dose: 0 100, 300, 750, 1000 milligram per kilogram
General Toxicity Parent: NOAEL (No observed adverse effect level): 300 mg/kg bw/day
General Toxicity F1: No observed adverse effect level F1: 300 mg/kg bw/day
Method: OECD Test Guideline 421
GLP: yes

Target Organ Systemic Toxicant - Repeated exposure : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity : No aspiration toxicity classification

12. ECOLOGICAL INFORMATION

PRODUCT INFORMATION:

Ecotoxicology Assessment

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.
Harmful to aquatic life with long lasting effects.

Further information on ecology

Hazardous to the ozone layer

Regulation : 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

COMPONENTS:

Ecotoxicology Assessment

Component: tert-Butyl peroxybenzoate

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

Test result

Component: tert-Butyl peroxybenzoate

Ecotoxicity effects

Toxicity to fish : LC50: 1.6 mg/l
Exposure time: 96 h
Species: Danio rerio (zebra fish)

Toxicity to daphnia and other aquatic invertebrates : EC50: 11 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae : EC10: 0.44 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (green algae)
Test Type: Growth inhibition
Method: OECD Test Guideline 201

ErC50: 0.8 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (green algae)
Test Type: Growth inhibition
Method: OECD Test Guideline 201

M-Factor (Acute) : 1

Toxicity to bacteria : EC50: 43 mg/l
Exposure time: 0.5 h
Species: activated sludge
Test Type: Respiration inhibition
Method: Domestic OECD Guideline 209

Elimination information (persistence and degradability)

Biodegradability : Result: Readily biodegradable.

13. DISPOSAL CONSIDERATIONS

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Hazardous waste
Dispose of contents/container in accordance with local regulation.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not burn, or use a cutting torch on, the empty drum.

Due to the high risk of contamination recycling/recovery is not recommended.
Follow all warnings even after the container is emptied.

14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No.	: UN 3103
Proper shipping name	: Organic peroxide type C, liquid (tert-Butyl peroxybenzoate)
Class	: 5.2
Subsidiary risk	: HEAT
Packing group	: Not Assigned
Labels	: 5.2 (HEAT)
Packing instruction (cargo aircraft)	: 570
Packing instruction (passenger aircraft)	: 570
Environmentally hazardous	: yes

IMDG-Code

UN number	: UN 3103
Proper shipping name	: ORGANIC PEROXIDE TYPE C, LIQUID (tert-Butyl peroxybenzoate)
Class	: 5.2
Packing group	: Not Assigned
Labels	: 5.2
EmS Code	: F-J, S-R
Marine pollutant	: yes (tert-Butyl peroxybenzoate)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	: UN 3103
Proper shipping name	: Organic peroxide type C, liquid : (tert-Butyl peroxybenzoate, 98%)
Class	: 5.2
Packing group	: Not Assigned
Labels	: 5.2
ERG Code	: 146
Marine pollutant	: yes (tert-Butyl peroxybenzoate)
Reportable Quantity	: This product does not contain an environmentally hazardous substance per 49 CFR 172.101, Appendix A.

15. REGULATORY INFORMATION

Notification status

DSL	: YES. All components of this product are on the Canadian DSL
AICS	: YES. On the inventory, or in compliance with the inventory
NZIoC	: YES. On the inventory, or in compliance with the inventory

ENCS	: YES. On the inventory, or in compliance with the inventory
ISHL	: YES. On the inventory, or in compliance with the inventory
KECI	: YES. On the inventory, or in compliance with the inventory
PICCS	: YES. On the inventory, or in compliance with the inventory
IECSC	: YES. On the inventory, or in compliance with the inventory
TCSI	: YES. On the inventory, or in compliance with the inventory
TSCA	: YES. All chemical substances in this product are either listed on the TSCA Inventory or in compliance with a TSCA Inventory exemption.

For explanation of abbreviations, see section 16.

TSCA list

TSCA 5(a)(2)	: No substances are subject to a Significant New Use Rule.
TSCA 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Organic peroxides Acute toxicity (any route of exposure) Skin corrosion or irritation Respiratory or skin sensitization
SARA 302	: This material does not contain any components with a section 302 EHS TPQ.
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals subject to disclosure and listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Benzoic acid	65-85-0	0.1 - 1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Benzoic acid	65-85-0	0.1 - 1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

tert-Butyl peroxybenzoate	614-45-9	90 - 100 %

Pennsylvania Right To Know

tert-Butyl peroxybenzoate	614-45-9	90 - 100 %

New Jersey Right To Know

tert-Butyl peroxybenzoate	614-45-9	90 - 100 %

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

16. OTHER INFORMATION

Full text of H-Statements

H242	:	Heating may cause a fire.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H332	:	Harmful if inhaled.
H400	:	Very toxic to aquatic life.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CAL PEL	:	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2


ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CAL PEL / STEL	:	Short term exposure limit
CAL PEL / PEL	:	Permissible exposure limit
CAL PEL / C	:	Ceiling
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA CARC / STEL	:	Excursion limit
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-2 / CEIL	:	Acceptable ceiling concentration
OSHA Z-2 / Peak	:	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

HMIS Classification : Health Hazard: 2
Flammability: 1
Physical hazards: 3

NFPA Classification : Health Hazard: 2
Fire Hazard: 2
Reactivity Hazard: 3



Notification status explanation

REACH	1907/2006 (EU)
DSL	Canadian Domestic Substances List (DSL)
AICS	Australia Inventory of Chemical Substances (AICS)
NZIoC	New Zealand. Inventory of Chemical Substances
ENCS	Japan. ENCS - Existing and New Chemical Substances Inventory
ISHL	Japan. ISHL - Inventory of Chemical Substances
KECI	Korea. Korean Existing Chemicals Inventory (KECI)
PICCS	Philippines Inventory of Chemicals and Chemical Substances (PICCS)

IECSC	China. Inventory of Existing Chemical Substances in China (IECSC)
TCSI	Taiwan Chemical Substance Inventory (TCSI)
TSCA	United States TSCA Inventory

Further information

Revision Date	03/31/2020

The information in this safety data sheet should be provided to all who will use, handle, store, transport or otherwise be exposed to this product. The user must determine the appropriate measures that need to be implemented for the use and handling of this product in the c ontext of the user's operations and use of this product. The information contained herein supersedes all previously issued bulletins on the subject matter covered. If the date on this document is more than three years old,call to make certain that this sheet is current. No warranty is made as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. User must determine for himself, by preliminary tests or otherwise, the suitability of this product for his purposes, including mixing with other products. Not hing contained herein shall be construed as granting or extending any license under any patent.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.