SPARTAN LED
CID2 SPZ Bulkhead









Intelligent Emergency Variants



Compact Design

The compact, low profile design is ideal for applications where space is restricted.

Robust and Durable

Designed from marine grade aluminium and able to withstand the most extreme environments.

Easy Maintenance

Featuring a unique modular design, key components are easily accessible for straightforward maintenance and inspection.

Intelligent Emergency

Self-testing emergency battery providing up to 3 hours emergency back-up.

5 YEAR WARRANTY

All Raytec luminaires are provided with an industry leading 5 year warranty and have an expected useful life in excess of 10 years. See Warranty Statement for details.

5 YEAR WARRANTY

Raytec Global (excluding Americas): +44 (0) 01670 520055 • sales@raytecled.com
Raytec Americas: +1 613 270 9990 • ushazsales@raytecled.com

Technical Specifications

Certification

UL Rating	UL/CSA Class I Division 2 rated for Gas and Dust
Certification	Class I, Div. 2 Gr ABCD T5 Class II, Div. 1, Div. 2 Gr EFG Tamb" -50˚C to + 55˚C(Standard), or Tamb: -20˚C to + 55˚C (Emergency) Enclosure Type 4X Applicable Standards CSA C22.2 No. 94.2-07 CSA C22.2 No. 25-1996 CSA C22.2 No. 213-2016 CSA C22.2 No. 250.13-14 CSA C22.2 No. 141-15 UL 50E 1st edition ANS/ISA-12.12.01-2015 UL 8750 2nd edition UL 1203 5th edition UL 844 13th edition UL 924 10th edition
File Number	E115626
ABS Certificate #	ABS Certificate #23-2432337-PDA

Electrical

	BL24	BL24-HO	BL24 EMX25	BL24-HO EMX25
Input	110-254V 50/60Hz AC only Low voltage: 18-48V AC and 18-69V DC		110-254V 50/60Hz AC only	
Power	20W	34W	24W	37W
Termination	Incoming terminal block suitable for looping 4 core 4mm² cable (6mm² available - POA)			
Power Factor	>0.9			
Cable Entries	4 x 3/4" NPT as standard (other entries available upon request), dispatched complete with three approved blanking plug			

Optical

	BL24	BL24-HO	BL24 EMX25	BL24-HO EMX25
Beam Patterns - Circular	10°x 10° or 30°x 30° or 50°x 50° or 80°x 80° or 120°x 120° (10°x 10° option can be upgraded to Vario Technology)			
Beam Patterns - Elliptical	35°x 10° or 60°x 25°or 80°x 30° or 120°x 50° (VARIO)			
Lumen output on mains	Up to 2,500 lm – circular beam patterns 2,250 lm – elliptical beam patterns (VARIO)	Up to 4,650 lm – circular beam patterns 4,100 lm – elliptical beam patterns (VARIO)	Up to 2,500 lm – circular beam patterns 2,250 lm – elliptical beam patterns (VARIO)	Up to 4,650 lm – circular beam patterns 4,100 lm – elliptical beam patterns (VARIO)
LED type	Platinum Elite SMT LEDs			
Number of LEDs	24			
CRI	80+			
Colour Temperature	6500K standard			

Mechanical

	BL24	BL24-HO	BL24 EMX25	BL24-HO EMX25
Burning Position	Universal			
IP Rating	NEMA 4X (IP66 & IP67)			
Temperature Range	- 58°F to + 131°F (- 50°C to + 55°C)		- 4°F to + 131°F (- 20°C to + 55°C)	
Weight	11.0lbs (5kg)		13.2lbs (6kg)	
Enclosure	Marine grade aluminium epoxy powder coated, toughened glass, all external fasteners and brackets are marine grade stainless steel			
Unit Colour	Silver (RAL 9006)			
Installation instructions	Please see document 940-M-0033 at www.raytecled.com			
Battery care instructions	Please see document 0010-D-00001 at www.raytecled.com			
Dimensions	See Dimensional Sketches			
Mounting	Comes complete with stainless steel brackets (as shown on next page). Other options available			


Raytec Global (excluding Americas): +44 (0) 01670 520055 • sales@raytecled.com
Raytec Americas: +1 613 270 9990 • ushazsales@raytecled.com


Technical Specifications - Continued

Intelligent Emergency	BL24 EMX25	BL24-HO EMX25
Function	Self-testing intelligent emergency	
System health indicator	Tri-colour LED indicator	
Emergency Duration	Up to 3hrs @ 25% power Other options available	
Emergency Battery	2.5 Ah	
Emergency Charge Time	20 hours	

Product Dimensions

BL24, BL24-EMX







Raytec Global (excluding Americas): +44 (0) 01670 520055 • sales@raytecled.com
Raytec Americas: +1 613 270 9990 • ushazsales@raytecled.com

Product Dimensions - Continued

BL24 Exit Sign






Exit Sign Kit Contents

- 2 max viewing distance indicator labels 150x12mm supplied with each kit
- 2 blanking pieces 150x75mm supplied with each kit
- 6 pre-cut self-adhesive graphics 150x150mm supplied on one sheet as shown

  48 different combinations available

  Other languages available - contact Raytec




Lines for illustration purposes only


Raytec Global (excluding Americas): +44 (0) 01670 520055 • sales@raytecled.com
Raytec Americas: +1 613 270 9990 • ushazsales@raytecled.com
www.raytecled.com

Beam patterns - Circular


10° x 10°




30° x 30°




50° x 50°



80° x 80°




120° x 120°




Beam patterns – Elliptical (VARIO)


35° x 10°




60° x 25°



80° x 30°



120° x 50°



Raytec Global (excluding Americas): +44 (0) 01670 520055 • sales@raytecled.com
Raytec Americas: +1 613 270 9990 • ushazsales@raytecled.com


Part Code Builder

SPARTAN Bulkhead

Example - SPZ-BL24-W-120120-EMX25-CID2									
Family	Model	Light Type	Optic	Emergency	Variant	CCT	Power	Entry	Mounting
SPZ	BL24	W - White Light	120120	NOT STATED - Non EM	CID2	Not Stated - 6500K	Not Stated - Standard Mains	Not Stated - 3/4" NPT	Not stated - Standard Wall Brackets
	BL24-HO		12050	EMX25 (3 hour)		4K - 4000K	LV - Low Voltage (Non EM only)	M25 M20	EXIT - c/w Exit Sign Kit
			1010				LO - Low Output (12W)		
			3030						
			5050						
			8080						
			50120						
			8030						
			6025						
			3510						

*Other options available, please contact Raytec for more information

Products in the SPARTAN Family




SPARTAN Flood



SPARTAN Linear



SPARTAN Bulkhead



SPARTAN Crane

Raytec Global (excluding Americas): +44 (0) 01670 520055 • sales@raytecled.com
Raytec Americas: +1 613 270 9990 • ushazsales@raytecled.com