

EU Type Examination Certificate CML 25ATEX3451 Issue 0

- 1 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU
- 2 Equipment **Spartan High Power Flood / Bay**
- 3 Manufacturer **Raytec Limited**
- 4 Address **Unit 15 Wansbeck Business Park,
Rotary Parkway,
Ashington,
Northumberland,
NE63 8QW**
- 5 The equipment is specified in the description of this certificate and the documents to which it refers.
- 6 Eurofins CML B.V., Chamber of Commerce No 67386717, Koopvaardijweg 32, 4906CV Oosterhout, The Netherlands, Notified Body Number 2776, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in the confidential reports listed in Section 12.
- 7 If an 'X' suffix appears after the certificate number, it indicates that the equipment is subject to conditions of safe use (affecting correct installation or safe use). These are specified in Section 14.
- 8 This EU Type Examination certificate relates only to the design and construction of the specified equipment or component. Further requirements of Directive 2014/34/EU Article 13 apply to the manufacture of the equipment or component and are separately certified.
- 9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the confidential report, has been demonstrated through compliance with the following documents:

EN IEC 60079-0:2018

EN IEC 60079-31:2024

- 10 The equipment shall be marked with the following:



II 2 D

Ex tb IIIC T99°C Db

Ta=-40°C to +60°C

Standard Power

Ta=-40°C to +65°C

Reduced Power

Ta=-40°C to +70°C

Low Power

11 Description

The Spartan High Power Flood / Bay is a hazardous area luminaire. It is rated at a voltage of 110 – 277V or 110 – 254V model dependent. Optionally these models may be operated in a dim mode with a reduced or low power.

It briefly comprises a rectangular aluminium enclosure with a bolted cover. The cover houses a toughened glass window. The front of the enclosure has a separate cover fixed with 4 M6 bolts which houses increased safety terminals. The rear of the enclosure has two separate covers each fixed with 4 M6 bolts; this house encapsulated drivers. All covers are sealed with silicone gaskets.

Beneath the glass window are 4 light engines, each light engine consisting of 96 LEDs arranged in groups of 16. Each group of 16 LEDs are covered by a polycarbonate cover secured to the PCB with silicone adhesive. The light engine PCB is supplied in 4 strings of 24LEDs.

Each luminaire is supplied by encapsulated drivers, they are encapsulated into the rear of the luminaire via 2 driver housings. Optionally the drivers may be mounted remotely via a separate aluminium enclosure. There are 4 different driver models permitted (Universal, Dali, Extended and MP). Each luminaire is supplied by either 2 drivers (MP) or 4 drivers, 2 in each enclosure (Universal, Dali, Extended).

Connection to the luminaire is made via separately certified increased safety terminals, housed within the terminal enclosure at the front of the luminaire. Entry into the terminal enclosure is made via separately certified cable glands.

The luminaire is offered as High Power Flood (HPFL) and High Power Bay (HPBY). The difference in models being the mounting bracket it is supplied with.

Equipment	Type	Model	Light type	Optical Beam Angle	Dust Only	Optional	
						Dali PSU	Remote Mount of PSU
SPZ	HPFL	300 (Full Power)	W * More options available	AAA	-Z21	-DA	-RM
		200 (Reduced Power)					
	HPBY	100 (Low Power)					

12 Certificate history and evaluation reports

Issue	Date	Associated report	Notes
0	06 Aug 2026	R18810A/00	Issue of Prime Certification

Note: Drawings that describe the equipment or component are listed in the Annex.

13 Conditions of Manufacture

The following conditions are required of the manufacturing process for compliance with the certification.

- i. Where the product incorporates certified parts or safety critical components, the manufacturer of the product defined on this certificate shall continually monitor these parts/components for any modifications introduced by the manufacturer(s) of these constituent parts. If the manufacturer of any constituent part introduces any changes which affect the compliance of the certified product that is the subject of this certificate, the manufacturer is required to have this certificate updated.

14 Specific Conditions of Use (Special Conditions)

None

Certificate Annex

Certificate Number CML 25ATEX3451
Equipment Spartan High Power Flood / Bay
Manufacturer Raytec Limited



The following documents describe the equipment or component defined in this certificate:

Issue 0

Drawing No	Sheets	Rev	Approved date	Title
1050-SD-00007	1 to 3	A	06 Aug 2026	Spartan High Power Flood Gen 2
1250-SD-0002	1 to 3	A	06 Aug 2026	PCB Schematic Spartan MPFL Power Supply
	1 to 1	A	06 Aug 2026	
1250-SD-0003	1 to 5	A	06 Aug 2026	FMEA - Spartan MPFL Power Supply
1250-SD-0004	1 to 1	A	06 Aug 2026	Parts List Spartan MPFL Power Supply
1250-SD-0005	1 to 1	A	06 Aug 2026	Thermal fuse positions
SB SD 4 C 145 75 0 R00	1 to 10	0	06 Aug 2026	Safety assessment for LED ECG 4 C 145 75 0
70.03	1 to 7	0	06 Aug 2026	Test Report, Part List No. 4 C 145 75 0, LED Control Gear 7000mA 45 W, 110-254 V
4C 145 75 0 R00	1 to 2	0	06 Aug 2026	LED Control Gear 7000mA 45 W, 110-254 V Bill of Materials
4 S 002 88 0	1 to 3	0	06 Aug 2026	SMD LED Control Gear 700 mA, 45 W, 110-245 V, Bill of Materials
5 a 003 44 1	1 of 1	0	06 Aug 2026	Leitung, Z-Nr.: 7 E 00 187 01 0 Bill of Materials
5 a 003 44 2	1 of 1	0	06 Aug 2026	Leitung, Z-Nr.: 7 E 00 187 01 0 Bill of Materials
5 a 003 44 3	1 of 1	0	06 Aug 2026	Leitung, Z-Nr.: 7 E 00 187 01 0 Bill of Materials
5 a 003 44 4	1 of 1	0	06 Aug 2026	Leitung, Z-Nr.: 7 E 00 187 01 0 Bill of Materials
5 a 003 44 5	1 of 1	0	06 Aug 2026	Leitung, Z-Nr.: 7 E 00 187 01 0 Bill of Materials
1G22020	1 to 3	G	06 Aug 2026	EFD25/16/9 X'Fmer Product Specifications
LED ECG 4 C 145 75 6	1 to 12	E01.6	06 Aug 2026	Safety assessment for LED ECG 4 C 145 75 6
BOM 4C 145 75 6	1 of 1	0	06 Aug 2026	LED Control Gear 7000mA 45 W, 110-277 V DALI Bill of Materials
BOM 4B 145 75 6	1 of 1	0	06 Aug 2026	LED Control Gear 7000mA 45 W, 110-277 V DALI Bill of Materials

Certificate Annex

Certificate Number CML 25ATEX3451
Equipment Spartan High Power Flood / Bay
Manufacturer Raytec Limited



Drawing No	Sheets	Rev	Approved date	Title
4 S 003 53 0	1 to 3 of 4	0	06 Aug 2026	SMD LED Control Gear 700 mA, 45 W, 110-277 V DALI Bill of Materials
LED ECG 4 C 145 75 1	1 to 11	E01.4	06 Aug 2026	Safety assessment for LED ECG 4 C 145 75 1
4C 145 75 1	1 to 2	E01.4	06 Aug 2026	LED Control Gear 700 mA, 45 W, 110-277 V Bill of Materials
4 S 002 88 1	1 to 3	E01.4	06 Aug 2026	SMD LED Control Gear 700 mA, 45 W, 10- 277V Bill of Materials