Product Information

Item 3923 | HHB24090

MAFFIOLETTI

HHB24090

Industrial heating jacket

Best for: faster liquid heating, viscosity reduction and low melt point materials.



- Fast, efficient heating for applications up to approximately 60-70°C.
- Wrap-around jacket with retaining straps and quick-release buckles for simple fitting.
- Suitable for liquids and low-melting solids where a faster heat-rate is needed.
- Easy to adjust analogue thermostat with 0-90ºC range
- Indoor use. May be used outdoors with additional manufacturer supplied cover
- FR-rated polyester outer fabric with silicone-coated glass cloth inner and high-density fibreglass insulation.
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities
- Custom sizes available

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	50L (B)
CORD LENGTH	5m
AMBIENT TEMPERATURE	-20ºC to +40ºC
INDICATIVE HEATING RATE †	8-12ºC/hr
WIDTH / HEIGHT	460 mm
POWER	400 W

IP RATING	IP 54
THERMOSTAT	0-90°C *
APPROVALS	CE, UKCA
ADJUSTABLE CIRCUMFERENCE	1100-1250 mm
VOLTAGE	240V
NET WEIGHT	2.3 kg

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.

* Heater may not be able to reach maximum thermostat temperature