Product Information

Item 1912 | HPD2240160

MAFFIOLETTI

HPD2240160

Industrial heating jacket

Best for: Higher temperature processes, difficult to heat products and melting solids



- Maximum power and insulation to reach highest temperatures
- Wrap-around jacket with retaining straps and quick-release buckles for simple fitting.
- Suitable for high-temperature or hard-to-heat products and demanding industrial use.
- Easy to adjust analogue thermostat with 0-160ºC range
- Indoor use. May be used outdoors with additional manufacturer supplied cover
- Silicone-coated glass cloth outer fabrics with high-density fibreglass insulation.
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities
- Custom sizes available

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	200L (D)	IP RATING	IP 54
CORD LENGTH	5m	THERMOSTAT	0-160°C *
AMBIENT TEMPERATURE	-20ºC to +40ºC	APPROVALS	CE, UKCA
INDICATIVE HEATING RATE †	7-11ºC/hr	ADJUSTABLE CIRCUMFERENCE	1800-1950 mm
WIDTH / HEIGHT	850 mm	VOLTAGE	240V
POWER	2x 1030 W	NET WEIGHT	9.2 kg

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.

* Heater may not be able to reach maximum thermostat temperature