Product Information

Item 1965 | 640L IBC Heating Jacket

MAFFIOLETTI

640L IBC Heating Jacket

Industrial heating jacket

Best for: faster liquid heating, viscosity reduction and low melt point materials.



- Designed for IBC/tote bulk storage heating of liquids and low-melting-point solids.
- Useful for viscosity reduction, gentle warming and anti-freeze/crystallisation applications.
- Ideal for customers requiring liquids to be heated rapidly and as evenly as possible up to around 60-70ºC
- Easy to adjust analogue thermostat with 0-90ºC range
- Indoor use. May be used outdoors with additional manufacturer supplied cover
- FR-rated polyester outer fabric with silicone-coated glass cloth inner and high-density fibreglass insulation.
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	640L IBC
CORD LENGTH	5m
AMBIENT TEMPERATURE	-20ºC to +40ºC
INDICATIVE HEATING RATE †	1-3ºC/hr
WIDTH / HEIGHT	850 mm
POWER	1750 W

IP RATING	IP 54
THERMOSTAT	0-90°C *
APPROVALS	CE, UKCA
ADJUSTABLE CIRCUMFERENCE	3750-4000 mm
VOLTAGE	240V
NET WEIGHT	10.5 kg

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.

* Heater may not be able to reach maximum thermostat temperature