Product Information

Item 1111 | HHG24090

MAFFIOLETTI

HHG24090

Industrial heating jacket

Best for: frost protection, flow improvement



- Fast, efficient heating for applications up to approximately 60-70°C.
- Wrap-around jacket with retaining straps and quick-release buckles for simple fitting.
- Helps maintain gas cylinder flow by warming cylinders containing liquefied gas. Can help prevent frosting and improve stability of gas delivery rates.
- Easy to adjust analogue thermostat with 0-90ºC range
- Indoor use. May be used outdoors with additional manufacturer supplied cover
- FR-rated polyester outer fabric with silicone-coated glass cloth inner and high-density fibreglass insulation.
- Safe to use 24 hours per day

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	Gas Size K (G)
CORD LENGTH	5m
AMBIENT TEMPERATURE	-20ºC to +40ºC
ADJUSTABLE CIRCUMFERENCE	685-830 mm
VOLTAGE	240V
NET WEIGHT	2.9 kg

IP RATING	IP 54
THERMOSTAT	0-90°C *
APPROVALS	CE, UKCA
WIDTH / HEIGHT	1060 mm
POWER	450 W

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.

* Heater may not be able to reach maximum thermostat temperature