Product Information

Item 1917 | IHF-R/A/T4 90W ATEX Heating Jacket w/Control

MAFFIOLETTI

IHF-R/A/T4 90W ATEX Heating Jacket w/Control

Hazardous area heating jacket

Best for: frost protection, viscosity reduction and temperature maintenance.



- Hazardous-area heating jacket with temperature regulator/control for process temperature management.
- Wrap-around jacket with retaining straps and quick-release buckles for simple fitting.
- Low power for gentle heating up to 40-50C. Fitted with temperature control
- Fitted with adjustable temperature control
- Indoor use only
- Silicone-coated glass cloth outer fabrics with high-density fibreglass insulation.
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities
- Custom sizes available

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	25L (A)	IP RATING	IP 54
CORD LENGTH	5m	THERMOSTAT	0-50°C *
AMBIENT TEMPERATURE	-20ºC to +40ºC	APPROVALS	CE, UKCA, ATEX, IECEx.
INDICATIVE HEATING RATE †	5-10ºC/hr	ADJUSTABLE CIRCUMFERENCE	870-1020 mm
WIDTH / HEIGHT	400 mm	VOLTAGE	240V
POWER	90 W	NET WEIGHT	4.7 kg
EX MARKINGS	II 2 G D Ex eb IIC T4 Gb Ex tb IIIC T135°C Db (Zones 1, 2, 21 and 22)		

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.

* Heater may not be able to reach maximum thermostat temperature