Product Information

Item 2505 | IHF/D/T4 540W ATEX Heating Jacket

MAFFIOLETTI

IHF/D/T4 540W ATEX Heating Jacket

Hazardous area heating jacket

Best for: frost protection, viscosity reduction and temperature maintenance.



- For hazardous area use; self-limiting or controlled Ex heating jacket design.
- Suitable for ATEX/IECEx/UKEX hazardous areas where certified heating is required.
- Low power for gentle heating up to 50ºC above ambient temperature
- Indoor use only
- Silicone-coated glass cloth outer fabrics with high-density fibreglass insulation.
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities
- Custom sizes available

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	200L (D)	IP RATING	IP 54
CORD LENGTH	5m	AMBIENT TEMPERATURE	-20ºC to +40ºC
APPROVALS	CE, UKCA, ATEX, IECEx.	INDICATIVE HEATING RATE †	2-4ºC/hr
ADJUSTABLE CIRCUMFERENCE	1800-1950 mm	WIDTH / HEIGHT	850 mm
VOLTAGE	240V	POWER	540 W
NET WEIGHT	7.8 kg		
EX MARKINGS	II 2 G D Ex eb IIC T4 Gb Ex tb IIIC T135°C Db (Zones 1, 2, 21 and 22)		

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.