

Product Information

Item 1902 | IHF/G/T4 100W ATEX Heating Jacket



IHF/G/T4 100W ATEX Heating Jacket

Hazardous area heating jacket

Best for: frost protection, viscosity reduction and temperature maintenance.



- For hazardous area use; self-limiting or controlled Ex heating jacket design.
- Suitable for ATEX/IECEx/UKEX hazardous areas where certified heating is required.
- Low power for gentle heating up to 30°C above ambient temperature
- Indoor use only
- Silicone-coated glass cloth outer fabrics with high-density fibreglass insulation.
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities
- Custom sizes available

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	Gas Size K (G)	IP RATING	IP 54
CORD LENGTH	5m	AMBIENT TEMPERATURE	-20°C to +40°C
APPROVALS	CE, UKCA, ATEX, IECEx.	ADJUSTABLE CIRCUMFERENCE	685-830 mm
WIDTH / HEIGHT	1060 mm	VOLTAGE	240V
POWER	100 W	NET WEIGHT	4.7 kg
EX MARKINGS	II 2 G D Ex eb IIC T4 Gb Ex tb IIIC T135°C Db (Zones 1, 2, 21 and 22)		

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.