

Product Information

Item 1906 | IHF-R/G/T4 100W ATEX Heating Jacket w/Control



IHF-R/G/T4 100W ATEX Heating Jacket w/Control

Hazardous area heating jacket

Best for: frost protection, viscosity reduction and temperature maintenance.



- Hazardous-area heating jacket with temperature regulator/control for process temperature management.
- Wrap-around jacket with retaining straps and quick-release buckles for simple fitting.
- Low power for gentle heating up to 40-50°C. Fitted with temperature control
- Fitted with adjustable temperature control
- Indoor use only
- Silicone-coated glass cloth outer fabrics with high-density fibreglass insulation.
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities
- Custom sizes available

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	Gas Size K (G)	IP RATING	IP 54
CORD LENGTH	5m	THERMOSTAT	0-50°C *
AMBIENT TEMPERATURE	-20°C to +40°C	APPROVALS	CE, UKCA, ATEX, IECEx.
ADJUSTABLE CIRCUMFERENCE	685-830 mm	WIDTH / HEIGHT	1060 mm
VOLTAGE	240V	POWER	100 W
NET WEIGHT	6.7 kg		
EX MARKINGS	II 2 G D Ex eb IIC T4 Gb Ex tb IIIC T135°C Db (Zones 1, 2, 21 and 22)		

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.

* Heater may not be able to reach maximum thermostat temperature