Product Information

Item 1661 | THA Type A THERMOSAFE Induction Drum Heater

MAFFIOLETTI

THA Type A THERMOSAFE Induction Drum Heater

THA Type A THERMOSAFE
Induction Drum Heater

Combine with Faratherm base heater for melting of solids



- Fast induction heating of steel drums for liquids, powders and melting solids.
- Useful for fast heating and melting in hazardous areas; efficient and maintenance-free.
- Can typically heat the drum wall up to 120ºC (20ºC ambient)
- Combine with Faratherm base heater for melting of solids
- Outdoor use
- Rigid GRP IP66 construction
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	200L (D)	IP RATING	IP 66
CORD LENGTH	5m	AMBIENT TEMPERATURE	-20ºC to +40ºC
APPROVALS	CE, UKCA, ATEX, IECEx.	INDICATIVE HEATING RATE †	10-15ºC/hr
WIDTH / HEIGHT	711 mm	VOLTAGE	240V
POWER	2750 W	NET WEIGHT	48 kg
EX MARKINGS	II 2 GD Ex eb IIC T170°C (T3) Gb Ex tb IIIC T170°C Db (For use in Zones 1, 2, 21 and 22)		

† Typical heating rate for a light oil in a standard container. Actual performance depends on product, fill level, container type and site conditions.