



THERMOSAFE® Type B Induction Heater

Uses the same technology as the proven Thermosafe Type A Induction Heater

Lighter and easier to handle, ideal where height is restricted

2 heaters can be stacked to heat full height of drum

110v operation



To complement the longstanding and successful 240v Thermosafe Type A, our 110v Type B model is available, ideal where height is restricted, or for heating smaller containers. Two Type B heaters can also be stacked and operated at 110v or 240v.

A single Type B heater can heat the lower section of a 200L steel drum to around 110C. Two heaters can be stacked to enable the full height of the drum to reach approximately these temperatures.

Just like the Thermosafe Type A, the Type B is suitable for use in hazardous areas, certified to ATEX and IECEx standards (zones 1 and 2).



PRODUCT SPECIFICATION

Single Phase up to 120v, 50/60Hz ac

Current / power consumption: 23A / 1500W

Class II Appliance

Ingress Protection IP66

Hazardous Area Certification.

Standards: EN 60079-0:2004, EN 60079-7:2003, EN 31241-0:2006, EN61241-1:2004

EC-Type Examination Certificate Number: Sira 08ATEX3101X

IECEx Examination Certificate Number: IECEx SIR 08.0037X

Ex II 2 GD Ex e II T3 Ex tD A21 T200C (Zones 1 and 2)

Overall diameter: 743mm

Internal diameter: 610mm

Overall height: 425mm

Weight: 30kg