Product Information

Item 1659 | FARATHERM Induction Base Heater ATEX / IECEx / UKCA

MAFFIOLETTI

FARATHERM Induction Base Heater ATEX / IECEx / UKCA

Hazardous area base heater

NOT CERTIFIED FOR USE WITH IHF HEATING JACKETS



- Induction base heater to warm the base of drums and containers.
- Can be used alone for low-temperature heating or with Thermosafe to improve melting times.
- ATEX / IECEx / UKEx certified
- NOT CERTIFIED FOR USE WITH IHF HEATING JACKETS
- Outdoor use
- Double-insulated induction base heater with chemically resistant IP66 surfaces.
- Safe to use 24 hours per day
- Manufactured in ISO9001 approved facilities

TECHNICAL SPECIFICATIONS

CONTAINER SIZE	200L (D)	IP RATING	IP 66
CORD LENGTH	5m	AMBIENT TEMPERATURE	-20ºC to +40ºC
APPROVALS	CE, ATEX, IECEx, UKEX.	INDICATIVE HEATING RATE †	Varies depending on use
WIDTH / HEIGHT	743 mm	VOLTAGE	240V
POWER	500 W	NET WEIGHT	45 kg
EX MARKINGS	II 2 G D Ex eb IIC T3 Gb Ex tb IIIC T200°C Db (zones 1, 2, 21 and 22)		