Datasheet
SLAM Extension Cable 16Ex

Designed for High Temp Areas

Manufacturing date	9.10.2014 -
ATEX marking	Ex II 2 G Ex de IIC T4 Gb Ex II 2 D Ex tb IIIC T120°C Db
Product description	Explosion protected portable extension cable
Temperature classification	T4 (internal) T120 °C (external)
Operating temperature	-20°C … +55°C
Supply Voltage (min-max)	12 V, 24V, 42V, 110V, 230V +/- 6%
Supply Current typical	Max. 16A
Electrical class	110-230V Class I, 12-42V Class 3
Maximum load	230V 3680W 110V 1760W 42V 672W 24V 384W 12V 192W
Cable	Orange H07BQ-F black H07BN4-F, H07RN-F, H-FLEX From 5m up to 25m
Plug and mobile socket options	ATX, CEAG, Stahl, Marechal
Ingress protection	IP66
Warranty	You will find detailed warranty conditions from www.atexor.com/downloads/warranty



Made in Finland by ATEXOR Oy
Tel: +358 207 343250, E-mail: info@atexor.com www.atexor.com
5/04/2024

ATEXOR Oy prepared this information herein in good faith but makes no representation as to its comprehensiveness or accuracy. ATEXOR Oy reserves the right to make changes to specifications and product descriptions at any time without notice. Ask for more technical data from our sales support.