

|                        |                                                                                                                                              |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| MODEL                  | MLC                                                                                                                                          |
| Product description    | Single vehicle charger                                                                                                                       |
| Certification          | e17*72/245*2006/28*0108*02                                                                                                                   |
| Input voltage          | 12 ... 24VDC                                                                                                                                 |
| Charging temperature   | 0°C ...+40°C                                                                                                                                 |
| Charge current         | 350mA                                                                                                                                        |
| Trickle charge current | 100mA                                                                                                                                        |
| Enclosure              | High impact Nylon/Aluminium                                                                                                                  |
| Weight                 | 170 g                                                                                                                                        |
| Dimensions             | 142 x 83 x 72 mm                                                                                                                             |
| Mounting               | Wall mounted vertical or horizontal                                                                                                          |
| Compatible product     | ML-600, ML-601, ML-602, ML-808 ATEX                                                                                                          |
| Charging time          | 5 h 30 min: ML-600, ML-808 ATEX<br>4 h: ML-601, ML-602                                                                                       |
| Charging features      | Sophisticated charge and battery protection                                                                                                  |
| Accessories            | MICA IL-2 mains adapter, order code IL_2<br>MICA supply cable 12-30VDC, order code M01113<br>MICA cigarette lighter cable, order code M01112 |

