



Headset

SM1P series

SM1PBWEXPFO1 ATEX / INMETRO

- SENS® Technology - remain aware of surrounding noises and hazards
- Clear two-way radio communication in high-noise environments
- Compatible with two-way radios and ecom mobile devices via Bluetooth®
- Bluetooth cellular connection for conversation and audio streaming (HFP, HSP and A2DP profiles)
- Improved Short Range with VOX capabilities and additional channel banks for headset-to-headset communications

SM1P, Headband, Zone 1/21, with Bluetooth



Technical Data

General specifications

Description	Headband
-------------	----------

Hardware

Microphone	Boom microphone noise cancelling
------------	-------------------------------------

Electrical specifications

Battery type	Li-ion Rechargeable 2250 mAh
Charging time	4 h
Operating duration	18 h

Communication

Bluetooth	Bluetooth® 3.0 HFP (8 KHz and 16 KHz), HSP, A2DP Range: 15 m
Connections	SENS® 360° Situational Awareness: 95 dB(A) Half-duplex communications, Up to 8 programmable FM channels, Up to 50 meters

Ambient conditions

Charging temperature	0 ... 40 °C (32 ... 104 °F)
----------------------	-----------------------------

Mechanical specifications

Degree of protection	IP54
Mass	495 g

Data for application in connection with hazardous areas

ATEX approval	
ATEX certificate	Baseefa18ATEX0049X
ATEX marking	Ⓔ I M2 Ex ib I Mb (-20°C to +60°C) Ⓔ II 2G Ex ib IIC T4 Gb (-20°C to +40°C) Ⓔ II 2D Ex ib IIC T155°C Db (-20°C to +40°C)

International approvals

IECEX approval	
IECEX certificate	IECEX BAS 18.0035X
IECEX marking	Ex ib I Mb (-20°C to +60°C) Ex ib IIC T4 Gb (-20°C to +40°C) Ex ib IIC T155°C Db (-20°C to +40°C)
UKCA approval	
UKCA certificate	BAS23UKEX0020X

Release date: 2026-03-11 Date of issue: 2026-03-11 Filename: 70110932_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0002
pa-info@us.pepperl-fuchs.com

Germany: +49 621 776 2222
pa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
pa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

UKCA marking		Ⓢ I M2 Ex ib I Mb (-20°C to +60°C) Ⓢ II 2G Ex ib IIC T4 Gb (-20°C to +40°C) Ⓢ II 2D Ex ib IIC T155°C Db (-20°C to +40°C)
INMETRO approval		
INMETRO certificate		DNV 23.0209 X/00
INMETRO marking		Ex ib I Mb (-20°C to +60°C) Ex ib IIC T4 Gb (-20°C to +40°C) Ex ib IIC T155°C Db (-20°C to +40°C)
Approved for		Mining

Technical Features

Hearing Protection

Volume limiter	82 dB(A) [programmable] - only applicable when the headset is powered on.		
Region	Australia / New Zealand	USA / Canada	Europe
Standard	AS/NZS 1270	ANSI S3.19	EN352-1/EN352-3
Result	SLC80	NRR	SNR
SM1P-EX / -IS (HB)	31 dB, Class 5	27 dB	33 dB
SM1P-EX / -IS (BTN)	27 dB, Class 5	24 dB	30 dB
SM1P-EX / -IS (HM)	26 dB, Class 5	23 dB	31 dB
SM1P-EXDP (HM)	30 dB, Class 5	36 dB	38 dB
SM1P-ISDP (HM)	30 dB, Class 5	36 dB	38 dB

HB = Headband, BTN = Behind-the-neck, HM = Helmet mount

Accessories

Accessories for this product can be found on the internet at www.pepperl-fuchs.com.