Leading the way in hazardous area static control

Application Spotlight



Online Enquiry >

NewsonGale
HOERBIGER Safety Solutions

Sole-Mate™ II
Test Plant Personnel's Footwear - Don't be in for a Shock

Through their own movement people can generate large amounts of static charge if they are not grounded. Over 30,000 volts can be carried by people who are completely unaware that they themselves are the potential source of an electrostatic spark discharge that could ignite a flammable atmosphere. Discharges of static electricity have been identified as an ignition source for a broad range of processes that cut right across a wide selection of industry groups with both plant equipment and personnel based operations.

Sole-Mate™ II Test Plant Personnel's Footwear - Don't be in for a Shock

Static charge accumulation on workers can be mitigated by issuing them with footwear that is designed in accordance with EN ISO 20345 and ASTM F2413 safety standards or recommended practice documents like IEC TS 60079-32-1 and NFPA 77 that incorporate static dissipative properties in the structure of the footwear.

Static dissipative footwear is designed to mitigate hazards that may arise due to excessively high footwear resistance with respect to ground. Regular testing of static dissipative footwear is strongly recommended to ensure the static dissipative properties of the shoes do not change during the duration of their use. The provision of footwear to plant personnel only reduces the risk if properly maintained, and this cannot be detected by visual inspection of the shoes alone. It should therefore be a fundamental requirement of organisations that have employees handling flammable and combustible materials in hazardous environments to ensure that the product is capable of fulfilling its designed function of dissipating electrostatic charges. There is an obligation to perform electrical resistance tests via in-house footwear testers.

The Sole-Mate™ II tester from Newson Gale provides a time efficient and cost effective method of ensuring personnel operating in hazardous areas are wearing static dissipative shoes that are capable of mitigating electrostatic charge accumulation on their bodies. The system tests the condition by checking the resistance of the footwear to ensure static is capable of dissipating from personnel through their shoes to ground.



IEC TS 60079-32-1, 11.3 "Dissipative and conductive footwear" states:

"Resistances can be measured with commercially available footwear conductivity testers which measure the resistance between a hand-held metal bar via body and feet to a metal plate on which the person stands. Alternatively, the resistance between a shoe filled with shot pellets and a steel plate on which the shoe is pressed can be measured according to IEC TS 61340-4-3.

The resistance of footwear can increase with the accumulation of debris on the footwear, use of orthopaedic insoles, and reduced floor contact area. The conductivity of footwear should be tested frequently to confirm functionality."

** Always check for and read the latest version of the International Standards, Guidance and/or Recommended Practices.*



Sole-Mate™ II Test Plant Personnel's Footwear - Don't be in for a Shock

The Sole-Mate II testing station is typically located at the entrance to a hazardous area and plant personnel are provided with a quick 'pass' or 'fail' reading instantly. If the resistance of the shoes is too high, the Sole-Mate II tester will indicate that the shoes have failed the test via a red LED and buzzer alarm. If the shoes pass the test a green LED will indicate to the operator that the shoes are fit for purpose. For those companies that want to interlock the system to certain areas of their facility with entry access or audible alarms, an integral volt free relay contact makes it possible for the system to prevent access to a hazardous area without a pass reading on the tester, indicating that only suitable footwear is being worn upon entry.

It is not uncommon to find that footwear fails; after-all that is what the tester is designed to do. If footwear fails due to conditions – these present a risk as it indicates there is not a dissipative path through the person to ground to the required standard (for example, EN ISO 20345) and this presents a risk to operators and other plant personnel on site.

It is important to consider factors that could affect the resistance between the test button and foot plate. The electrical resistance of static dissipative footwear can be changed significantly by a number of factors such as (to name a few):

1. New footwear – new shoes can have a slightly higher resistance due to the material coating on the sole. Once the footwear has been worn in, typically a pass is registered.

2. Coated footwear – common in the coatings industry where the Sole-Mate II test is vital, a build-up of paints or coatings on the sole of the shoe regularly occurs. Again, a cleaner sole will usually give off a lower resistance.

3. Insulating inner sole – although a common occurrence in everyday footwear, the inserting of an inner sole isolates the body of the individual from the shoes. Only safety footwear inner soles should be used.

4. Wrong certification – if shoes manufactured in accordance with EN ISO 20345 are tested on a footwear tester designed to test shoes at NFPA 77 recommended practice, there is a strong possibility that the tester will fail the shoes.

The Sole-Mate II footwear tester is just part of the static grounding and bonding equipment available from Newson Gale. Newson Gale offers a wide range of static grounding and bonding equipment which is made to provide optimum safety in explosive atmospheres for a variety of process applications. The Newson Gale range mitigates static charge accumulation by using practical and innovative design, and ensures effective static control on three levels – grounding and bonding clamps, visual verification systems and interlockable control systems.



Copyright Notice
The website and its content is copyright of Newson Gale Ltd © 2021. All rights reserved.

Any redistribution or reproduction of part or all of the contents in any form is prohibited other than the following:

- you may print or download to a local hard disk extracts for your personal and noncommercial use only
- you may copy the content to individual third parties for their personal use, but only if you acknowledge the website as the source of the material

You may not, except with our express written permission, distribute or commercially exploit the content. Nor may you transmit it or store it in any other website or other form of electronic retrieval system.

Right to change
This document provides general information only and may be subject to change at any time without notice. All information, representations, links or other messages may be changed by Newson Gale at any time without prior notice or explanation.

Newson Gale is not obliged to remove any outdated information from its content or to expressly mark it as being outdated. Please seek the advice of professionals as necessary regarding the evaluation of any content.

Disclaimer of liability
The information provided in this Application Spotlight is provided by Newson Gale without any representations or warranties, expressed or implied, as to its accuracy or completeness. The liability of Newson Gale for any expenses, losses or actions incurred whatsoever by the recipient as a result of the use of this Application Spotlight shall be excluded.

United Kingdom
Newson Gale Ltd
Omega House
Private Road 8
Colwick, Nottingham
NG4 2JX, UK
+44 (0)115 940 7500
groundit@newson-gale.co.uk

United States
IEP Technologies LLC
417-1 South Street
Marlborough, MA 01752
USA

+1 732 961 7610
groundit@newson-gale.com

Deutschland
IEP Technologies GmbH
Kaiserswerther Str. 85C
40878 Ratingen
Germany

+49 (0)2102 58890
erdung@newson-gale.de

NG UK AS06 SM 181121 R4